

EV14-P47B-Q

Share

StrongHold™ Pin Terminal, vinyl insulated, 16 - 14 AWG, .49 pin length.

Find A Distributor

Qty Add to Bom

Specifications Packaging Detail Resources Related Products Top of Page

Specifications

Package Type	Bag
Base Material	Copper
Insulation Material	Vinyl
Seam Type	Butted Seam
Overall Length (In.)	0.97
Overall Length (mm)	24.6
Color	Blue
Maximum Operating Temperature (°C)	105
Maximum Operating Temperature (°F)	221
Pin Length (In.)	0.49
Pin Length (mm)	12.4
Wire Strip Length (In.)	5/16
Wire Strip Length (mm)	7.9
Finish/Coating	Tin-Plated
Maximum Voltage (V)	600
Standards Met	UL
For Use With	CT-100A, CT-260, CT-1550, CT-1551, CT-2300/ST with CD-550, CT-2500/L with CT-2550CH
Barrel Configuration	Funnel Entry
Flammability Rating	V0
Insulation Diameter (In.)	0.17
Insulation Diameter (mm)	0.2
Maximum Wire Insulation Diameter (mm)	4.3
Part Number Series	PV
RoHS Compliancy Status	Compliant
Min. Order Qty.	25

Packaging Detail

UPC	61305636713
Std. Pkg. Qty.	25
Std. Pkg. Volume (cf)	0.0103
Std. Ctn. Qty.	250
Std. Ctn. Volume (cf)	0.1031

Resources

Part Drawings	Vinyl Pin Terminal 22-10 awg	US English	View PDF (569.96KB) Download PDF Share PDF

Related Products



P10-P55-D

Pin Terminal, 12 10 AWG, non-insulated, .55 pin length, bulk package.



P10-P55-L

Pin Terminal, 12 10 AWG, non-insulated, .55 pin length, standard package.



P14-P47-C

Pin Terminal, 16 14 AWG, non-insulated, .49 pin length, standard package.

Copyright 2019 Panduit

Legal Information Privacy Policy Unsubscribe