PV14-P47-E

Share

Loose Piece Terminal

Pin Terminal, 16 14 AWG, vinyl insulated, .49 pin length, convenience package.

Find A Distributor

Qty Add to Bom

Specifications Packaging Detail Resources Related Products Top of Page

Specifications

Package Type	Bag
Base Material	Copper
Insulation Material	Vinyl
Pin Length (In.)	0.49
Pin Length (mm)	12.4
Finish/Coating	Tin
Wire Range In. (mm^2)	16 - 14 AWG (1.5 - 2.5)
Barrel Configuration	Standard
Barrel Type	Brazed Seam
Color Code	Blue
Plating Type	Tin
Part Number Series	PV
Stock In. (mm)	0.03 (0.8)
Width In (mm)	0.07 (1.8)
Wire Strip Length In. (mm)	5/16 (7.9)
Flammability Rating	UL94-V0
Maximum Output Voltage (V)	600.0
Temperature Rating	221 Degrees Fahrenheit (105 Degrees Celsius)
CA-800/EZ Series Crimp Die	NA
CSA Certified	No
UL Listed	UL486A/B
Insulation Diameter (In.)	0.17
Insulation Diameter (mm)	4.3
Part Features	Solid pin designed to prevent damage to the wire from over tightening, resulting in a reliable electrical connection Insulation support helps to prevent wire damage in bending applications Internal barrel serrations assure good wire contact and maximum tensile strength
RoHS Compliancy Status	Compliant
Min. Order Qty.	20

Packaging Detail

UPC	07498336423
Std. Pkg. Qty.	20
Std. Pkg. Volume (cf)	0.0141
Std. Ctn. Qty.	100
Std. Ctn. Volume (cf)	0.0705

Resources

Selection Guides	Terminal Tools Selection Guide	US English	View PDF (76.9KB) Download PDF Share PDF
Selection Guides	Convenience Pack Terminals - WW-TMFL05	US English	View PDF (494.9KB) Download PDF Share PDF

Related Products

P10-P55-D

Pin Terminal, 12 10 AWG, non-insulated, .55 pin length, bulk package.

P10-P55-L

Pin Terminal, 12 10 AWG, non-insulated, .55 pin length, standard package.

P14-P47-C

Pin Terminal, 16 14 AWG, non-insulated, .49 pin length, standard package.

Copyright 2019 Panduit