PLC1M-S4-M

Share

Cable Ties

Pan-Ty® locking clamp tie, miniature cross section, #4 (M2.5) screw, 4.3 (109mm) length, nylon 6.6, natural, bulk package.

Find A Distributor

Qty Add to Bom

Specifications Packaging Detail Resources Related Products Top of Page

Specifications

Minimum Loop Tensile Strength (N)	80
Minimum Loop Tensile Strength (lb)	18
Material	Nylon 6.6
Color	Natural
Environment	Plenum
Application	General
BMEcat - Cross section (mm^2)	Miniature
Locking Style	Locking
Plenum-Rated	Yes, AH-2
Thickness In (mm)	0.04 (1.1)
Width In (mm)	0.10 (2.5)
CE Compliant	Yes
CSA Certified	Yes
UL 62275 Compliant (Type 1, 11)	No
UL 62275 Compliant (Type 2, 21)	Yes
UL Listed (File #E56854)	Yes
UL Recognized (File #E56854)	Yes
Continuous Use Temperature Range	-76°F (-60°C) - 185°F (85°C)
Maximum Bundle Diameter (In.)	0.75
Part Features	Used to secure a cable bundle to another surface such as a control panel, communication rack, wall or ceiling.
Thickness (mm)	1.1
RoHS Compliancy Status	Compliant
Min. Order Qty.	1,000

Packaging Detail

UPC	07498355041
Std. Pkg. Qty.	1000
Std. Pkg. Volume (cf)	0.0777
Std. Ctn. Qty.	50000
Std. Ctn. Volume (cf)	3.8849

Resources

Selection Guides	Cable Ties Product Selection Guide: CTSG05-SA-ENG	US English	View PDF (1.24MB)	Download PDF	Share PDF
Part Drawings	#D STP Drawing PLC1M-S4	US English	View STP (279.63KB)	Download STP	Share STP
Part Drawings	PAN-TY Clamp Tie: SS-2724	US English	View PDF (64.85KB)	Download PDF	Share PDF

Related Products

PLT2S-M76

Pan-Ty® locking cable tie, standard cross section, 7.4 (188mm) length, TEFZEL, aqua, 1000 pc.

PLT4H-TL0

Pan-Ty® locking tie, light-heavy cross section, 14.5 (368mm) length, weather resistant nylon 6.6, black, bulk package.

PLT4S-M0

Pan-Ty® locking tie, standard cross section, 14.5 (368mm) length, weather resistant nylon 6.6, black, bulk package.

Copyright 2019 Panduit