



Keyword, Part Number or Cross-Reference

[All Products](#)[Solutions](#)[Support](#)

Bill of Materials

[Home](#) / [Products](#) / [Wire Routing, Management & Protection](#) / [Cable & Wire Ties, Mounts & Straps](#) / [Cable & Wire Ties](#) / [PLT.7M-M](#)



PLT.7M-M

Share

Cable Tie

Pan-Ty® locking tie, miniature cross section, 3.1 (79mm) length, nylon 6.6, natural, bulk package.

Find A Distributor

Qty

Add to Bom

[Specifications](#)[Packaging Detail](#)[Resources](#)[Related Products](#)[Top of Page](#)

Specifications

Product Type	Cable Tie
Color	Natural
Environment	Indoor
Sub Brand	Pan-Ty®
For Use With	GTS-E, GS2B-E, PTS
Material	Nylon 6.6
Resistance Properties	NA
Maximum Bundle Diameter (In.)	0.68
Maximum Bundle Diameter (mm)	17.3
Maximum Installation Temperature (°F)	32
Maximum Operating Temperature (°C)	85
Maximum Operating Temperature (°F)	185
Minimum Bundle Diameter (In.)	0.03
Minimum Bundle Diameter (mm)	0.8
Minimum Installation Temperature (°C)	-20

(°C)	
Minimum Installation Temperature (°F)	-4
Minimum Loop Tensile Strength (lb)	18
Minimum Loop Tensile Strength (N)	80
Minimum Operating Temperature (°F)	-76
Minimum Operating Temperature (°C)	-60
Overall Length (mm)	79
Overall Length (In.)	3.1
Body Width (mm)	2.3
Body Width (In.)	0.09
Body Thickness (mm)	0.8
Body Thickness (In.)	0.032
Standards Met	UL Recognized (File #E56854), UL 62275 Compliant (Type 2, 21), RoHS Complaint
Part Features	One-piece locking wedge for consistent performance and reliability. Low thread force and high loop tensile strength.

Packaging Detail

UPC	07498352600
Std. Pkg. Qty.	1000
Std. Pkg. Volume (cf)	0.0361
Std. Ctn. Qty.	50000
Std. Ctn. Volume (cf)	1.8029

Resources


NOTE: Not all resources are available in your language.
If product info is not displayed in your selected language, it will be coming. We will continue to improve the experience over time.

Language

All

Part Drawings	PAN-TY Cable Tie - PLT Series: SS-5540 Sheet 1	English	 View PDF (166.49KB)	 Download PDF	 Share PDF
Compliances	Military Cross Reference Cable Ties	English	 View PDF (57.53KB)	 Download PDF	 Share PDF
Selection Guides	Cable Ties Product Selection Guide	English	 View PDF (2.70MB)	 Download PDF	 Share PDF

Related Products




PLT1M-M

Pan-Ty® locking tie, miniature cross section, 3.9 (99mm) length, nylon 6.6, natural, bulk package.



BT4LH-L0

Dome-Top® barb ty cable tie, light-heavy cross section, 14.9 (378mm) length, weather resistant nylon 6.6, black, standard package.



PLT4H-TL0

Pan-Ty® locking tie, light-heavy cross section, 14.5 (368mm) length, weather resistant nylon 6.6, black, bulk package.



Email Support

Available 24/7



800-777-3300

Monday through Thursday 7:00 am-6:30 pm
CST Friday 7:00 am-6:00 pm CST



Where to Buy

Find a Panduit Distributor or Partner

About Us

Research and Development

Awards

Partner Ecosystem

World

Headquarters

Company Profile

Media Resources

Case Studies

Panduit Code of Conduct

Careers at Panduit

The Hub – Partner Portal

Product Registration

Panduit Connections Blog



Get Our Catalog

Download the PDF or request a copy be mailed to you.

-Choose a catalog-

Download

Choose Language



Copyright 2020 Panduit

[Legal Information](#) [Privacy Notice](#)

[Unsubscribe](#)

[HAVE FEEDBACK?](#)