






PLT2S-C00

Share

Cable Tie

Pan-Ty® locking tie, standard cross section, 7.4 (188mm) length, military spec weather resistant nylon 6.6, black, standard package.

Find A Distributor

Qty | Add to Bom

Specifications | Packaging Detail | Resources | Related Products | Top of Page

Specifications

Product Type	Cable Tie
Color	Black
Environment	Outdoor
Sub Brand	Pan-Ty®
For Use With	GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PTH
Material	Nylon 6.6
Resistance Properties	UV Resistant
Maximum Bundle Diameter (In.)	1.88
Maximum Bundle Diameter (mm)	47.8
Maximum Installation Temperature (°F)	32
Maximum Operating Temperature (°C)	85
Maximum Operating Temperature (°F)	185
Minimum Bundle Diameter (In.)	0.06
Minimum Bundle Diameter (mm)	1.5
Minimum Installation Temperature	-20

(°C)	
Minimum Installation Temperature (°F)	-4
Minimum Loop Tensile Strength (lb)	50
Minimum Loop Tensile Strength (N)	222
Minimum Operating Temperature (°F)	-76
Minimum Operating Temperature (°C)	-60
Overall Length (mm)	188
Overall Length (In.)	7.4
Body Width (mm)	4.8
Body Width (In.)	0.19
Body Thickness (mm)	1.3
Body Thickness (In.)	0.052
Standards Met	CSA Certified, UL Recognized (File #E56854), UL 62275 Compliant (Type 2, 21), RoHS Complaint
Part Features	One-piece locking wedge for consistent performance and reliability. Low thread force and high loop tensile strength.

Packaging Detail

UPC	07498354130
Std. Pkg. Qty.	100
Std. Pkg. Volume (cf)	0.0321
Std. Ctn. Qty.	1000
Std. Ctn. Volume (cf)	0.3208

Resources

NOTE: Not all resources are available in your language.
If product info is not displayed in your selected language, it will be coming. We will continue to improve the experience over time.

Language

All

Selection Guides	Cable Ties Product Selection Guide.	English	View PDF (2.73MB)	Download PDF	Share PDF
Videos	Premium Cable Ties	English	View MP4 (25.40MB)	Download MP4	Share MP4
Compliances	Military Cross Reference Cable Ties	English	View PDF (57.53KB)	Download PDF	Share PDF

Drawings	Customer 3D STP Drawing	English	View STP (367.58KB)	Download STP	Share STP
Part Drawings	Pan-Ty Cable Tie, SS-5540 (Pg 2)	English	View PDF (210.32KB)	Download PDF	Share PDF

Related Products



PLT1M-M

Pan-Ty® locking tie, miniature cross section, 3.9 (99mm) length, nylon 6.6, natural, bulk package.

BT4LH-L0

Dome-Top® barb ty cable tie, light-heavy cross section, 14.9 (378mm) length, weather resistant nylon 6.6, black, standard package.

PLT4H-TL0

Pan-Ty® locking tie, light-heavy cross section, 14.5 (368mm) length, weather resistant nylon 6.6, black, bulk package.

Email Support
Available 24/7

800-777-3300
Monday through Thursday 7:00 am-6:30 pm CST Friday 7:00 am-6:00 pm CST

Where to Buy
Find a Panduit Distributor or Partner

About Us
Research and Development
Awards
Partner Ecosystem
World Headquarters

Company Profile
Media Resources
Case Studies
Panduit Code of Conduct

Careers at Panduit
The Hub – Partner Portal
Product Registration
Panduit Connections Blog

Get Our Catalog
Download the PDF or request a copy be mailed to you.

-Choose a catalog-
Download

Choose Language

Copyright 2020 Panduit

Legal Information Privacy Notice
Unsubscribe

HAVE FEEDBACK?