



## Panduct® Base Wiring Duct

F1X2LG6-A

Panduct® type F narrow slot wiring duct, 1 W x 2 H, 6' length, PVC, adhesive, light gray.

### Specifications

Application	Narrow slot/finger design provides more slots to fit the spacing of high-density terminal block applications
Note	Adhesive tape is not meant for permanent mounting of wiring duct. One mounting hole on each end will be exposed for permanent mounting with fasteners. For best results, wiring duct should be applied to clean, dry, grease-free surfaces. We recommend the surface be cleaned prior to wiring duct installation
Product Type	Base Wiring Duct
Color	Light Gray
Cover Part Number	C1LG6
Flammability Rating	UL94 V-0
Includes	Wiring Duct Base
Standards Met	RoHS Compliant, UL Recognized, CE Compliant
Material	Lead-Free PVC
Mount Method	Mounting Holes with Adhesive
Measurement System	Imperial
Wiring Duct Style	Narrow Slot Wiring Duct
Wiring Duct Type	F
Overall Height (In.)	2.12
Overall Height (mm)	53.8
Overall Length (ft.)	6
Overall Length (m)	1.8
Overall Width (In.)	1.25
Overall Width (mm)	31.8
Slot Width (In.)	0.2
Slot Width (mm)	5
Sub Brand	Panduct®
Part Features	Narrow finger and slot design closely matches the spacing of high-density components. Upper and lower scorelines allows easy finger and sidewall section removals. Double restricted slot design for retaining wires, eliminating hassle and saving time

**Packaging Detail**

UPC	07498333779
Std. Pkg. Qty.	6
Std. Pkg. Volume (cf)	0.0872
Std. Ctn. Qty.	120
Std. Ctn. Volume (cf)	1.7437