



Dome-Top® BT4S-M300 Barb Tie, Black, High Heat UV PA6.6, 15.1"L, 50lb, PK1000

BT4S-M300

The BT4S-M300 Dome-Top® barb ty, features a unique patented design with its round smooth edges. Paired with the stainless-steel locking barb, these cable ties provide consistent performance, reliability and infinite adjustability through the entire bundle range. Standard cross section, 15.1” (384mm) length. Appropriate for Indoor/Outdoor use, made of Heat Stabilized Weather Resistant Nylon 6.6 with high resistance to ultraviolet light and high temperature applications, are black in color and come in packages of 1000.

Specifications

Product Type	Cable Tie
Color	Black
Environment	Indoor/Outdoor
Sub Brand	Dome-Top®
For Use With	GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PTH, PPTS, STS2, STH2
Material	Heat Stabilized Weather Resistant Nylon 6.6
Resistance Properties	Heat and UV Resistant
Maximum Bundle Diameter (In.)	4
Maximum Bundle Diameter (mm)	102
Maximum Installation Temperature (°C)	0
Maximum Installation Temperature (°F)	32
Maximum Operating Temperature (°C)	115
Maximum Operating Temperature (°F)	239
Minimum Bundle Diameter (In.)	0.06
Minimum Bundle Diameter (mm)	1.5
Minimum Installation Temperature (°C)	-20
Minimum Installation Temperature (°F)	-4
Minimum Loop Tensile Strength (N)	222
Minimum Loop Tensile Strength (lb)	50
Minimum Operating Temperature (°C)	-60
Minimum Operating Temperature (°F)	-76
Overall Length (In.)	15.1
Overall Length (mm)	384
Body Width (In.)	0.185

Specifications (continued)

Body Width (mm)	4.7
Body Thickness (In.)	0.052
Body Thickness (mm)	1.3
Standards Met	UL 62275 (File E56854), CSA-C22.2 No. 62275 (File 31212), Cert 05968/C0, BV File ACE 14/601/01 Product Code: 2535H, 89/60111 (E3), 11130200, QPL-AS23190, RoHS Compliant

Packaging Detail

UPC	07498310714
Std. Pkg. Qty.	1000
Std. Pkg. Volume (cf)	0.3516
Std. Ctn. Qty.	5000
Std. Ctn. Volume (cf)	1.7578