

Product Country of Use United States of America | Show Only Offered Products

Home / All Products / Fiber Optic Systems / Fiber Optic Cassettes / F9UYBXRNNSNM015

FlexCore™ Front-Access Fiber Optic ODF Tethered Cassette Assembly

F9UYBXRNNSNM015

Share

Print

Download Available Options

Our ODF tethered cassette assembly provides pre-terminated, front-access, modular fiber optic units for easy organization and distribution of high-fiber count cables.

Fiber Type: OS2

OM4

OM4+

OS2

Flammability Rating: LSZH

LSZH

Plenum (OFNP)

Connector 1 Type: LC Duplex

LC Duplex

LC Duplex APC

Select product to view details, compare, or add to list:

FlexCore™ Front-Access Fiber Optic ODF Tethered Cassette Assembly

F9UYBXLNNSNM015

OS2 Single Mode 24 Fiber Indoor Small Diameter Trunk, Euroclass B2ca, FlexCore Front Access ODF LC Cassette, Left side Blunt end, Standard Insertion Loss, No pulling Eye - 15 Meters

FlexCore™ Front-Access Fiber Optic ODF Tethered Cassette Assembly

F9UYBXRNNSNM015

OS2 Single Mode 24 Fiber Indoor Small Diameter Trunk, Euroclass B2ca, FlexCore Front Access ODF LC Cassette, Right side Blunt end, Standard Insertion Loss, No pulling Eye - 15 Meters

+

-

↺

↻

⌂

Region & Language

US & Canada | English

Product Country of Use

United States of America

Set as Default

Choose Region/Language

US & Canada | English

Find a Partner or Distributor

Contact Us

My Account

Specifications

Fiber Type	OS2
Connection Type	LC
Sub Brand	FlexCore™
Number of Fibers	24
Connector 1 Type	LC Duplex
Adapter Color	Blue
Maximum Connector Insertion Loss (dB)	0.35
Minimum Connector Return Loss (dB)	55
Overall Width (In.)	11.53
Overall Width (mm)	292.8
Overall Height (In.)	0.46
Overall Height (mm)	11.7
Overall Depth (In.)	6.75
Overall Depth (mm)	171.5
Product Type	Front-Access Fiber Optic ODF Tethered Cassette Assembly
Standards Met	ISO/IEC 11801, ANSI/TIA-568-C.3, TIA-604-5, (FOCIS-5), TIA-604-10 (FOCIS-10), RoHS 2002/95/EC compliant, supports IEEE802.3 and ANSI T11.2 (Fiber Channel)
Color	Black
Fiber Diameter (µm)	9
Flammability Rating	LSZH

Packaging Detail

UPC	61305683715
Std. Pkg. Qty.	1
Std. Pkg. Volume (cf)	1.1131
Std. Ctn. Qty.	0
Std. Ctn. Volume (cf)	0.0000

Resources

NOTE: Not all resources are available in your language.
If product info is not displayed in your selected language, it will be coming. We will continue to improve the experience over time.

Language

All

Specification Sheets	FlexCore Front Access Cassettes - Specification Sheet FBSP209--WW-ENG	English	View PDF (1007.46KB)	Download PDF	Share PDF
Specification Sheets	Casetes de Fibrá Óptica FlexCore™ de Acceso Frontal Hoja de Especificaciones FBSP209--WW-SPA	Spanish (Español)	View PDF (1021.71KB)	Download PDF	Share PDF
Videos	Flex Core Video	English	View MP4 (119.59MB)	Download MP4	Share MP4
Videos	FlexCore™ Installation Video		View MP4 (1.29GB)	Download MP4	Share MP4
Videos	Fiber Cassette Cleaning Video	English	View MP4 (117.06MB)	Download MP4	Share MP4
Part Drawings	Flexcore ODF Tethered Cassette, 12-Port LC to Blunt Part Drawing 00986EAG-DC	English	View PDF (1.29MB)	Download PDF	Share PDF
Selection Guides	FlexCore™ Optical Distribution Frame Ordering Guide FBCB58	English	View PDF (10.13MB)	Download PDF	Share PDF

Email Support
Available 24/7

800-777-3300
Monday - Friday 7:00 am-6:00 pm CST

Where to Buy
Find a Panduit Distributor or Partner

About Us

Research and Development

Awards

Thought Leadership

Panduit Code of Conduct & Compliance

Company Profile

Media Resources

Environmental, Social, and Governance

Partner Ecosystem

World Headquarters

Careers at Panduit

The Hub – Partner Portal

Product Registration

Panduit Connections Blog

Panduit Product Catalogs

US & Canada | English

© 2025 Panduit Corp. All Rights Reserved.

Legal Information Privacy Notice Cookie Settings Unsubscribe