

G5 Intelligent PDU

MS PDU, 208V, (24)C13/C15, (24)C13/15/C19/C21

P48E22M Discontinued - Limited Stock

[Share](#) [Print](#) [Download Available Options](#)

Enhance data center efficiency with our G5 Intelligent PDU offering. Benefit from real-time power monitoring, space-saving design, and rapid fault detection for improved system reliability.

Show Discontinued Options

Rack PDU Type: Monitored & Switched

Monitored & Switched

Monitored & Switched per Outlet

Monitored Input

Monitored per Outlet

PDU Form Factor: 0U FULL

0U FULL

0U FULL +

0U FULL - Wide

0U FULL - Wide +

0U HALF

0U MID

1U

2U

Plug Type: NEMA L15-30P

CS8365

IEC 60309 2P+E 6h 16A (IP44)

IEC 60309 2P+E 6h 32A (IP44)

IEC 60309 3P+E 9h 60A (IP44)

IEC 60309 3P+N+E 6h 16A (IP44)

IEC 60309 3P+N+E 6h 20A/16A (IP44)

IEC 60309 3P+N+E 6h 30A (IP44)

IEC 60309 3P+N+E 6h 30A (IP67)

IEC 60309 3P+N+E 6h 30A/32A (IP44)

IEC 60309 3P+N+E 6h 32A (IP44)

IEC 60309 3P+N+E 6h 60/63A (IP44)

IEC 60309 3P+N+E 6h 60A/63A (IP44)

NEMA 5-15P

NEMA 5-20P

NEMA L15-30P

NEMA L21-30P

NEMA L22-30P

NEMA L5-20P

NEMA L5-30P

NEMA L6-20P

NEMA L6-30P

Universal (uPDU)

Input Amperage (A): 30

15

16

20

30

32

50

60

63

Phase: 3-Phase

3-Phase

Single-Phase

Apparent Power (kVA): 8.6

1.4

1.9

2.9

3.3

3.7

5

5.0 (NA)/7.4 (EU)

7.4

8.3

8.6

+ More

Output Receptacles: (24)C13/C15, (24)C13/15/C19/C21

(12)5-20R

(12)C13

(12)C13, (12)C19

(12)C13, (4)C19

(16)5-20R

(18)5-20R

(18)C13, (6)C19

(18)C13, (6)C19, (6)5-20R

(18)C13/C15, (18)C13/C15/C19/C21

(20)C13, (4)C19

(21)C13/C15, (21)C13/C15/C19/C21

(24)5-20R

(24)C13

(24)C13, (12)C19

(24)C13, (6)C19

(24)C13, (8)C19

(24)C13/C15, (24)C13/15/C19/C21

(28)C13, (6)C19

(30)C13, (12)C19

(30)C13, (6)C19

(30)C13, (6)C19, (2)5-20R

(32)C13, (6)C19

(36)C13, (12)C19

(36)C13, (6)C19

(38)C13, (6)C19


(42)C13, (6)C19

(48)C13

(6)C19

(8)5-20R

(8)C13



Discontinued - Limited Stock
It is the buyer's responsibility to determine if the suggested replacement part is suitable for your application and intended use.

Suggested Replacement Parts:

[P48E22G](#)

Add to List

Buy Here

Need help selecting the right product for you? Visit our [Guided Selection Tool](#) to find a Panduit solution that fits your needs.

☐ Compare

Find a Distributor

Specifications

Note	NA Only
Includes	(1) Mounting Hardware Kit
Product Type	PDU
Mount Orientation	Vertical
PDU Form Factor	0U FULL
Sub Brand	G5
Rack PDU Type	Monitored & Switched
Plug Type	NEMA L15-30P
Number of Circuit Breakers	3
Input Voltage (V)	208
Input Amperage (A)	30
Phase	3-Phase
Frequency Compatibility (Hz)	50/60
Current Measurement Accuracy (%)	±1%
Voltage Measurement Accuracy (%)	±1%
Power Measurement Accuracy (%)	±1%
Input Cord Length (ft.)	10
Input Cord Length (m)	3
Output Receptacles	(24)C13/C15, (24)C13/15/C19/C21
Output Voltage (V)	208
Front Panel Display	Use display to set IP address, update firmware, quick configure, rotate display, balance loads across phases, view alarms, read current, voltage, power and energy on the device
Apparent Power (kVA)	8.6
Network Monitoring Port	Gigabit network port reduces labor by auto negotiating with data center level network switches
SNMP Compatibility	Yes
Network Compatibility	10 Mbps, 100 Mbps (Fast Ethernet), 1 Gbps (Gigabit)
Network Card	Panduit G5 Gigabit Network Module
Communications Interface	(1) RJ45 Network, (2) RJ45 Sensor, (2) RJ45 Daisy Chain, (1) USB
Daisy-Chainable / Cascadable	Cascade up to 4 PDUs
LED Indicators	Green LED indicates outlet is on
Material	Metal
Finish/Coating	Powder-Coated

Region & Language
US & Canada | English

Product Country of Use
United States of America

Set as Default

Choose Region/Language



US & Canada | English [Find a Partner or Distributor](#) [Contact Us](#) [My Account](#)



Keyword, Part Number or Cross-Reference

All Products Solutions Support About Us

Parts List

Overall Depth (mm)	75
Number of Rack Units	42
Maximum Operating Temperature (°C)	60
Maximum Operating Temperature (°F)	140
Minimum Operating Temperature (°C)	10
Minimum Operating Temperature (°F)	50
Maximum Storage Temperature (°C)	60
Maximum Storage Temperature (°F)	140
Minimum Storage Temperature (°C)	-20
Minimum Storage Temperature (°F)	-4
Compliance Certifications	UL 62368-1, FCC Pat 15 Class A (USA), NOM (Mexico)
Standards Met	UL Listed File number: E218078
Product Warranty Period (Worldwide)	3 Years

Part Features	• Combination Outlets • Optimized Web Interface • Hot Swappable Network Module • No disruption to outlets during controller installation • Ready to go out of the box • High Outlet Density • Optimal Form Factor • Operating Temperature: 60° C at Full Load
---------------	---

Packaging Detail

UPC	61305685919
Std. Pkg. Qty.	1
Std. Pkg. Volume (cf)	1.6884
Std. Ctn. Qty.	0
Std. Ctn. Volume (cf)	0.0000

Resources

NOTE: Not all resources are available in your language.

If product info is not displayed in your selected language, it will be coming. We will continue to improve the experience over time.

Language

All

Specification Sheets	G5 Intelligent Power Distribution Units (iPDUs) Specification Sheet FBSP28	English	View PDF (2.37MB)	Download PDF	Share PDF
Part Drawings	Intelligent Series PDU P48E22M-XXYZ Part Drawing	English	View PDF (687.57KB)	Download PDF	Share PDF
Installation Documents	G5 PDU Installation Manual IM054 REV 10	English	View PDF (1.69MB)	Download PDF	Share PDF
Brochures	G5 PDU Pocket Guide	English	View PDF (3.32MB)	Download PDF	Share PDF
Flyers	Soluciones de Monitoreo de Seguridad y Ambiental con la Solución iPDU G6 de Panduit - PUFL07	Spanish (Español)	View PDF (314.00KB)	Download PDF	Share PDF
Flyers	Soluciones de Monitoreo de Seguridad y Ambiental con la Solución iPDU G5 Folleto PUFL07	Spanish (Español)	View PDF (315.89KB)	Download PDF	Share PDF
Flyers	G5 iPDU infographic Flyer PUFL06--SA-ENG	English	View PDF (2.06MB)	Download PDF	Share PDF
Manuals	G5 Intelligent PDU User Manual v4.8	English	View PDF (4.17MB)	Download PDF	Share PDF
Selection Guides	Panduit G5 PDU Security and Environmental Solution Guide PUFL07	English	View PDF (3.32MB)	Download PDF	Share PDF
Selection Guides	PDU Guía de Bolsillo Guía PUCB27--SA-SPA	Spanish (Español)	View PDF (3.57MB)	Download PDF	Share PDF

Email Support
Available 24/7

800-777-3300
Monday - Friday 7:00 am-6:00 pm CST

Where to Buy
Find a Panduit Distributor or Partner



About Us
Research and Development

Awards
Thought Leadership

Panduit Code of Conduct & Compliance

Company Profile
Media Resources

Environmental, Social, and Governance

Partner Ecosystem

World Headquarters

Careers at Panduit
The Hub - Partner Portal

Product Registration

Panduit Connections Blog

Panduit Product Catalogs

Also of Interest [Power, Environmental, Security & Connectivity Hardware](#) [Power Distribution Units Support](#) [Power Distribution Units \(PDUs\)](#)

