

CATEGORIES

Square Pin Connectors

GRID

All

ROWS

All

TYPE

All

For more information or to request assistance, please contact sales@precidip.com

« Back to search results

YOUR SELECTED PRODUCT

Square Pin Connectors - 0.5 / 0.635 mm

SERIES
890

890-PP-NNN-20-001101

Single row
2.54 mm, Right angle solder tail, Square pin diam. 0.635 mm

Right angle square pin headers, solder tail

Technical specs.:

- Insulator:Black glass filled polyester PA-GF30-FR
- Flammability:UL 94V-O
- Contact:Brass
- Connecting pin:Square 0.635 mm
- Mechanical life:Min. 100 cycles
- Rated current:3 A
- Dielectric strength:Min. 1000 V RMS



Ordering information RoHS-compliant parts

PP Plating code	Termination	Connecting pin
70	Gold flash	Gold flash
80	Tin	Tin
18	Tin	Gold 0.25 µm

NNN number of poles. Replace NNN with the requested number of poles, e.g. 890-70-NNN-20-006101 for a single row version with 8 pins becomes 890-70-008-20-006101.

General technical specs.

View CAD

890-PP-NNN-20-XXX101

Right angle square pin header, solder tail, single row.

Square pin Ø 0.635 mm

Availability from: 2 to 40 contacts.
Standard number of contacts 40.



890-PP-NNN-20-001101

Right angle square pin header, solder tail, single row.

Square pin Ø 0.635 mm

Availability from: 2 to 40 contacts.
Standard number of contacts 40.

A = 6 mm



890-PP-NNN-20-002101

Right angle square pin header, solder tail, single row.

Square pin Ø 0.635 mm

Availability from: 2 to 40 contacts.
Standard number of contacts 40.

A = 7 mm



CAD CATALOG

[Literature](#)
[Catalog](#)
[CAD catalog](#)

ABOUT PRECI-DIP

[Career](#)
[Contact](#)
[Events](#)

OTHER INFO

[Feedback](#)
[Legal disclaimer](#)
[Cross references](#)

NEWSLETTER

Stay informed!

Company

Last name, first name

Email

subscription

© 2018 - PRECI-DIP SA. All rights reserved