

DISTRIBUTORS
REPS LOCATION

DISTRIBUTOR
INVENTORY SEARCH

[PRODUCTS](#)

[MARKETS](#)

[CUSTOM DESIGN](#)

[DISTRIBUTORS](#)

[ABOUT US](#)

[ASSISTANCE](#)

[CONTACT](#)

CATEGORIES

Pin Connectors

GRID

All

ROWS

All

TYPE

All

For more information or to request assistance, please contact sales@precidip.com

[« Back to search results](#)

YOUR SELECTED PRODUCT

PCB Connectors - Pin Connectors

SERIES
450



450-PP-2NN-00-006101

Double row
2.54 mm, Straight solder tail, Pin 0.47mm

Pin connectors, solder tail.

Technical specs.:

Insulator:	Black glass filled polyester PCT-GF30-FR
Flammability:	UL 94V-O
Contact:	Brass CuZn36Pb3 (C36000)
Connecting pin Ø:	0.47 mm
Mechanical life:	Min. 500 cycles
Rated current:	3 A
Dielectric strength:	Min. 1000 V RMS
Coplanarity SMD terminations:	



Ordering information RoHS-compliant parts

PP Plating code	Termination	Connecting pin
10	Gold 0.25 µm	Gold 0.25 µm
80	Tin	Tin
V3*	Tin	Gold 0.75 µm

*only for 450...00-006101 series

NN number of poles. Replace NN with the requested number of poles, e.g. 450-10-2NN-00-006101 for a double row version with 16 pins becomes 450-10-216-00-006101.

[General technical specs.](#)

[View CAD](#)

450-PP-2NN-00-006101

Straight pin connector low profile height 3.5 mm: solder tail, double row,

Pin Ø 0.47 mm

Availability from: 4 to 72 contacts.
Standard number of contacts 72.

450-PP-2NN-00-006101

Straight pin connector low profile height 3.5 mm: solder tail, double row

Pin Ø 0.47 mm

Availability from: 4 to 72 contacts.
Standard number of contacts 72.

450-PP-2NN-00-001101

Straight pin connector, height 4 mm: solder tail, double row.

Pin Ø 0.47 mm

Availability from: 4 to 72 contacts.
Standard number of contacts 72.

450-PP-2NN-00-001101

Straight pin connector, height 4 mm: solder tail, double row.

Pin Ø 0.47 mm

Availability from: 4 to 72 contacts.
Standard number of contacts 72.

450-PP-2NN-00-013101

Straight pin connector, height 4.1 mm: solder tail, double row.

Pin Ø 0.47 mm

Availability from: 4 to 72 contacts.
Standard number of contacts 72.

450-PP-2NN-00-013101

Straight pin connector, height 4.1 mm: solder tail, double row.

Pin Ø 0.47 mm

Availability from: 4 to 72 contacts.
Standard number of contacts 72.

CAD CATALOG

Literature
Catalog
CAD catalog

ABOUT PRECI-DIP

Career
Contact
Events

OTHER INFO

Feedback
Legal disclaimer
Cross references

NEWSLETTER

Stay informed!