



RUE SAINT-HENRI 11, P.O. BOX 834 - CH-2800 DELÉMONT / SWITZERLAND

## Your selected product

### Jumpers - PCB Connectors

Series 999

**999-11-230-10**

2.54 mm, Male Jumpers

Available with or without insulator, and with 2.54, 5.08 or 7.62 mm pin spacing. For use with standard socket connectors.

#### Technical specs.:

**Insulator:** Black glass filled polyester PBT-GF30-FR

**Flammability:** UL 94V-O

**Contact:** Brass CuZn36Pb3 (C36000)


**Connecting pin Ø:** 0.56 mm

**Mechanical life:** Min. 100 cycles

**Rated current:** 3 A

**Contact resistance:** Max. 10 mΩ

**Dielectric strength:** Min. 1000 V RMS



### Ordering information RoHS-compliant parts

**P Plating code**

1 Gold 0.25 µm

**Option**

Jumpers without insulator with wire Ø 0.50 mm instead of 0.56 mm. Part numbers:



B = 2.54 mm 999-51-110-10

B = 5.08 mm 999-51-112-10

B = 7.62 mm 999-51-113-10

[General technical specs.](#) [View CAD](#)**Advanced information:**

Order Codes		
999-11-230-10	<a href="#">View Image</a>	

**999-11-110-10**Jumpers for socket connectors,  
B = 2.54 mm, not insulated**999-11-210-10**Jumpers for socket connectors,  
B = 2.54 mm, with black insulator**999-11-210-11**Jumpers for socket connectors,  
B = 2.54 mm, with red insulator**999-11-112-10**

Jumpers for socket connectors,  
B = 5.08 mm, not insulated

---

**999-11-220-10**

Jumpers for socket connectors,  
B = 5.08 mm, with black insulator

---

**999-11-220-11**

Jumpers for socket connectors,  
B = 5.08 mm, with red insulator

---

**999-11-113-10**

Jumpers for socket connectors,  
B = 7.62 mm, not insulated

---

**999-11-230-10**

Jumpers for socket connectors,  
B = 7.62 mm with black insulator

---

**999-11-230-11**

Jumpers for socket connectors,  
B = 7.62 mm with red insulator

---

**999-11-110-10**

Jumpers for socket connectors,  
B = 2.54 mm, not insulated

---

**999-11-210-10**

Jumpers for socket connectors,  
B = 2.54 mm, with black insulator

---

**999-11-210-11**

Jumpers for socket connectors,  
B = 2.54 mm, with red insulator

---

**999-11-112-10**

Jumpers for socket connectors,  
B = 5.08 mm, not insulated

---

**999-11-220-10**

Jumpers for socket connectors,  
B = 5.08 mm, with black insulator

---

**999-11-220-11**

Jumpers for socket connectors,  
B = 5.08 mm, with red insulator

---

**999-11-113-10**

Jumpers for socket connectors,  
B = 7.62 mm, not insulated

### **999-11-230-10**

Jumpers for socket connectors,  
B = 7.62 mm with black insulator

---

### **999-11-230-11**

Jumpers for socket connectors,  
B = 7.62 mm with red insulator

---