



Project - 0 item(s)

MY PROJECT LIST

PRODUCTS

APPLICATIONS

INDUSTRIES

NEW PRODUCTS

CONFIGURATORS

Products ▾


Search

Home > VME64x-based systems 1 U, 2 slot, with rear I/O

VME64x-based systems 1 U, 2 slot, with rear I/O



Other Views

**Catalog Number: 20836-145**[Back To Product](#)

- ATX PSU, 250 W
- Heat dissipation by pull-out hot-swap fan unit, from right to left
- Backplane VME64x2 slot, 6 U, with P0 plug
- Fan monitoring and voltage display
- System for horizontal board mounting with board formats; Front: 6 U, 160 mm deep; Rear, rear I/O: 6 U, 80 mm deep

Delivery Includes:

completely assembled, wired and tested

Note:

Modified systems available on requestSystem in accordance with IEC 60297-3-101, 102, 103; IEEE 1101.1, 1101.10/11; ☐ backplane conforms to VITA 1.1-1997

Specification:

VME64x

Form factor:

Rackmount

Power type:

ATX

Select product specifications before modifying or adding to project list or requesting a quote.

[Clear Selection](#)Quantity

Modify Product ►

Add Item to Project List +

Documents

User manual



Operating instructions

Rear I/O:

Yes

Number of slots:

2



Links



Main Catalog - Systems VME,
VME64x, VXS, VPX



Configurator - VME64X
Systems

Technical Data


Depth mm	277.5
Height mm	44.45
Number of slots	2
Width mm	449.0
Material	Al
Power W	200.0
Description	VME64xbus subrack system
Height U	1
Width HP	84
Board height	6

Delivery Comprises:

1	1	Shielded 19" chassis, steel plate, black powder-coated (RAL 9005)
2	2	Front slot; IEEE guide rails, incl. ESD clips (ESD clips fitted to right), for horizontal mounting of rear I/O boards (6 U, 160 mm deep)

3	2	Rear slot; IEEE guide rails, incl. ESD clips (ESD clips fitted to right), for horizontal mounting of rear I/O boards □(6 U, 80 mm deep)
4	1	Backplane VME64x for 6 U boards, 2 slot, with P0 plug, with connector plug for fan unit and ATX PSU
5	1	ATX power supply; 250 W; □wide range input 100 ... 240 VAC, □output 3.3 V/14 A, 5 V/23 A, 12 V/16 A, - 12 V/0.5 A; with IEC connector; mains switch; fan
6	1	Hot-swap fan unit with 4 fans; □incl. fan monitoring and voltage display
7	1	DC switch (with LED), switches off only the DC output of the power supply unit, power ON
8	1	Cable harness to connect all system components


Accessories



Equipment cable, SCHUKO/UTE - IEC 320, angled, SCHUKO/UTE connector / plug, IEC 320 female connector, 2,5 m, grey, 1 piece

60704-020


Add Item to Project List +



Equipment cable USA, USA connector, IEC 60320 female connector, 2 m, black, 1 piece

60103-141


Add Item to Project List +



Mains cable, IEC, IEC 60320 C14 plug, IEC 60320 C13 socket, 2.5 m, black, 1 piece

60197-053

Add Item to Project List +




Equipment cable SCHUKO/UTE, SCHUKO/UTE plug, IEC 60320 socket, 2.5 m, grey, 1 piece

60103-131

Add Item to Project List +

Mains cable, BS, British Standard plug, IEC 60320

60103-137



C13 socket, 2.5 m, black, 1 piece

Add Item to Project List +

EXPLORE

About Us
Services & Capabilities
News & Events
Newsletter Subscriptions
Strategic Partnerships
Investor Relations

CONTACT

Customer Service
Find a Sales Office or Distributor
Global Locations
Product Compliance & Certifications
Partner Login

DOWNLOAD

Download Center
Reference Projects
Videos
Product Configurators
Warranties and Terms of Sale & Procurement

© 2018 Pentair. All rights reserved | [Privacy Policy](#) | [Terms of Use](#) | [Cookie Policy](#) | [Imprint](#) | [Site Map](#)

Connect With Us

