


Industrial Low profile PulseJack™ Integrated Connector

Rugged design for fast Ethernet and 1Gigabit connectivity



- Ⓢ Fully compliant to IEEE802.3 for 10/100/1000Base-T
- Ⓢ Open Inductance 350uH @ 8mA
- Ⓢ Compatible with market leading PHYs
- Ⓢ Rugged design for outdoor and industrial use
- Ⓢ Fully RoHS and Lead Free compliant-No exemptions
- Ⓢ Peak wave solder temperature 260°C

Electrical Specifications @ 25°C - Operating Temperature -40°C to +85°C

Part Number	Data Rate	Turns Ratio	LED Configuration (L/R)	EMI Fingers Configuration	Design Style	Isolation (Pri:Sec)	Possible replacement to older design
JXD1-1V07NL	100Base-TX	1.00 +/- 3%	Green-Orange/Yellow	Top and Side	3W CMC on TX	2250VDC / 60sec	J0G-0007NL
JXD1-1V17NL	100Base-TX	1.00 +/- 3%	Green-Orange/Yellow	None	2W CMC on RX	2250VDC / 60sec	NEW
JXD1-1V09NL	1000Base-T	1.00 +/- 3%	Green-Orange/Yellow	Top and Side	3W CMC on PHY side	2250VDC / 60sec	J0G-0009NL

Recommended replacements for older PulseJack latch-up products - J0G-00xxNL

Electrical Specifications @ 25°C - Operating Temperature -40°C to +85°C

Part Number	Insertion Loss (MAX)	Return Loss (MIN)			Crosstalk (MIN)			CMRR (MIN)	DCR (J1-J2) (J3-J6)
	1 - 100MHz	1 - 30MHz	30 - 60MHz	60 - 80MHz	1MHz	30 - 60MHz	100MHz	1 - 100MHz	
JXD1-1V07NL	-1.0dB	-18dB	-16dB	-12dB	-35dB	-30dB	-30dB	-30dB	1.2 OHM max
JXD1-1V17NL	-1.0dB	-18dB	-16dB	-12dB	-35dB	-30dB	-30dB	-30dB	1.2 OHM max

Electrical Specifications @ 25°C - Operating Temperature -40°C to +85°C

Part Number	Insertion Loss (MAX)	Return Loss (MIN)			Crosstalk (MIN)			CMRR (MIN)	DCR (J1-J2), (J3-J6) (J4-J5), (J7-J8)
	1 - 125MHz	1 - 30MHz	30 - 60MHz	60 - 100MHz	1MHz	30 - 60MHz	100MHz	1 - 100MHz	
JXD1-1V09NL	-1.2dB	-18dB	-16dB	-10dB	-38dB	-33dB	-30dB	-30dB	1.2 OHM max

Notes:

1. ROHS Compliant:
2. Plastic housing: thermoplastic material with flammability rating UL94V-0 or better
3. Contacts plating: 30 micro-inch gold plating
4. Contacts base material: Phosphor bronze
5. Under plating: 50u inches min nickel
6. Solder Tail Plating: 100 min u inches 100% tin, matte finish

7. Metal shield - nickel plating on Stainless Steel
8. Jack cavity conforms to FCC part 68 subpart
9. PCB plating: HASL
10. Storage temperature: -40°C to 85°C
11. Compliance to J-STD:
 - A. J-STD-002: solderability at 245°C DIP and LOOK test
 - B. J-STD-020: level 1, no moisture sensitive
 - C. J-STD-075: W2, 270°C maximum through wave solder
12. All parts are shipped in trays with 60pcs/tray - see page4 for details

RJ45 Connector performance:

- Insulation Resistance : 500M Ohms Min
- Insertion force with the latch depressed : 22N Max
- Removal force with the latch depressed : 44N Max
- Durability : 750 Cycles


Industrial Low profile PulseJack™ Integrated Connector

Rugged design for fast Ethernet and 1Gigabit connectivity




MECHANICALS

JXD1-IVxxNL



RECOMMENDED FOOTPRINT



SUGGESTED FOOTPRINT (COMPONENT SIDE SHOWN)


Industrial Low profile PulseJack™ Integrated Connector

Rugged design for fast Ethernet and 1Gigabit connectivity




SCHEMATICS

JXD1-1V07NL, JXD1-1V17NL



JXD1-1V09NL




SUGGESTED FOOTPRINT (COMPONENT SIDE SHOWN)

Industrial Low profile PulseJack™ Integrated Connector

Rugged design for fast Ethernet and 1Gigabit connectivity

LED SCHEMATICS

JX20-0114NL, JX20-0206NL, JX20-0237NL




LED SPECIFICATION


EMITTING COLOR	λ_p (nm)	$V_f @ I_f = 20\text{mA}$	$I_r @ V_r = 5\text{V}$
GREEN	570	1.7V-2.6V	10 μA max.
YELLOW	590	1.7V-2.6V	10 μA max.
ORANGE	610	1.7V-2.6V	10 μA max.

PACKING DETAILS

COMPONENT PACKING TRAY



TOP PACKING COVER



1. **Material:** Conductive PET, 0.5mm thick
2. **Components per Tray:** 60 pcs
3. **Quantity per box:** 10x Tray = 600 pcs

For More Information:

Americas - prodinfo@networkamericas.yageo.com | Europe - prodinfo@networkemea.yageo.com | Asia - prodinfo@networkapac.yageo.com

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners. © Copyright, 2022. Pulse Electronics, Inc. All rights reserved.