



PJ2306



30V N-Channel Enhancement Mode MOSFET-ESD Protected

Features

- $R_{DS(ON)}, V_{GS}@10V, I_{DS}@3.2A=65m\Omega$
- $R_{DS(ON)}, V_{GS}@4.5V, I_{DS}@2.8A=85m\Omega$
- Advanced Trench Process Technology
- High Density Cell Design For Ultra Low On-Resistance
- Very Low Leakage Current In Off Condition
- Specially Designed for Load Switch, PWM Applications
- ESD Protected
- Lead free in compliance with EU RoHS 2011/65/EU directive.
- Green molding compound as per IEC61249 Std..(Halogen Free)

Mechanical Data

- Case: SOT-23 Package
- Terminals: Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 0.0003 ounces, 0.084 grams
- Marking: 06



Maximum Ratings and Thermal Characteristics ($T_A=25^\circ\text{C}$ unless otherwise noted)

PARAMETER		SYMBOL	LIMIT	UNITS
Drain-Source Voltage		V_{DS}	30	V
Gate-Source Voltage		V_{GS}	± 20	V
Continuous Drain Current		I_D	3.2	A
Pulsed Drain Current ¹⁾		I_{DM}	16	A
Maximum Power Dissipation	$T_A=25^\circ\text{C}$	P_D	1.25	W
	$T_A=75^\circ\text{C}$		0.75	W
Operating Junction and Storage Temperature Range		T_J, T_{STG}	-55 to +150	$^\circ\text{C}$
Junction to Ambient Thermal Resistance (PCB mounted) ²		$R_{\theta JA}$	100	$^\circ\text{C/W}$

Note:1. Maximum DC current limited by the package
2. Surface mounted on FR4 board, $t \leq 5$ sec





PJ2306

Electrical Characteristics

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
Static						
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{GS}=0V, I_D=250\mu A$	30	-	-	V
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=250\mu A$	1	-	2.5	V
Drain-Source On-State Resistance	$R_{DS(on)}$	$V_{GS}=4.5V, I_D=2.8A$	-	72	85	mΩ
		$V_{GS}=10V, I_D=3.2A$	-	55	65	
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=24V, V_{GS}=0V$	-	-	1	μA
Gate-Source Leakage Current	I_{GSS}	$V_{GS}=\pm 16V, V_{DS}=0V$	-	-	± 10	μA
Forward Transconductance	g_{fs}	$V_{GS}=4.5V, I_D=2.8A$	3	-	-	S
Diode Forward Voltage	V_{SD}	$I_S=2.8A, V_{GS}=0V$	-	0.88	1.2	V
Dynamic						
Total Gate Charge	Q_g	$V_{DS}=15V, I_D=3.2A,$ $V_{DS}=5V$	-	2.8	3.5	nC
		$V_{DS}=15V, I_D=3.2A,$ $V_{GS}=10V$	-	5	6.5	
Gate-Source Charge	Q_{gs}		-	0.5	-	
Gate-Drain Charge	Q_{gd}	-	1.1	-		
Turn-On Delay Time	$t_{d(on)}$	$V_{DD}=15V, R_L=15\Omega$ $I_D=1A, V_{GEN}=10V,$ $R_G=6\Omega$	-	8.6	11.2	ns
Turn-On Rise Time	t_r		-	12.8	16.8	
Turn-Off Delay Time	$t_{d(off)}$		-	18.6	26	
Turn-Off Fall Time	t_f		-	1.9	2.6	
Input Capacitance	C_{iss}	$V_{DS}=15V, V_{GS}=0V$ $f=1MHz$	-	270	-	pF
Output Capacitance	C_{oss}		-	45	-	
Reverse Transfer Capacitance	C_{rss}		-	30	-	

NOTES : Plus Test : Pluse Width $\leq 300\mu s$, Duty Cycle $\leq 2\%$.





PJ2306

Typical Characteristics Curves ($T_a=25^\circ\text{C}$, unless otherwise noted)




Fig.1 Output Characteristic




Fig.2 Transfer Characteristic




Fig.3 On Resistance vs Drain Current




Fig.4 On Resistance vs Gate to Source Voltage




Fig.5 On Resistance vs Junction Temperature




Fig.6 Capacitance



PJ2306

Typical Characteristics Curves (Ta=25°C, unless otherwise noted)




Fig. 7 Gate Charge Waveform




Fig. 8 Source-Drain Diode Forward Voltage





Fig.9 Breakdown Voltage vs Junction Temperature



PJ2306

MOUNTING PAD LAYOUT



ORDER INFORMATION

- Packing information
T/R - 12K per 13" plastic Reel
T/R - 3K per 7" plastic Reel



PJ2306

Part No_packing code_Version

PJ2306_R1_00001

PJ2306_R2_00001

For example :

RB500V-40_R2_00001



Packing Code XX				Version Code XXXXX		
Packing type	1 st Code	Packing size code	2 nd Code	HF or RoHS	1 st Code	2 nd ~5 th Code
Tape and Ammunition Box (T/B)	A	N/A	0	HF	0	serial number
Tape and Reel (T/R)	R	7"	1	RoHS	1	serial number
Bulk Packing (B/P)	B	13"	2			
Tube Packing (T/P)	T	26mm	X			
Tape and Reel (Right Oriented) (TRR)	S	52mm	Y			
Tape and Reel (Left Oriented) (TRL)	L	PANASERT T/B CATHODE UP (PBCU)	U			
FORMING	F	PANASERT T/B CATHODE DOWN (PBCD)	D			



PJ2306

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.