



SK13447

REVISION RECORD

₽

COLE BS

## **-**—0.971±0.005 [24.67±0.13]—► 00000000 00000000 1.312±0.005 [33.32±0.13]- $[7.90\pm0.13]$ 0.311±0.005

0.**494** [12.55]

ø0.066 [ø1.68]<sup>⊥</sup>

ø0.045 [ø1.14]—

15X MALE CONTACT ENLARGED

 $-0.170^{+0.015}_{-0.020}$ 

-0.538 [13.67]-

## 1. MATERIALS AND FINISHES:

INSULATOR: GLASS FILLED DAP PER ASTM-D5948, SDG-F, UL 94V-0, COLOR: GREEN CONTACTS: PRECISION MACHINED COPPER ALLOY, GOLD FLASH OVER NICKEL PLATE.

SHELLS: STEEL, ZINC PLATE WITH CHROMATE SEAL.

HOOD AND CABLE CLAMPS: DIE CAST ZINC. COVER AND CABLE CLAMP SCREWS: STEEL WITH NICKEL PLATE.

LOCK TABS: STEEL WITH NICKEL PLATE.

2. DETAILED PRODUCT, MECHANICAL, AND ELECTRICAL INFORMATION IS AVAILABLE IN THE LATEST STANDARD DENSITY D-SUB PRODUCT PUBLICATION. VISIT CONNECTPOSITRONIC.COM/PRODUCTS/45/STANDARDDENSITYD-SUBMINIATURE OR CONNECTPOSITRONIC.COM.

3. DIMENSIONS ARE IN INCHES [MILLIMETERS].

