




THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO POSITRONIC AND ITS SUBSIDIARIES. POSITRONIC BELIEVES THE DATA ON THIS DRAWING TO BE RELIABLE. SINCE THE USER ASSUMES ALL RESPONSIBILITY FOR THE DESIGN AND CONSTRUCTION OF SUCH INFORMATION, POSITRONIC ASSUMES NO RESPONSIBILITY FOR RESULTS OBTAINED OR DAMAGES INCURRED FROM USE OF SUCH INFORMATION IN WHOLE OR IN PART.




CONTACT HOLE PATTERN

- NOTES:
1. MATERIALS AND FINISHES:
INSULATOR: GLASS FILLED POLYESTER PER ASTM D5927, UL 94V-0, BLUE COLOR.
CONTACTS: PRECISION MACHINED COPPER ALLOY, GOLD FLASH OVER NICKEL FINISH.
SHELLS: STEEL, ZINC PLATED WITH CHROMATE SEAL.
ALIGNMENT BAR: GLASS FILLED POLYESTER, COLOR BLACK.
RIVETS: STEEL, ZINC PLATE WITH CHROMATE SEAL.
MOUNTING BRACKET: BRASS, ZINC PLATE WITH CHROMATE SEAL.
 2. DETAILED PRODUCT, ELECTRICAL, AND MECHANICAL INFORMATION IS AVAILABLE IN THE LATEST HIGH DENSITY D-SUBMINIATURE PRODUCT PUBLICATION.
VISIT CONNECTPOSITRONIC.COM/PRODUCTS/59/HIGHDENSITYD-SUBMINIATURE
OR CONNECTPOSITRONIC.COM.
 3. CONNECTORS ARE COMPLIANT TO THE CURRENT ROHS DIRECTIVE.
 4. DIMENSIONS ARE IN INCHES [MILLIMETERS].

DATE	REV	REVISION/RECORD	APP	DR	CK
10-26-11	NC	ECO 34641	COLF	LD	COLF
6-17-13	A	ECO 39627	TK	BE	TK

SK12835



POSITRONIC INDUSTRIES INC.
www.connectpositronic.com

DECIMAL TOL.	± 0.015 [0.38]	SCALE	N.T.S.	DRAWN BY	L. OMENS
ANGULAR TOL.	± 5°	TITLE	DD SERIES	APPROVED BY	COLF
DATE	10-27-11	DRAWING NUMBER	DD104S4R7000/AA	FSCM	28198
			SK12835	REV.	A