


Product Overview

The QPL1816 is a GaAs pHEMT single ended RF amplifier IC featuring 10dB of gain and low noise. The balance of low noise and distortion provides an ideal solution for a wide range of broadband amplifiers used in Cable TV applications such as Optical Receivers and low noise front ends. QPL1816 is packaged in a SOT-89 package for convenient layout and design in set top and infrastructure projects for 75 Ω CATV and satellite applications.



Functional Block Diagram



Top View

Key Features

- 50 MHz to 1800 MHz Operation
- 6 V Single Power Supply
- Gain: 10 dB Typical
- Noise Figure: 2.5 dB Typical at 1250 MHz
- Convenient SOT-89 Package
- RoHS Compliant

Applications

- FTTH GPON and GEPON
- DOCSIS 4.0
- Head End CMTS Equipment
- Optical Node
- Satellite Low Noise Amplifier
- Cable Modem and Set Top Box
- Single Ended Gain Block

Ordering Information

Part Number	Description
QPL1816SB	Sample bag with 5 pieces
QPL1816SR	7" Reel with 100 pieces
QPL1816TR13	13" Reel with 2500 pieces
QPL1816EVB-01	Evaluation Board



QPL1816

75 Ω 10 dB CATV Amplifier 50 – 1800 MHz

Absolute Maximum Ratings

Parameter	Rating
Supply Voltage (V_{DD})	+8 V
Supply Current (I_{DD})	170 mA
Maximum Input Level	60 dBmV
Operating Temperature Range	-40 to +100 °C
Storage Temperature Range	-65 to +150 °C
Maximum Junction Temperature	+150 °C


Exceeding any one or a combination of the Absolute Maximum Rating conditions may cause permanent damage to the device. Extended application of Absolute Maximum Rating conditions to the device may reduce device reliability.

Electrical Specifications at +6 V


Parameter	Condition ⁽¹⁾	Min	Typ	Max	Unit
Supply Voltage (V_{DD})			6		V
Supply Current (I_{DD})			120		mA
Frequency Range		50		1800	MHz
Gain			10		dB
Gain Flatness			± 1		dB
Reverse Isolation			17		dB
Input Return Loss			16		dB
Output Return Loss			16		dB
Noise Figure			2.5		dB
OIP2 (Lower)	0 dBm / tone output		60		dBm
OIP2 (Upper)	0 dBm / tone output		50		dBm
OIP3	0 dBm / tone output		36		dBm
OP1dB			19		dBm
Thermal Resistance	Θ_{JC}		+42		°C/W

Note: Typical performance at these conditions: Temp = +25 °C, V_{DD} = +6 V, 75 Ω system, Full band unless otherwise noted

Evaluation Board Schematic 50 MHz – 1800 MHz









Evaluation Board Assembly Drawing



**QPL1816****75 Ω 10 dB CATV Amplifier 50 – 1800 MHz****Evaluation Board Bill of Materials**





Ref Des.	Description	Mfg Name	Mfg Part #
U1	CATV DOCSIS 4.0 LNA, 5V, 1.8GHz, 75-ohm	Qorvo	QPL1816
C5	CAP, 1000 PF, 50V, 10%, 0603	AVX Asia Limited	06035C102KAT2A
C7	CAP, 0.5pF, +/-0.25pF, 50V, HI-Q, 0402	MURATA ELECTRONICS	GJM1555C1HR50CB01D
C1, C6	CAP, 1000pF, 5%, 50V, C0G, 0402	MURATA ELECTRONICS	GRM1555C1H102JA01D
C2	CAP, 0.3pF, +/-0.05pF, 50V, HI-Q, 0402	MURATA ELECTRONICS	GJM1555C1HR30WB01D
R1	RES, 0 OHM, 0603	Kamaya, Inc	RMC1/16JPTP
L1	IND, 3.9nH, +/-0.3nH, M/L, 0402	MURATA ELECTRONICS	LQG15HN3N9S02D
L2	IND, 4.3nH, +/-0.1nH, T/F, 0402	MURATA ELECTRONICS	LQP15MN4N3B02D
L3	FER, BEAD, 1500 OHM, 500mA, 0603	MURATA ELECTRONICS	BLM18HE152SN1D
JP1	CONN, HDR, ST, 3-PIN, 0.100"	SAMTEC INC.	TSW-103-07-G-S
J1, J2	CONN, F FEM EDGE MOUNT, 75 OHMS, 0.068"	Millimeter Wave Tech	MW-846-C-DD-75
R2, R6, R3, R4, R5, C3, C4, L4	NOT POPULATED ITEM-1		DUMMY PART

Performance Data at +6 V



Notes: (1) OIP3: 0dBm/tone output


Performance Data at +6 V



Notes:

- (1) OIP2: 0 dBm/ tone output
- (2) 54MHz to 1794MHz, 0dB tilt, 1 OFDM (54-246MHz) + 254 QAM (252-1794MHz) Channels.
CCN Noise BW (ANSI/SCTE 17): 5.36MHz for J.83/B.
- (3) Tx Data: ITU-T, Annex B, QAM256, 5.36 MSymbols/s

Pin Configuration and Description




Top View

Pin Number	Label	Description
1	RF IN	RF Input, DC blocking capacitor required
2	GND	Internally Not Connected
3	RF OUT / VDD	RF Output – VDD bias choke required
Backside Paddle	GND	Ground. Use recommended via pattern to minimize inductance and thermal resistance. See PCB Mounting Pattern for suggested footprint.


Package Outline

NOTES:

1. SHADED LEAD IS PIN 1.



Recommended Mounting Pattern



Notes:

1. Ground/thermal vias are critical for the proper performance of this device. Vias should use a .35 mm (#80/.0135") diameter drill and have a final, plated thru diameter of 0.25 mm (0.010").
2. Add as much copper as possible to inner and outer layers near the part to ensure optimal thermal performance.
3. RF trace width depends upon the PC board material and construction.
4. All dimensions are in millimeters (inches). Angles are in degrees.

Handling Precautions

Parameter	Rating	Standard
ESD – Human Body Model (HBM)	Class 1B	ESDA/JEDEC JS-001
ESD – Charged Device Model (CDM)	Class C3	ESDA/JEDEC JS-002
MSL – Moisture Sensitivity Level	Level 3	IPC/JEDEC J-STD-020



Caution!
ESD-Sensitive Device

Solderability

Compatible with both lead-free (260 °C max. reflow temp.) and tin / lead (245 °C max. reflow temp.) soldering processes.
Solder profiles available upon request.

Contact plating: NiPdAu

RoHS Compliance

This part is compliant with 2011/65/EU RoHS directive (Restrictions on the Use of Certain Hazardous Substances in Electrical and Electronic Equipment) as amended by Directive 2015/863/EU.

This product also has the following attributes:

- Lead Free
- Halogen Free (Chlorine, Bromine)
- Antimony Free
- TBBP-A (C₁₅H₁₂Br₄O₂) Free
- SVHC Free
- PFOS Free



Contact Information

For the latest specifications, additional product information, worldwide sales and distribution locations:

Tel: 1-844-890-8163

Web: www.qorvo.com

Email: customer.support@qorvo.com

Important Notice

The information contained herein is believed to be reliable; however, Qorvo makes no warranties regarding the information contained herein and assumes no responsibility or liability whatsoever for the use of the information contained herein. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for Qorvo products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information. **THIS INFORMATION DOES NOT CONSTITUTE A WARRANTY WITH RESPECT TO THE PRODUCTS DESCRIBED HEREIN, AND QORVO HEREBY DISCLAIMS ANY AND ALL WARRANTIES WITH RESPECT TO SUCH PRODUCTS WHETHER EXPRESS OR IMPLIED BY LAW, COURSE OF DEALING, COURSE OF PERFORMANCE, USAGE OF TRADE OR OTHERWISE, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.**

Without limiting the generality of the foregoing, Qorvo products are not warranted or authorized for use as critical components in medical, life-saving, or life-sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.

Copyright 2019 © Qorvo, Inc. | Qorvo is a registered trademark of Qorvo, Inc.