

COAXIAL TERMINATIONS



TNC

1 to 2 WATTS

Part Number	Power		Frequency range (GHz)	V.S.W.R. (MAX)							Impedance (Ω)	Type	Obs
	avg (W)	peak (W)		DC-0.5	0.5-1	1-2.5	2.5-4	4-8	8-12.4	12.4-18			
R404021000	1	500	DC-1	1.08	1.15						50 $\pm$ 2%	M	
R404021120	1	500	DC-1	1.08	1.15						50 $\pm$ 2%	M	1
R404024000	1	500	DC-1	1.08	1.15						50 $\pm$ 2%	F	
R404024120	1	500	DC-1	1.08	1.15						50 $\pm$ 2%	F	1
R404022000	1	500	DC-1	1.08	1.15						75 $\pm$ 2%	M	4
R404022120	1	500	DC-1	1.08	1.15						75 $\pm$ 2%	M	1-4
R404023000	1	500	DC-1	1.08	1.15						75 $\pm$ 2%	F	4
R404023120	1	500	DC-1	1.08	1.15						75 $\pm$ 2%	F	1-4
R404121000	1	500	DC-2.5	1.08		1.20					50 $\pm$ 2%	M	
R404121120	1	500	DC-2.5	1.08		1.20					50 $\pm$ 2%	M	1
R404122000	1	500	DC-2.5	1.08		1.20					50 $\pm$ 2%	F	
R404122120	1	500	DC-2.5	1.08		1.20					50 $\pm$ 2%	F	1
R404120000	1	500	DC-8		1.10		1.20	1.25			50 $\pm$ 5%	M	3
R404120120	1	500	DC-8		1.10		1.20	1.25			50 $\pm$ 5%	M	1-3
R404225000	1	500	DC-12.4		1.10			1.15	1.25		50 $\pm$ 5%	M	
R404225120	1	500	DC-12.4		1.10			1.15	1.25		50 $\pm$ 5%	M	1
R404225121	1	500	DC-12.4		1.10			1.15	1.25		50 $\pm$ 5%	M	2
R404370000	2	100	DC-18		1.08			1.10	1.15	1.20	50 $\pm$ 5%	M	
R404370120	2	100	DC-18		1.08			1.10	1.15	1.20	50 $\pm$ 5%	M	1
R404375000	2	100	DC-18				1.20				50 $\pm$ 5%	F	

OBS : 1) With 2.75" (70 mm) Bead Chain
2) With 2.75" (70 mm) Cord

3) VSWR < 1.10 up to 2 GHz
4) 75 Ohms connector



Part Number	A inch (mm)	B inch (mm)	Weight (g)
R404021000	1.02" (26)	.57" (14.5)	16
R404021120	1.18" (30)		20
R404022000	1.02" (26)		16
R404022120	1.18" (30)		20
R404023000	1.14" (29)	.43" (11)	15
R404023120	1.30" (33)		20
R404024000	1.14" (29)		15
R404024120	1.30" (33)		20
R404120000	1.26" (32)	.57" (14.5)	15
R404120120			20

Part Number	A inch (mm)	B inch (mm)	Weight (g)
R404121000	1.06" (27)	.57" (14.5)	16
R404121120	1.18" (30)		20
R404122000	1.14" (29)	.43" (11)	15
R404122120	1.30" (33)		20
R404225000	1.26" (32)	.57" (14.5)	15
R404225120			20
R404225121			
R404370000	.98" (25)	.63" (16)	23
R404370120	1.10" (28)		25
R404375000	.90" (23)	.51" (13)	15