

STRAIGHT FEMALE PANEL RECEPTACLES (captive center contact)





Fig. 1





Fig. 2

Part number	Fig.	Imp. (Ω)	Dimensions (mm)		Panel drilling	Finish	Note
			A	B			
R113 402 220	1	50	8.7	4.8	P03	BBR	Press-in mount
R113 553 000	2		8.65	2.5	P02	Gold	Recessed front mount

STRAIGHT MALE PCB RECEPTACLES (captive center contact)



Part number	Imp. (Ω)	Dimensions (mm)			Panel drilling	Finish
		A	B	C		
R113 425 000	50	9.65	4.1	0.98	P05	Gold

STRAIGHT FEMALE PCB RECEPTACLES (captive center contact)





Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5

Part number	Fig.	Imp. (Ω)	Dimensions (mm)			Assembly instructions	Panel drilling	Finish	Note
			A	B	C				
R113 423 000	1	50	6.9	1.4	0.5	M01	P05	Gold	SMT/Edge-card
R113 424 000	2		5.9	4.7	0.96				SMT
R113 424 010									SMT/reel 100 pieces
R113 424 020									SMT/reel 500 pieces
R113A 424 020					SMT/reel 500 pieces ECO version				
R113 426 000	3		10	4.1	0.98		100 pieces ECO version		
R113A 426 000							BBR		
R113 426 020									
R113 427 000	4		9	3	0.5		P06	Gold	Space saving on PCB
R213 426 000	3	75	10	4.1	0.71		P05	Gold	
R213 424 800	5					M01		Gold	SMT/reel 100 pieces

To download data sheets and assembly instructions, visit www.radiall.com & enter the part number in the Search box.

Bold part numbers represent products typically in stock & available for immediate shipment.

See page 8 and 9 for packaging information.