

# UPD78F1505AGC-UEU-AX

User's Manual: Hardware

Overview

Design Support

Documentation

Sample Code

Software & Tools

Ordering

## PARAMETRICS

Parameters	UPD78F1505AGC-UEU-AX
<b>Package</b>	
Pin Count	100
Package Type	LFQFP
<b>Memory</b>	
Program memory	128 KB Flash memory
RAM	7 KB
<b>CPU (Bit, Clock, DMA, External Bus etc)</b>	
CPU	78K0R (16-bit)
Max. Frequency	20 MHz
Sub-Clock (32.768 kHz)	YES
On-chip Oscillator Freq.	20, 8, 1 MHz
Power-On Reset	YES
Low Voltage Detection	YES
DMA Remarks	DMAC x 2 ch
External Interrupt Pins	12
I/O Ports	65
<b>Timers</b>	
16-bit Timers	12 ch
Watchdog Timers	1 ch
PWM Output	7
<b>Analog</b>	
A/D Converters	12-bit x 12 ch
D/A Converters	12-bit x 2 ch
<b>Interfaces</b>	
CSIs	3 ch
UARTs	4 ch
I2Cs	3 ch
LIN	1 ch
<b>Display Functions</b>	
LCD Remarks	seg=36, com=8
<b>Operating Conditions</b>	
Operating Voltage	1.8 to 5.5 V
Operating Temperature	-40 to 85 °C (Ambient Temperature)
<b>Remarks</b>	
Remarks	100-pin 16-bit single-chip microcontroller (78K0R/LG3)

[View Less](#)

### Need More Help?

Contact Us Website Feedback  
Forums Videos  
Knowledgebase

### About Renesas

News  
Investors  
Careers

### Follow Us

Facebook YouTube  
Twitter LinkedIn