


AX SERIES

UPGRADE

105°C Ultra Miniaturized

◆FEATURES

- Suitable for AC-adaptor of portable device.
- Load Life: 105°C, 1000~2000 hours.
- RoHS compliance.



◆SPECIFICATIONS

Items	Characteristics								
Category Temperature Range	-40~+105℃								
Rated Voltage Range	6.3~35, 400Vdc								
Capacitance Tolerance	±20% (20℃, 120Hz)								
Leakage Current(MAX)	6.3~35Vdc				400Vdc				
	I=0.01CV or 3μA whichever is greater. (After 2 minutes application of rated voltage)				I=0.04CV+100μA (After 1 minute application of rated voltage) I=0.02CV+25μA (After 5 minutes application of rated voltage)				
	I=Leakage Current(μA)				C=Capacitance(μF)		V=Rated Voltage(Vdc)		
(tanδ) Dissipation Factor(MAX)	Rated Voltage (Vdc)	6.3	8	10	16	25	35	400	(20℃, 120Hz)
	tanδ	0.22	0.20	0.19	0.16	0.14	0.12	0.25	
Endurance	After applying rated voltage with rated ripple current for specified time at 105℃, the capacitors shall meet the following requirements.								
	Capacitance Change		Within ±25% of the initial value.				Case Size	Life Time (hrs)	
	Dissipation Factor		Not more than 200% of the specified value.				L≤7.5	1000	
	Leakage Current		Not more than the specified value.				L≥9	2000	
Low Temperature Stability Impedance Ratio(MAX)	Rated Voltage (Vdc)	6.3	8	10	16	25	35	400	(120Hz)
	Z (-25℃)/Z (20℃)	2	2	2	2	2	2	6	
	Z (-40℃)/Z (20℃)	12	12	12	10	8	6	10	

◆MULTIPLIER FOR RIPPLE CURRENT

6.3~35Vdc

Frequency (Hz)		120	1k	10k	100k≤
Coefficient	68~82μF	0.21	0.73	0.92	1.00
	150~270μF	0.36	0.73	0.92	1.00
	330~750μF	0.55	0.77	0.94	1.00
	820~1200μF	0.60	0.80	0.96	1.00

400Vdc

Frequency (Hz)		60(50)	120	500	1k	10k≤
Coefficient	4.7~8.2μF	0.65	1.00	1.20	1.30	1.50
	10~24μF	0.80	1.00	1.20	1.30	1.50

◆OPTION


	Code
PET Sleeve	EFC

◆PART NUMBER

□□□	AX	□□□	M	□□□	□□	D×L
Rated Voltage	Series	Capacitance	Capacitance Tolerance	Option	Lead Forming	Case Size

◆DIMENSIONS

(mm)



◆STANDARD SIZE

Rated Voltage (Vdc)	Capacitance (μF)	Size φD×L(mm)	Rated ripple current (mA r.m.s./105°C,100kHz)	Impedance (Ω MAX/20°C,100kHz)
6.3	82	5×7	510	0.25
	220	6.3×7	720	0.13
		5×11	800	0.14
	470	8×7.5	1080	0.065
		6.3×11	1140	0.067
	680	8×9	1360	0.049
	820	8×10.8	1600	0.042
	1000	8×16	2010	0.027
		10×9	1540	0.036
1200	10×12.5	1970	0.025	
8	75	5×7	510	0.25
	200	6.3×7	720	0.13
		5×11	800	0.14
	390	8×7.5	1080	0.065
	430	6.3×11	1140	0.067
	620	8×9	1360	0.049
	750	8×10.8	1600	0.042
	910	8×16	2010	0.027
		10×9	1540	0.036
1100	10×12.5	1970	0.025	
10	68	5×7	510	0.25
	180	6.3×7	720	0.13
		5×11	800	0.14
	330	8×7.5	1080	0.065
	390	6.3×11	1140	0.067
	560	8×9	1360	0.049
	680	8×10.8	1600	0.042
	820	8×16	2010	0.027
		10×9	1540	0.036
1000	10×12.5	1970	0.025	

Rated Voltage (Vdc)	Capacitance (μF)	Size φD×L(mm)	Rated ripple current (mA r.m.s./105°C,100kHz)	Impedance (Ω MAX/20°C,100kHz)
16	390	8×9	1360	0.049
	470	8×10.8	1600	0.042
	560	8×16	2010	0.027
		10×9	1540	0.036
	680	10×12.5	1970	0.025
	1000	10×16	2480	0.019
25	220	8×9	1360	0.049
	270	8×10.8	1600	0.042
	390	8×16	2010	0.027
		10×9	1540	0.036
	470	10×12.5	1970	0.025
	680	10×16	2480	0.019
35	150	8×9	1360	0.049
	180	8×10.8	1600	0.042
	220	8×16	2010	0.027
		10×9	1540	0.036
	270	10×12.5	1970	0.025
	390	10×16	2480	0.019

Rated Voltage (Vdc)	Capacitance (μF)	Size φD×L(mm)	Rated ripple current (mA r.m.s./105°C,120Hz)
400	4.7	6.3×14	50
		8×9	
	6.8	8×10.8	70
	7.5	8×10.8	75
	8.2	8×16	85
		10×9	
	10	8×16	90
		10×12.5	100
	12	10×12.5	110
		8×20	120
	15	8×20	130
		10×16	150
	18	10×16	150
	22	12.5×16	180
24	12.5×16	190	