



ERM5-040-02.0-L-DV-P-TR



ERM5-020-05.0-L-DV-K-TR



ERM5 SERIES

(0.50 mm) .0197"

RUGGED HIGH-SPEED HEADER

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?ERM5

Insulator Material:

Black LCP

Terminal Material:

Phosphor Bronze or BeCu

Plating:

Au or Sn over

50 μ" (1.27 μm) Ni

Current Rating (-DV to -DV):

1.5 A per pin

(1 pin powered per row)

Current Rating (-DV to -RA):

1.6 A per pin

(1 pin powered per row)

Operating Temp Range:

-55 °C to +125 °C

Voltage Rating:

194 VAC mated with ERF5

RoHS Compliant:


Yes

Mates with:
ERF5



20 to 150 I/Os

Rugged Edge Rate® contacts for reduced broadside coupling



HIGH-SPEED CHANNEL PERFORMANCE

ERM5/ERF5 @ 7 mm Mated Stack Height

Rating based on Samtec reference channel. For full SI performance data visit Samtec.com or contact SIG@samtec.com

26
Gbps

7 mm, 9 mm, 10 mm, 11 mm or 12 mm stack height

PROCESSING

Lead-Free Solderable:

Yes

SMT Lead Coplanarity:

(0.10 mm) .004" max (010-040)
(0.13 mm) .005" max (050-075)

RECOGNITIONS

For complete scope of recognitions see www.samtec.com/quality



FILE NO. E111594



ALSO AVAILABLE (MOQ Required)

- Friction Lock
 - Weld Tab
 - Other platings
- Contact Samtec.

ERM5	NO. OF POSITIONS PER ROW	LEAD STYLE	PLATING OPTION	DV	PICK & PLACE PAD	TR
	-010, -020, -030, -040, -050, -060, -070, -075	-02.0 = 2 mm Body Height -04.0 = 4 mm Body Height -05.0 = 5 mm Body Height	-L = 10 μ" (0.25 μm) Gold on contact, Matte Tin on tail		-K = (3.50 mm) .138" DIA Polyimide Film Pick & Place Pad (-04.0 & -05.0 lead style only) -P = Plastic Pick & Place Pad (-02.0 lead style only) (-010 positions not available)	

MATED HEIGHT*		
ERM5 LEAD STYLE	ERF5 LEAD STYLE	
	-05.0	-07.0
-02.0	(7.00) .276	(9.00) .354
-04.0	(9.00) .354	(11.00) .433
-05.0	(10.00) .394	(12.00) .472

*Processing conditions will affect mated height.



LEAD STYLE	A	B
-02.0	(1.94) .076	(4.84) .191
-04.0	(3.94) .155	(6.84) .269
-05.0	(4.94) .194	(7.84) .309

Notes:
Patented

Some lengths, styles and options are non-standard, non-returnable.