

REVISION E

DESIGNED AND DIMENSIONED IN INCHES[MILLIMETERS]
ALL DIMENSIONS REFERENCE EXCEPT AS SHOWN

DO NOT
SCALE FROM
THIS PRINT

240-J-P-EP-ST-CMM-X-X

SERIES

240: 2.40MM

GENDER

-J: JACK

TYPE

-P: PCB

PACKAGING

-BLANK: INDIVIDUALLY BAGGED
-B: FULL TRAY (QTY = 100 MIN OR MULTIPLES OF 100)

OPTION

-1: OPTION 1 (WITHOUT SCREWS)
-2: OPTION 2 (FOR PCB THICKNESS .016" TO .125")
-3: OPTION 3 (FOR PCB THICKNESS .069" TO .178")

TERMINATION







-CMM: COMPRESSION MOUNT MICROSTRIP

ORIENTATION

-ST: STRAIGHT

FINISH

-EP: 50μ" EXTRA HEAVY GOLD
CENTER CONTACT, PASSIVATED
OUTER CONTACT



RECOMMENDED PCB LAYOUT (SEE NOTE 2)

FIG 1

240-J-P-EP-ST-CMM-X-X SHOWN

NOTES:

1. RECOMMENDED MOUNTING TORQUE 0.5~0.8 INCH-POUNDS.
2. THIS IS A GENERAL FOOTPRINT AND IS NOT OPTIMIZED FOR ELECTRICAL PERFORMANCE, CONTACT SIG@SAMTEC.COM FOR ASSISTANCE WITH ELECTRICAL LAYOUT.

PROPRIETARY NOTE

THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION AND ALL DESIGN, MANUFACTURING, REPRODUCTION, USE, PATENT RIGHTS AND SALES RIGHTS ARE EXPRESSLY RESERVED BY SAMTEC, INC. THIS DOCUMENT SHALL NOT BE DISCLOSED, IN WHOLE OR PART, TO ANY UNAUTHORIZED PERSON OR ENTITY NOR REPRODUCED, TRANSFERRED OR INCORPORATED IN ANY OTHER PROJECT IN ANY MANNER WITHOUT THE EXPRESS WRITTEN CONSENT OF SAMTEC, INC.

MATERIAL:

BODY, BUSHING & SCREW: STAINLESS STEEL
SOCKET: COPPER ALLOY

DO NOT SCALE DRAWING
SHEET SCALE: 6:1

DESCRIPTION:
2.40MM ST JACK FOR COMPRESSION MOUNT MICROSTRIP

DWG. NO.

240-J-P-EP-ST-CMM-X-X

BY: SHERRY W 2/24/2019 SHEET 1 OF 1

F:\DWG\MISC\MKTG\240-J-P-EP-ST-CMM-X-X-MKT.SLDDRW

samtec

520 PARK EAST BLVD, NEW ALBANY, IN 47150
PHONE: 812-944-6733 FAX: 812-948-5047
e-Mail: info@SAMTEC.com code: 55322