

DESIGNED AND DIMENSIONED IN INCHES[MILLIMETERS]
ALL DIMENSIONS REFERENCE EXCEPT AS SHOWN

DO NOT
SCALE FROM
THIS PRINT








FIG 1
-08: 8 ROW
(SEAFC-20-5.0-X-08-1-N-K-XR SHOWN)
(SOME CENTER FEATURES REMOVED FOR CLARITY)



SEAFC-XX-X.X-X-XX-X-X-K-XR

No OF POSITIONS

-20, -30, -40, -50
(PER ROW)

LEAD STYLE

-5.0: .199 [5.05] HEIGHT
* -6.0: .238 [6.05] HEIGHT
-6.5: .258 [6.55] HEIGHT
* -7.5: .297 [7.54] HEIGHT
(SEE TABLE 1)

PLATING SPECIFICATION

-S: SELECTIVE GOLD (30μ") IN CONTACT AREA,
MATTE TIN ON TAIL
-L: LIGHT GOLD (10μ") IN CONTACT AREA,
MATTE TIN ON TAIL

ROWS

-04: 4 ROWS (SEE SHT 2, FIG 2)
-06: 6 ROWS
-08: 8 ROWS (SEE FIG 1)
-10: 10 ROWS

PACKAGING (SEE NOTES 3, 4 & 7)

-TR: TAPE & REEL
-FR: FULL REEL QTY. TAPE & REEL

K-DOT

(SEE FIG 3, SHT 2)

OPTION

-N: NO LATCH
** (LEAVE BLANK FOR LATCH POST)
(SEE SHT 3, FIG 4)
(ONLY AVAILABLE WITH -5.0
LEAD STYLE, -04, -06, -08 & -10 ROW)
-PP: POLARIZATION PIN (SEE SHT 3, FIG 5)
(ONLY AVAILABLE WITH -05.0 LEAD
STYLE, 6, 8 & 10 ROWS)
(NOT AVAILABLE WITH N OPTION)

SOLDER COMPOSITION & STYLE

-1: 63% TIN / 37% LEAD
CHARGE TAIL
-2: 95.5% TIN/3.8% SILVER/.7%
COPPER **CHARGE TAIL**

* = NOT TOOLED

** = ONLY AVAILABLE WITH -5.0 LEAD STYLE,
-04, -06, -08 & -10 ROW.

TABLE 2

No OF ROWS	"B"	"D"
-04	.079 [2.01]	.223 [5.66]
-06	.120 [3.05]	.323 [8.20]
-08	.120 [3.05]	.423 [10.74]
-10	.120 [3.05]	.523 [13.28]

TABLE 1

No. OF ROWS	LEAD STYLE	"C"
-04	-5.0	.213 [5.41]
	-6.0	.252 [6.40]
	-6.5	.272 [6.91]
	-7.5	.311 [7.90]
-06, -08, -10	-5.0	.208 [5.28]
	-6.0	.247 [6.27]
	-6.5	.267 [6.78]
	-7.5	.306 [7.77]

TABLE 3

No OF POS.	"A"	"E"
-20	1.229 [31.22]	1.1410 [28.981]
-30	1.729 [43.92]	1.6410 [41.681]
-40	2.229 [56.62]	2.1410 [54.381]
-50	2.729 [69.32]	2.6410 [67.081]

NOTES:

- NOTE DELETED.
- A-PINS PROVIDED AS STANDARD.
- TAPE & REEL IS STANDARD PACKAGING.
- ATTACH LABEL -4x2 TO EACH REEL.
- SOLDER CHARGE VOLUME .00000891 CUBIC INCHES (REF).
- NON-FUNCTIONAL VOIDING IN PLASTIC BODY TO BE AT SAMTEC'S DISCRETION.
- ORDERS WILL BE PACKAGED ACCORDING TO THE SAMTEC PACKAGING EFFICIENCY STANDARDS (SPES) FOUND ON WWW.SAMTEC.COM

* PROPRIETARY NOTE *

THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION AND ALL DESIGN, MANUFACTURING, REPRODUCTION, USE, PATENT RIGHTS AND SALES RIGHTS ARE EXPRESSLY RESERVED BY SAMTEC, INC. THIS DOCUMENT SHALL NOT BE DISCLOSED, IN WHOLE OR PART, TO ANY UNAUTHORIZED PERSON OR ENTITY NOR REPRODUCED, TRANSFERRED OR INCORPORATED IN ANY OTHER PROJECT IN ANY MANNER WITHOUT THE EXPRESS WRITTEN CONSENT OF SAMTEC, INC.

MATERIAL:

INSULATOR: LCP, COLOR: BLACK
CONTACT OR TERMINAL:
SHIELD: PHOS BRONZE

DO NOT SCALE DRAWING
SHEET SCALE: 2:1

samtec

520 PARK EAST BLVD, NEW ALBANY, IN 47150
PHONE: 812-944-6733 FAX: 812-948-5047
e-Mail: info@SAMTEC.com code 55322

DESCRIPTION:

.050 PITCH SOCKET ARRAY ASSEMBLY

DWG. NO.

SEAFC-XX-X.X-X-XX-X-X-K-XR

BY: JERRY SU

04/12/2019

SHEET 1 OF 3




FIG 2
-04: 4 ROW
(SEAFC-20-5.0-X-04-1-N-K-XR SHOWN)
(DIFFERENT AS SHOWN, OTHERWISE SAME AS FIG 1)
(SOME CENTER FEATURES REMOVED FOR CLARITY)

TABLE 4						
ROWS	"G"	"H"				"J"
		20 POS	30 POS	40 POS	50 POS	
-04	.256 [6.50]	.504 [12.79]	.754 [19.14]	1.004 [25.49]	1.254 [31.84]	.017 [.43]
-06	.256 [6.50]	.504 [12.79]	.754 [19.14]	1.004 [25.49]	1.254 [31.84]	.034 [.86]
-08	.325 [8.25]	.469 [11.92]	.719 [18.27]	.969 [24.62]	1.219 [30.97]	.049 [1.24]
-10	.404 [10.25]	.430 [10.92]	.680 [17.27]	.930 [23.62]	1.180 [29.97]	.060 [1.52]





FIG 3
K-DOT
(SEAFC-20-5.0-X-08-1-N-K-XR SHOWN)
(DIFFERENT AS SHOWN, OTHERWISE SAME AS FIG 1)
(SOME CENTER FEATURES REMOVED FOR CLARITY)



-04 ROW ONLY
(DIFFERENT AS SHOWN, OTHERWISE SAME AS FIG 3)

• PROPRIETARY NOTE THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION AND ALL DESIGN, MANUFACTURING, REPRODUCTION, USE, PATENT RIGHTS AND SALES RIGHTS ARE EXPRESSLY RESERVED BY SAMTEC, INC. THIS DOCUMENT SHALL NOT BE DISCLOSED, IN WHOLE OR PART, TO ANY UNAUTHORIZED PERSON OR ENTITY NOR REPRODUCED, TRANSFERRED OR INCORPORATED IN ANY OTHER PROJECT IN ANY MANNER WITHOUT THE EXPRESS WRITTEN CONSENT OF SAMTEC, INC.		 520 PARK EAST BLVD, NEW ALBANY, IN 47150 PHONE: 812-944-6733 FAX: 812-948-5047 e-Mail info@SAMTEC.com code 55322	
DO NOT SCALE DRAWING SHEET SCALE: 2:1		DESCRIPTION: .050 PITCH SOCKET ARRAY ASSEMBLY	
		DWG. NO. SEAFC-XX-X.X-X-XX-X-X-K-XR	
BY: JERRY SU 04/12/2019		SHEET 2 OF 3	





FIG 4
LATCH POST OPTION
(SEAF-20-5.0-X-06-1-K-XR SHOWN)
(SOME CENTER FEATURES REMOVED FOR CLARITY)
(DIFFERENT AS SHOWN, OTHERWISE SAME AS FIG 1)
(LATCH POST OPTION REQUIRED FOR SEAC MATE ONLY)
(ONLY AVAILABLE WITH -5.0 LEAD STYLE -04, -06, -08 & -10 ROW)




FIG 5
-PP OPTION
(SEAF-20-5.0-X-06-1-PP-K-XR SHOWN)
(SOME CENTER FEATURES REMOVED FOR CLARITY)
(SAME AS FIG 5 EXCEPT AS SHOWN)
(-PP OPTION VALID FOR SEAR MATE ONLY)
(ONLY AVAILABLE WITH -05.0 LEAD STYLE 6, 8 & 10 ROW)




TABLE 5		
No OF POS.	"K"	"L"
-20	1.762 [44.75]	1.533 [38.94]
-30	2.262 [57.45]	2.033 [51.64]
-40	2.762 [70.15]	2.533 [64.34]
-50	3.262 [82.85]	3.033 [77.04]

PROPRIETARY NOTE
THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION AND ALL DESIGN, MANUFACTURING, REPRODUCTION, USE, PATENT RIGHTS AND SALES RIGHTS ARE EXPRESSLY RESERVED BY SAMTEC, INC. THIS DOCUMENT SHALL NOT BE DISCLOSED, IN WHOLE OR PART, TO ANY UNAUTHORIZED PERSON OR ENTITY NOR REPRODUCED, TRANSFERRED OR INCORPORATED IN ANY OTHER PROJECT IN ANY MANNER WITHOUT THE EXPRESS WRITTEN CONSENT OF SAMTEC, INC.

DO NOT SCALE DRAWING

SHEET SCALE: 3:1

samtec

520 PARK EAST BLVD, NEW ALBANY, IN 47150
PHONE: 812-944-6733 FAX: 812-948-5047
e-Mail: info@SAMTEC.com code 55322

DESCRIPTION:
.050 PITCH SOCKET ARRAY ASSEMBLY
DWG. NO.
SEAF-XX-X.X-X-XX-X-X-K-XR
BY: JERRY SU 04/12/2019 SHEET 3 OF 3