

SMP TO 40 GHz

SMP Board Connectors

SMP-TH, SMP-EM,
SMP-MT, SMP-SM

Cable Mates:

RF047-A, RF086,
RF23C, RF405, RF25S



SMP	GENDER	TYPE	PLATING	ORIENTATION	TERMINATION
-----	--------	------	---------	-------------	-------------

-PF
= Plug, Full Detent

-PL
= Plug, Limited Detent

-PS
= Plug, Smooth Bore

-PC
= Plug, Catcher's Mitt

-P
= PCB Mount

-HG
= 30 μ " (0.76 μ m)
Gold center contact,
10 μ " (0.25 μ m)
Gold outer body

-ST
= Straight


-SM
= Surface Mount

-TH"X"
= Through-hole
(Specify "X"
from chart)


-MT"X"
= Mixed Technology
(Specify "X"
from chart)

-EM
= Edge Mount
(-PF, -PL & -PS only)


OPTION (X)	A (HEIGHT DIM.)	BOARD THICKNESS
1 (-MT only)	(5.88) .2315	(1.60 mm) .062" PCB
2 (-MT only)	(6.72) .2645	(2.36 mm) .093" PCB
3 (-TH only)	(5.88) .2315	(1.60 mm) .062" PCB
4 (-TH only)	(6.72) .2645	(2.36 mm) .093" PCB




-SM



-TH(X)



-MT(X)



-EM

ALSO AVAILABLE

Low Frequency options.
Contact RFGroup@samtec.com

SMP Bullet Adaptor

SMP-B



SMP	J	TYPE	PLATING	ORIENTATION	BULLET LENGTH
-----	---	------	---------	-------------	---------------

-B
= Bullet Adaptor

-HG
= 30 μ " (0.76 μ m)
Gold center contact,
10 μ " (0.25 μ m)
Gold outer body

-ST
= Straight

-0625
= (6.25 mm) .246"

-0645
= (6.45 mm) .254"


-0725
= (7.25 mm) .285"

-0825
= (8.25 mm) .325"


-0925
(9.25 mm) .364"

-1325
(13.25 mm) .522"


-1450
= (14.50 mm) .571"




-0625




-0645




-0725




-0825



-0925



-1325



-1450