



MCP-8-02-L-01.00-T-S

MCP-8 SERIES

IP67 SEALED 8 SERIES CABLE ASSEMBLY

FEATURES

- IP67 dust and water protected when submerged 1 m deep for 30 minutes
- Lightweight plastic shell
- Push-pull latching system
- Molded-in grooves to prevent hand slippage
- Polarizing keys protect from mis-alignment
- Visual alignment indicators
- Cable-to-cable or cable-to-panel solutions

Mates with:
MCR(K)-8, MCP(K)-8

SPECIFICATIONS

For complete specifications see www.samtec.com?MCP-8

Insulator Material:
PPS
Terminal Material:
Phosphor Bronze
Contact Material:
Phosphor Bronze
Gasket Material:
Silicone
Spring Material:
Stainless Steel
Coupling Ring Spacer:
PBT
Cable Clamp:
POM
RoHS Compliant:
Yes



MCP	8	LEAD STYLE	PLATING	LENGTH	END 1 OPTION	END 2 OPTION
	-02	= 12 positions, 28 AWG	-L = 10µ" (0,25 µm) Gold on contact area	-01.00 = 1 meter -02.00 = 2 meters Standard lengths	-T = Terminal -S = Socket (Not available with End 2 -T)	-T = Terminal -S = Socket -BC = Blunt Cut


DUST CAPS

- -S (Socket) = DCA-MCR-8
 - -T (Terminal) = DCA-MCP-8
- Visit sealedio.samtec.com for a complete list of sealed systems

ALSO AVAILABLE (MOQ Required)

- Other lengths
- Contact Samtec.

Note:
Samtec's MCP-8 Series is dual sourced by Hirose Electric Co., LTD.



Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM