

Document Title

**64Kx16 Bit High Speed Static RAM(5.0V Operating), Revolutionary Pin out.
Operated at Commercial and Industrial Temperature Ranges.**

Revision History

| <u>RevNo.</u> | <u>History</u> | <u>Draft Data</u> | <u>Remark</u> |
|---------------|--|------------------------------------|-----------------------------------|
| Rev. 0.0 | Initial release with Design Target. | Apr. 1st, 1997 | Design Target |
| Rev. 1.0 | Release to Preliminary Data Sheet. 1.1. Replace Design Target to Preliminary. | Jun. 1st, 1997 | Preliminary |
| Rev. 2.0 | Release to Final Data Sheet. 2.1. Delete Preliminary. 2.2. Delete L-version. 2.3. Delete Data Retention Characteristics and Waveform. 2.4. Add Capacitive load of the test environment in A.C test load. 2.5. Change D.C characteristics. | Feb. 25th, 1998 | Final |
| | Items | Previous spec. (8/10/12ns part) | Changed spec. (8/10/12ns part) |
| | Icc | 200/190/180mA | 200/195/190mA |
| | ISB | 30mA | 50mA |

The attached data sheets are prepared and approved by SAMSUNG Electronics. SAMSUNG Electronics CO., LTD. reserve the right to change the specifications. SAMSUNG Electronics will evaluate and reply to your requests and questions on the parameters of this device. If you have any questions, please contact the SAMSUNG branch office near your office, call or contact Headquarters.



64K x 16 Bit High-Speed CMOS Static RAM


FEATURES

- Fast Access Time 8,10,12ns(Max.)
- Low Power Dissipation
 - Standby (TTL) : 50mA(Max.)
 - (CMOS) : 10mA(Max.)
 - Operating K6R1016C1B-8 : 200mA(Max.)
 - K6R1016C1B-10 : 195mA(Max.)
 - K6R1016C1B-12 : 190mA(Max.)
- Single 5.0V±10% Power Supply
- TTL Compatible Inputs and Outputs
- I/O Compatible with 3.3V Device
- Fully Static Operation
 - No Clock or Refresh required
- Three State Outputs
- Center Power/Ground Pin Configuration
- Data Byte Control : LB : I/O₁~ I/O₈, UB : I/O₉~ I/O₁₆
- Standard Pin Configuration
 - K6R1016C1B-J : 44-SOJ-400
 - K6R1016C1B-T : 44-TSOP2-400BF

GENERAL DESCRIPTION

The K6R1016C1B is a 1,048,576-bit high-speed Static Random Access Memory organized as 65,536 words by 16 bits. The K6R1016C1B uses 16 common input and output lines and has at output enable pin which operates faster than address access time at read cycle. Also it allows that lower and upper byte access by data byte control (UB, LB). The device is fabricated using SAMSUNG's advanced CMOS process and designed for high-speed circuit technology. It is particularly well suited for use in high-density high-speed system applications. The K6R1016C1B is packaged in a 400mil 44-pin plastic SOJ or TSOP2 forward.


PIN CONFIGURATION (Top View)



ORDERING INFORMATION

| | |
|------------------------|------------------|
| K6R1016C1B -C8/C10/C12 | Commercial Temp. |
| K6R1016C1B-I8/I10/I12 | Industrial Temp. |

FUNCTIONAL BLOCK DIAGRAM



PIN FUNCTION

| Pin Name | Pin Function |
|--------------|--|
| A0 - A15 | Address Inputs |
| WE | Write Enable |
| CS | Chip Select |
| OE | Output Enable |
| LB | Lower-byte Control(I/O ₁ ~I/O ₈) |
| UB | Upper-byte Control(I/O ₉ ~I/O ₁₆) |
| I/O1 ~ I/O16 | Data Inputs/Outputs |
| Vcc | Power(+5.0V) |
| Vss | Ground |
| N.C | No Connection |

ABSOLUTE MAXIMUM RATINGS*

| Parameter | | Symbol | Rating | Unit |
|---------------------------------------|------------|------------------------------------|-------------|------|
| Voltage on Any Pin Relative to Vss | | V _{IN} , V _{OUT} | -0.5 to 7.0 | V |
| Voltage on Vcc Supply Relative to Vss | | V _{CC} | -0.5 to 7.0 | V |
| Power Dissipation | | P _D | 1.0 | W |
| Storage Temperature | | T _{STG} | -65 to 150 | °C |
| Operating Temperature | Commercial | T _A | 0 to 70 | °C |
| | Industrial | T _A | -40 to 85 | °C |

* Stresses greater than those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operating sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect reliability.

RECOMMENDED DC OPERATING CONDITIONS*(T_A= to 70°C)

| Parameter | Symbol | Min | Typ | Max | Unit |
|--------------------|-----------------|-------|-----|------------------------|------|
| Supply Voltage | V _{CC} | 4.5 | 5.0 | 5.5 | V |
| Ground | V _{SS} | 0 | 0 | 0 | V |
| Input High Voltage | V _{IH} | 2.2 | - | V _{CC} +0.5** | V |
| Input Low Voltage | V _{IL} | -0.5* | - | 0.8 | V |

* The above parameters are also guaranteed at industrial temperature range.

** V_{IL}(Min) = -2.0V a.c(Pulse Width ≤ 6ns) for I ≤ 20mA.

*** V_{IH}(Max) = V_{CC} + 2.0V a.c (Pulse Width ≤ 6ns) for I ≤ 20mA.

DC AND OPERATING CHARACTERISTICS*(T_A=0 to 70°C, V_{CC}=5.0V±10%, unless otherwise specified)

| Parameter | Symbol | Test Conditions | | Min | Max | Unit |
|---------------------------|---------------------|--|------|-----|------|------|
| Input Leakage Current | I _{LI} | V _{IN} =V _{SS} to V _{CC} | | -2 | 2 | μA |
| Output Leakage Current | I _{LO} | $\overline{CS}=V_{IH}$ or $\overline{OE}=V_{IH}$ or $\overline{WE}=V_{IL}$ V _{OUT} =V _{SS} to V _{CC} | | -2 | 2 | μA |
| Operating Current | I _{CC} | Min. Cycle, 100% Duty $\overline{CS}=V_{IL}$, V _{IN} = V _{IH} or V _{IL} , I _{OUT} =0mA | 8ns | - | 200 | mA |
| | | | 10ns | - | 195 | |
| | | | 12ns | - | 190 | |
| Standby Current | I _{SB} | Min. Cycle, $\overline{CS}=V_{IH}$ | | - | 50 | mA |
| | I _{SB1} | f=0MHz, $\overline{CS} \geq V_{CC}-0.2V$, V _{IN} ≥V _{CC} -0.2V or V _{IN} ≤0.2V | | - | 10 | |
| Output Low Voltage Level | V _{OL} | I _{OL} =8mA | | - | 0.4 | V |
| Output High Voltage Level | V _{OH} | I _{OH} =-4mA | | 2.4 | - | V |
| | V _{OH1} ** | I _{OH1} =-0.1mA | | - | 3.95 | V |

* The above parameters are also guaranteed at industrial temperature range.

** V_{CC}=5.0V±5%, Temp.=25°C.

CAPACITANCE*(T_A=25°C, f=1.0MHz)

| Item | Symbol | Test Conditions | MIN | Max | Unit |
|--------------------------|------------------|----------------------|-----|-----|------|
| Input/Output Capacitance | C _{I/O} | V _{I/O} =0V | - | 8 | pF |
| Input Capacitance | C _{IN} | V _{IN} =0V | - | 6 | pF |

* Capacitance is sampled and not 100% tested.


AC CHARACTERISTICS (TA=0 to 70°C, VCC=5.0V±10%, unless otherwise noted.)

TEST CONDITIONS*

| Parameter | Value |
|--|-----------|
| Input Pulse Levels | 0V to 3V |
| Input Rise and Fall Times | 3ns |
| Input and Output timing Reference Levels | 1.5V |
| Output Loads | See below |


* The above test conditions are also applied at industrial temperature range.

Output Loads(A)



Output Loads(B)

for tHZ, tLZ, tWHZ, tOW, tOLZ & tOHZ



* Capacitive Load consists of all components of the test environment.

* Including Scope and Jig Capacitance

READ CYCLE*

| Parameter | Symbol | K6R1016C1B-8 | | K6R1016C1B-10 | | K6R1016C1B-12 | | Unit |
|---------------------------------|--------|--------------|-----|---------------|-----|---------------|-----|------|
| | | Min | Max | Min | Max | Min | Max | |
| Read Cycle Time | tRC | 8 | - | 10 | - | 12 | - | ns |
| Address Access Time | tAA | - | 8 | - | 10 | - | 12 | ns |
| Chip Select to Output | tCO | - | 8 | - | 10 | - | 12 | ns |
| Output Enable to Valid Output | tOE | - | 4 | - | 5 | - | 6 | ns |
| UB, LB Access Time | tBA | - | 4 | - | 5 | - | 6 | ns |
| Chip Enable to Low-Z Output | tLZ | 3 | - | 3 | - | 3 | - | ns |
| Output Enable to Low-Z Output | tOLZ | 0 | - | 0 | - | 0 | - | ns |
| UB, LB Enable to Low-Z Output | tBLZ | 0 | - | 0 | - | 0 | - | ns |
| Chip Disable to High-Z Output | tHZ | 0 | 4 | 0 | 5 | 0 | 6 | ns |
| Output Disable to High-Z Output | tOHZ | 0 | 4 | 0 | 5 | 0 | 6 | ns |
| UB, LB Disable to High-Z Output | tBHZ | 0 | 4 | 0 | 5 | 0 | 6 | ns |
| Output Hold from Address Change | tOH | 3 | - | 3 | - | 3 | - | ns |


* The above parameters are also guaranteed at industrial temperature range.


WRITE CYCLE*

| Parameter | Symbol | K6R1016C1B-8 | | K6R1016C1B-10 | | K6R1016C1B-12 | | Unit |
|---|--------|--------------|-----|---------------|-----|---------------|-----|------|
| | | Min | Max | Min | Max | Min | Max | |
| Write Cycle Time | tWC | 8 | - | 10 | - | 12 | - | ns |
| Chip Select to End of Write | tCW | 6 | - | 7 | - | 8 | - | ns |
| Address Set-up Time | tAS | 0 | - | 0 | - | 0 | - | ns |
| Address Valid to End of Write | tAW | 6 | - | 7 | - | 8 | - | ns |
| Write Pulse Width (\overline{OE} High) | tWP | 6 | - | 7 | - | 8 | - | ns |
| Write Pulse Width (\overline{OE} Low) | tWP1 | 8 | - | 10 | - | 12 | - | ns |
| \overline{UB} , \overline{LB} Valid to End of Write | tBW | 6 | - | 7 | - | 8 | - | ns |
| Write Recovery Time | tWR | 0 | - | 0 | - | 0 | - | ns |
| Write to Output High-Z | tWHZ | 0 | 4 | 0 | 5 | 0 | 6 | ns |
| Data to Write Time Overlap | tDW | 4 | - | 5 | - | 6 | - | ns |
| Data Hold from Write Time | tDH | 0 | - | 0 | - | 0 | - | ns |
| End Write to Output Low-Z | tOW | 3 | - | 3 | - | 3 | - | ns |

* The above parameters are also guaranteed at industrial temperature range.


TIMMING DIAGRAMS



TIMING WAVEFORM OF READ CYCLE(1) (Address Controlled, $\overline{CS}=\overline{OE}=V_{IL}$, $\overline{WE}=V_{IH}$, \overline{UB} , $\overline{LB}=V_{IL}$)


TIMING WAVEFORM OF READ CYCLE(2) ($\overline{WE}=V_{IH}$)

NOTES(READCYCLE)

1. \overline{WE} is high for read cycle.
2. All read cycle timing is referenced from the last valid address to the first transition address.
3. t_{HZ} and t_{OH} are defined as the time at which the outputs achieve the open circuit condition and are not referenced to V_{OH} or V_{OL} levels.
4. At any given temperature and voltage condition, $t_{HZ}(\text{Max})$ is less than $t_{LZ}(\text{Min})$ both for a given device and from device to device.
5. Transition is measured $\pm 200\text{mV}$ from steady state voltage with Load(B). This parameter is sampled and not 100% tested.
6. Device is continuously selected with $\overline{CS}=V_{IL}$.
7. Address valid prior to coincident with \overline{CS} transition low.
8. For common I/O applications, minimization or elimination of bus contention conditions is necessary during read and write cycle.

TIMING WAVEFORM OF WRITE CYCLE(1) (\overline{OE} Clock)

TIMING WAVEFORM OF WRITE CYCLE(2) (\overline{OE} = Low fixed)TIMING WAVEFORM OF WRITE CYCLE(3) (\overline{CS} = Controlled)

TIMING WAVEFORM OF WRITE CYCLE(4) (\overline{UB} , \overline{LB} Controlled)

NOTES(WRITE CYCLE)

1. All write cycle timing is referenced from the last valid address to the first transition address.
2. A write occurs during the overlap of a low CS, \overline{WE} , \overline{LB} and \overline{UB} . A write begins at the latest transition \overline{CS} going low and \overline{WE} going low ; A write ends at the earliest transition CS going high or \overline{WE} going high. t_{WP} is measured from the beginning of write to the end of write.
3. t_{CW} is measured from the later of \overline{CS} going low to end of write.
4. t_{AS} is measured from the address valid to the beginning of write.
5. t_{WR} is measured from the end of write to the address change. t_{WR} applied in case a write ends as \overline{CS} or \overline{WE} going high.
6. If \overline{OE} , CS and \overline{WE} are in the Read Mode during this period, the I/O pins are in the output low-Z state. Inputs of opposite phase of the output must not be applied because bus contention can occur.
7. For common I/O applications, minimization or elimination of bus contention conditions is necessary during read and write cycle.
8. If CS goes low simultaneously with \overline{WE} going or after \overline{WE} going low, the outputs remain high impedance state.
9. Dout is the read data of the new address.
10. When CS is low : I/O pins are in the output state. The input signals in the opposite phase leading to the output should not be applied.

FUNCTIONAL DESCRIPTION


| \overline{CS} | \overline{WE} | \overline{OE} | \overline{LB} | \overline{UB} | Mode | I/O Pin | | Supply Current |
|-----------------|-----------------|-----------------|-----------------|-----------------|----------------|------------------------------------|-------------------------------------|----------------|
| | | | | | | I/O ₁ ~I/O ₈ | I/O ₉ ~I/O ₁₆ | |
| H | X | X* | X | X | Not Select | High-Z | High-Z | Isb, Isb1 |
| L | H | H | X | X | Output Disable | High-Z | High-Z | Icc |
| L | X | X | H | H | | High-Z | High-Z | |
| L | H | L | L | H | Read | DOUT | High-Z | Icc |
| | | | H | L | | High-Z | DOUT | |
| | | | L | L | | DOUT | DOUT | |
| L | L | X | L | H | Write | DIN | High-Z | Icc |
| | | | H | L | | High-Z | DIN | |
| | | | L | L | | DIN | DIN | |

* X means Don't Care.

PACKAGE DIMENSIONS

Units: millimeters/Inches

44-SOJ-400



44-TSOP2-400BF

Units: millimeters/Inches

