

Features

- Dual Output
- SIP or DIP Package
- Industry Standard Pinout
- 1000 VDC Isolation
- -40°C to +85°C Operation
- MTBF >1.1 Mhrs

Specification

Input

Input Voltage Range	: Nominal $\pm 10\%$
Input Reflected Ripple Current	: 20mA pk-pk (through 12 μ H inductor 5Hz to 20MHz)
Input Reverse Voltage Protection	: None

Output

Output Voltage	: See table
Minimum Load	: None ⁽²⁾
Line Regulation	: 1.2% / 1% ΔV_{in}
Load Regulation	: 10% 20-100% load change
Setpoint Accuracy	: $\pm 3\%$
Ripple & Noise	: 75mV pk-pk max, 20MHz bandwidth
Temperature Coefficient	: 0.02% / °C
Maximum Capacitive Load	: $\pm 100\mu$ F

General


Efficiency	: See table
Isolation Voltage	: 1000V DC min
Isolation Resistance	: 10 ⁹ Ω
Isolation Capacitance	: 60pF typical
Switching Frequency	: Variable, 80KHz typical
MTBF	: >1.12Mhrs to MIL-HDBK-217F at 25°C, GB

Environmental

Operating Temperature	: -40°C to +85°C
Storage Temperature	: -40°C to +125°C
Case Temperature	: 100°C max
Cooling	: Convection-cooled

Input Voltage	Output Voltage	Output Current	Efficiency	Model Number	Description
5V DC	±5.0V	±100mA	74%	MCA05D05D	DC/DC Converter, 1W, Dual O/P
	±5.0V	±100mA	74%	MCA05D05S	
	±12.0V	±42mA	78%	MCA05D12D	
	±12.0V	±42mA	78%	MCA05D12S	
	±15.0V	±33mA	80%	MCA05D15D	
	±15.0V	±33mA	80%	MCA05D15S	
12V DC	±5.0V	±100mA	75%	MCA12D05D	
	±5.0V	±100mA	75%	MCA12D05S	
	±12.0V	±42mA	78%	MCA12D12D	
	±12.0V	±42mA	78%	MCA12D12S	
	±15.0V	±33mA	80%	MCA12D15D	
	±15.0V	±33mA	80%	MCA12D15S	
24V DC	±5.0V	±100mA	74%	MCA24D05D	
	±5.0V	±100mA	74%	MCA24D05S	
	±12.0V	±42mA	78%	MCA24D12D	
	±12.0V	±42mA	78%	MCA24D12S	
	±15.0V	±33mA	78%	MCA24D15D	
	±15.0V	±33mA	78%	MCA24D15S	

Mechanical Details



Notes

1. Operation at no load will not damage unit but it may not meet all specifications
2. All dimensions in inches (mm)
3. Pin pitch tolerance: ± 0.014 (± 0.35)
4. Case tolerance ± 0.02 (± 0.5)
5. Weight: SIP 0.006 lbs (2.6 g), DIP 0.005 lbs (2.3 g)

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.