DC-Link Film Capacitors - Radial Leaded MPDPB Series

multicomp PRO



Features

- Metallized polypropylene film construction
- Excellent electric property
- Plastic case (UL94 V-0), filled with resin
- High performance DC filtering applications (i.e. Frequency converters, Industrial and high-end power supplies and Solar inverters).

Specifications

Reference Standard	: GB/T17702 (IEC 61071)
Climatic Category	: 40/105/56
Rated Temperature	: +85°C
Operating Temperature Range	: -40°C to +105°C (+85°C to + 105°C : decreasing factor 1.5% per °C for U _N ,85°C)
Rated Voltage UN	: 600V DC, 700V DC, 800V DC, 1100V DC
Capacitance Range	: 8µF to 80µF
Capacitance Tolerance	: ±10% (K)
Voltage Proof	: 1.5UN (10s)
Insulation Resistance	: ≥10000s (20°C, 100V DC, 1min)
Self-Inductance Ls	: <1nH per mm of lead spacing
Max. Peak Current I (A)	: I=C.dV/dt
Expected Lifetime	: 100,000Hrs @ Un, өк =70°С

Specification Table

Part Number	lrms 10kHz	Peak Current	ESR 10kHz	ESL	Thermal Res	dv/dt
	A @ 70°C	Α	mΩ	nH	°C/W	V/us
MPDPB1K1A25K4Y050	13	625	8.2	35	8	25
MPDPB700A75K4Y050	20	1125	3.8	35	6.3	15
MPDPB1K1A30K4Y050	15	750	5	35	8.9	25
MPDPB1K1W80K4Q050	10.5	320	14	30	6.5	40
MPDPB800A20K0Q200	12	600	7	30	11.6	30
MPDPB800A50K4Y050	16	600	5	35	7.8	12
MPDPB600A80K4Y050	20	1200	4	35	6.3	15
MPDPB1K1A15K4Q050	16	600	7	30	5.4	40


Newark.com/exclusive-brands Farnell.com/exclusive-brands Element14.com/exclusive-brands



DC-Link Film Capacitors - Radial Leaded MPDPB Series

multicomp PRO

Dimensions



Part Number	W	Н	Т	Р	P1	d (Lead Dia.)
MPDPB1K1A25K4Y050	58	50	35	52.5	20.3	1.2
MPDPB700A75K4Y050	58	50	35	52.5	20.3	1.2
MPDPB1K1A30K4Y050	57.5	45	30	52.5	20.3	1.2
MPDPB1K1W80K4Q050	42.5	28	19	37.5	10.2	1.2
MPDPB800A20K0Q200	42.5	37	28	37.5	10.2	1.2
MPDPB800A50K4Y050	58	50	35	52.5	20.3	1.2
MPDPB600A80K4Y050	58	50	35	52.5	20.3	1.2
MPDPB1K1A15K4Q050	42.5	45	30	37.5	20.3	1.2

Dimensions : Millimetres

Part Number Table

Description	Part Number		
DC-Link Film Capacitor, 25µF, 1.1kV, ±10%, Radial Leaded	MPDPB1K1A25K4Y050		
DC-Link Film Capacitor, 75µF, 700V, ±10%, Radial Leaded	MPDPB700A75K4Y050		
DC-Link Film Capacitor, 30µF, 1.1kV, ±10%, Radial Leaded	MPDPB1K1A30K4Y050		
DC-Link Film Capacitor, 8µF, 1.1kV, ±10%, Radial Leaded	MPDPB1K1W80K4Q050		
DC-Link Film Capacitor, 20µF, 800V, ±10%, Radial Leaded	MPDPB800A20K0Q200		
DC-Link Film Capacitor, 50µF, 800V, ±10%, Radial Leaded	MPDPB800A50K4Y050		
DC-Link Film Capacitor, 80µF, 600V, ±10%, Radial Leaded	MPDPB600A80K4Y050		
DC-Link Film Capacitor, 15µF, 1.1kV, ±10%, Radial Leaded	MPDPB1K1A15K4Q050		

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/exclusive-brands Farnell.com/exclusive-brands Element14.com/exclusive-brands

