Power Film Capacitors -Screw/Stud Terminals multicomp

RoHS Compliant



Features


- Conduction cooled
- Polypropylene dielectric
- Self-healing
- Operating frequency up to 700kHz
- Maximum operating core temperature 85°C
- Capacitance tolerance ±10%
- Flame retardant UL94- V0

Standard Capacitor Values

Part Number	Rated Voltage Vrms	Nominal Capacitance µF at 1kHz	Max Current Irms	Max Power Kvar	Frequency kHz	ESR mΩ	Dimensions mm			Case Code	Terminal Style
							В	н	L		
MP004112	500	2.6	650		72-85	0.2	30.2	50	75	F1	4M
MP004109	600	1.32	650		100-170	0.3					
MP004110	700	0.33	500		295-401	1					
MP004111		0.66	500		147-200	0.8					
MP004108	1000	0.2	400	300	238-423	1.2					

Capacitor Drawing and Terminal Style

Terminal Style : 4M



Dimensions : Millimetres


Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro



Power Film Capacitors -Screw/Stud Terminals multicomp

Frequency Derating

→ Voltage - Current - Power




Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro

multicomp PRO

Power Film Capacitors -Screw/Stud Terminals multicomp

Frequency Derating

→ Voltage → Current → Power



Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet on the formation or use of it (including liability for loss or damage resulting from any reliance on the Information or use of it (including liability of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro

