


- Features:
- Robust metal oxide film element
 - Flameproof design
 - Compact Size
 - Useful in circuits where duty cycles require power resistors
 - Tin-plated copper leads
 - Cut and formed product is available on select sizes; contact factory for details
 - RoHS compliant / lead-free



Electrical Specifications						
Type / Code	Power Rating (Watts) @ 70°C	Maximum Working Voltage (1)	Maximum Overload Voltage	Resistance Temperature Coefficient	Ohmic Range (Ω) and Tolerance	
					1%, 2%	5%
RSPF14	0.25W	250V	500V	-200 ppm/°C ~ +350 ppm/°C	10 - 100K	2.2 - 1M
RSPF12	0.5W	400V	800V			
RSPF1	1W	500V	1,000V			
RSPF2	2W	500V	1,000V			
RSPF3	3W	500V	1,000V			
RSPL14	0.25W	√PR	√PR x 2.5	-200 ppm/°C ~ +350 ppm/°C	-	0.1 - 2
RSPL12	0.5W	√PR	√PR x 2.5			
RSPL1	1W	√PR	√PR x 2.5			
RSPL2	2W	√PR	√PR x 2.5			
RSPL3	3W	√PR	√PR x 2.5			

(1) Lesser of √PR or maximum working voltage




Mechanical Specifications					
Type / Code	A Body Length	B Body Diameter	C Lead Length (Bulk)	D Lead Diameter	Unit
RSPF14 / RSPL14	0.13 + 0.008 / 0	0.07 ± 0.01	1.10 ± 0.12	0.02 ± 0.002	inches
	3.20 + 0.20 / 0	1.82 ± 0.20	28.00 ± 3.00	0.45 ± 0.05	mm
RSPF12 / RSPL12	0.24 ± 0.020	0.09 ± 0.01	1.10 ± 0.12	0.02 ± 0.002	inches
	6.00 ± 0.50	2.30 ± 0.20	28.00 ± 3.00	0.55 ± 0.05	mm
RSPF1 / RSPL1	0.35 ± 0.039	0.12 ± 0.02	1.10 ± 0.12	0.03 ± 0.002	inches
	9.00 ± 1.00	3.00 ± 0.50	28.00 ± 3.00	0.70 ± 0.05	mm
RSPF2 / RSPL2	0.43 ± 0.039	0.16 ± 0.02	1.10 ± 0.12	0.03 ± 0.002	inches
	11.00 ± 1.00	4.00 ± 0.50	28.00 ± 3.00	0.80 ± 0.05	mm
RSPF3 / RSPL3	0.59 ± 0.039	0.22 ± 0.04	1.38 ± 0.12	0.03 ± 0.002	inches
	15.00 ± 1.00	5.50 ± 1.00	35.00 ± 3.00	0.80 ± 0.05	mm

Performance Characteristics	
Test	Test Results
Short Time Overload	$\pm(0.75\% + 0.05\Omega)$
Moisture Resistance	$\pm(5\% + 0.05\Omega)$
Load Life @ 70°C - 1,000 hours	$\pm(5\% + 0.05\Omega)$
Dielectric Withstanding Voltage	$\pm(5\% + 0.05\Omega)$
Resistance to Solvent	Permanent marking no physical damage or deterioration

Operating Temperature Range: -55°C to +155°C

How to Order



Product Series		Size	Power Rating	Tolerance			Packaging				Resistance Value
RSPF	Flameproof	14	0.25W	Code	Tol	Value	Code	Description	Size	Quantity	Four characters with the multiplier used as the decimal holder. 2.2 ohm = 2R20 10 Kohm = 10K0 1 Mohm = 1M00
RSPL	Low values	12	0.5W	F	1%	E96, E24	T	Tape and Reel	RSPF14, RSPL14 RSPF12, RSPL12	5,000	
		1	1W	G	2%	E24			RSPF1, RSPL1 RSPF2, RSPL2	2,500	
		2	2W	J	5%				RSPF3, RSPL3	1,000	
		3	3W				B	Bulk	RSPF14, RSPL14 RSPF12, RSPL12	1,000	
									RSPF1, RSPL1 RSPF2, RSPL2 RSPF3, RSPL3		
							A		Ammo		RSPF14, RSPL14 RSPF12, RSPL12
								RSPF1, RSPL1		2,000	
								RSPF2, RSPL2 RSPF3, RSPL3		1,000	