Features:

- General purpose resistor ideal for commercial/industrial applications
- Flame retardant coatings standard
- Flameproof version available as CFF and CFFM
- Panasert available on selected sizes - contact Stackpole
- Auto sequencing/insertion compatible
- CFM (mini) ideal choice when size constraints apply
- Cut and formed product is available on select sizes - contact Stackpole
- Standard lead wire for CF and CFM is copper plated steel, with 100% tin over plate
- 100% tin plate on copper wire is available as type CFQ and CFQM
- RoHS compliant, REACH compliant, lead free and halogen free



Electrical Specifications – CF, CFQ, PCF

Type/Code	Size	Power Rating (W) @ 70ºC	Maximum Working Voltage (V) (1)	Maximum Overload Voltage (V)	Dielectric Withstanding Voltage (V)	TCR (ppm/ºC) per Ohmic Range	Ohmic Range (Ω) and Tolerance	
							2%	5%
CF, CFQ	18	0.125	250	500	350	< 10Ω = ± 400 ppm/ºC 10Ω to 9.99KΩ = 0 ~ -400 ppm/ºC 10KΩ to 99KΩ = 0 ~ -500 ppm/ºC 100KΩ to 999KΩ = 0 ~ -850 ppm/ºC 1MΩ and above = 0 ~ -1500 ppm/ºC	10 - 1M	1 - 22M
CF, CFQ, PCF	14	0.25	350	600	350		1 - 1M	1 - 22M
CF, CFQ	12	0.5	350	700	600		10 - 1M	1 - 22M
CF, CFQ	1	1	500	1000	600		1 - 1M	1 - 10M
CF, CFQ	2	2	500	1000	600		1 - 1M	1 - 10M

(1) Lesser of √(P*R) or maximum working voltage.

Electrical Specifications – CFM, CFQM, PCFM

Type/Code	Size	Power Rating (W) @ 70ºC	Maximum Working Voltage (V) (1)	Maximum Overload Voltage (V)	Dielectric Withstanding Voltage (V)	TCR (ppm/ºC) per Ohmic Range	Ohmic Range (Ω) and Tolerance	
							2%	5%
CFM, CFQM	14	0.25	250	500	350	< 10Ω = ± 400 ppm/ºC 10Ω to 9.99KΩ = 0 ~ -400 ppm/ºC 10KΩ to 99KΩ = 0 ~ -500 ppm/ºC 100KΩ to 999KΩ = 0 ~ -850 ppm/ºC 1MΩ and above = 0 ~ -1500 ppm/ºC	1 - 1M	1 - 10M
CFM, CFQM, PCFM	12	0.5	350	600	350		1 - 1M	1 - 10M
CFM, CFQM	1	1	600	1000	600		1 - 1M	1 - 10M

(1) Lesser of √(P*R) or maximum working voltage.


Electrical Specifications – CFF/CFFM

Type/Code	Size	Power Rating (W) @ 70ºC	Maximum Working Voltage (V) (1)	Maximum Overload Voltage (V)	Dielectric Withstanding Voltage (V)	TCR (ppm/ºC) per Ohmic Range	Ohmic Range (Ω) and Tolerance
							2%, 5%
CFF	18	0.166	200	400	300	< 10 Ω = ±400 ppm/ºC 10 Ω to 9.99K Ω = 0 ~ -400 ppm/ºC 10 K Ω to 99K Ω = 0 ~ -500 ppm/ºC 100 K Ω to 999K Ω = 0 ~ -850 ppm/ºC 1M Ω and above = 0 ~ -1500 ppm/ºC	1 - 2.2M
	14	0.25	300	600	500		1 - 5.1M
	12	0.5	350	700	500		
CFFM	14	0.25	250	500	300		1 - 2.2M
	12	0.5	300	600	500		

(1) Lesser of √(P*R) or maximum working voltage.

This specification may be changed at any time without prior notice.
Please confirm technical specifications before use.

Mechanical Specifications



Type/Code	Size	A Body Length	B Body Diameter	C Lead Length (Bulk)	D - Lead Diameter	Unit
CF	18	0.130 ± 0.012 3.30 ± 0.30	0.067 ± 0.012 1.70 ± 0.30	1.102 ± 0.118 28.00 ± 3.00	0.016 ± 0.003 0.40 ± 0.08	inches mm
CFQ					0.018 ± 0.003 0.45 ± 0.08	inches mm
CFF	18	0.126 ± 0.008 3.20 ± 0.20	0.073 ± 0.008 1.85 ± 0.20		0.018 ± 0.002 0.45 ± 0.05	inches mm
CF, CFF, CFQ, PCF	14	0.236 ± 0.012 6.00 ± 0.30	0.091 ± 0.012 2.30 ± 0.30		0.022 ± 0.003 0.55 ± 0.08	inches mm
CFFM		0.126 ± 0.008 3.20 ± 0.20	0.073 ± 0.008 1.85 ± 0.20		0.018 ± 0.002 0.45 ± 0.05	inches mm
CFM		0.130 ± 0.012 3.30 ± 0.30	0.067 ± 0.012 1.70 ± 0.30		0.016 ± 0.003 0.40 ± 0.08	inches mm
CFQM					0.018 ± 0.003 0.45 ± 0.08	inches mm
CF	12	0.335 ± 0.039 8.50 ± 1.00	0.106 ± 0.020 2.70 ± 0.50		0.022 ± 0.003 0.55 ± 0.08	inches mm
CFF, CFQ					0.028 ± 0.004 0.70 ± 0.10	inches mm
CFM, CFQM, CFFM		0.236 ± 0.012 6.00 ± 0.30	0.091 ± 0.012 2.30 ± 0.30		0.022 ± 0.003 0.55 ± 0.08	inches mm
CF, CFQ	1	0.433 ± 0.039 11.00 ± 1.00	0.177 ± 0.020 4.50 ± 0.50	1.181 ± 0.118 30.00 ± 3.00	0.031 ± 0.004 0.80 ± 0.10	inches mm
CFM, CFQM		0.354 ± 0.020 9.00 ± 0.50	0.138 ± 0.020 3.50 ± 0.50	1.102 ± 0.118 28.00 ± 3.00	0.028 ± 0.002 0.70 ± 0.05	inches mm
CF, CFQ	2	0.591 ± 0.039 15.00 ± 1.00	0.197 ± 0.020 5.00 ± 0.50	1.339 ± 0.157 34.00 ± 4.00	0.031 ± 0.004 0.80 ± 0.10	inches mm


Performance Characteristics

Test	Test Method	Typical Result			Test Limit		
Current Noise	MIL-STD 202, Method 308	1Ω ~ 91KΩ 0.15µ V/V	100KΩ ~ 910KΩ 0.32µ V/V	1MΩ ~ 22MΩ 0.54µ V/V	1Ω ~ 91KΩ 0.2µ V/V	100KΩ ~ 910KΩ 0.4µ V/V	1MΩ ~ 22MΩ 0.6µ V/V
Short Time Overload	JIS C5201-1, IEC60115-1, 4.13	< ±0.25%			≤ ±(0.75% + 0.05Ω)		
Resistance to Soldering Heat	JIS C5201-1, IEC60115-1, 4.18	< ±0.3%			≤ ±(0.5% + 0.05Ω)		
Rapid Change of Temperature	JIS C5201-1, IEC60115-1, 4.19	< ±0.3%			≤ ±(1% + 0.05Ω)		
Endurance at 70°C	JIS C5201-1, IEC60115-1, 4.25.1	< ±1%			R < 100KΩ: ≤ ±(2% + 0.05Ω) R ≥ 100KΩ: ≤ ±(3% + 0.05Ω)		
Terminal Strength	MIL-STD 202, Method 211	< ±0.2%			≤ ±(0.5% + 0.05Ω)		
Damp Heat (Steady state)	JIS C5201-1, IEC60115-1, 4.24	< ±1.5%			R < 100KΩ: ≤ ±(3% + 0.05Ω) R ≥ 100KΩ: ≤ ±(5% + 0.05Ω)		

Operating temperature range is -55 to +155°C

This specification may be changed at any time without prior notice.
Please confirm technical specifications before use.


Power Derating Curve:



Recommended Soldering Condition


Flow Soldering:
- Pre-heating: 110°C MAX
- Peak temperature/duration: 260°C within 10 seconds (1st, 2nd wave total)
- Temperature profile (see chart on the right)

Iron Soldering:
- 380°C, 5 seconds, once/terminal



This specification may be changed at any time without prior notice.
Please confirm technical specifications before use.


Single Pulse Power:



Repetitive Pulse Information

If repetitive pulses are applied to resistors, pulse wave form must be less than “Pulse limiting voltage”, “Pulse limiting current” or “Pulse limiting wattage” calculated by the formula below.

$$Vp = K\sqrt{P \times R \times T/t}$$
$$Ip = K\sqrt{P/R \times T/t}$$
$$Pp = K^2 \times P \times T/t$$




Where: Vp: Pulse limiting voltage (V)
Ip: Pulse limiting current (A)
Pp: Pulse limiting wattage (W)
P: Power rating (W)
R: Nominal resistance (ohm)
T: Repetitive period (sec.)
t: Pulse duration (sec.)
K: Coefficient: 0.8
[Vr: Rated Voltage (V), Ir: Rated Current (A)]

Note 1: If T > 10 → T = 10 (sec.), T / t > 1000 → T / t = 1000.
Note 2: If T > 10 and T / t > 1000, “Pulse Limiting power (single pulse) is applied.
Note 3: If Vp < Vr (Ip < Ir or Pp < P), Vr (Ir, P) is Vp (Ip, Pp).
Note 4: Pulse limiting voltage (Current, Wattage) is applied at less than rated ambient temperature. If ambient temperature is more than the rated temperature (70°C), please decrease power rating according to “Power Derating Curve”.
Note 5: Please assure sufficient margin for use period and conditions for “Pulse limiting voltage”.
Note 6: If the pulse waveform is not square wave, please judge after transform the waveform into square wave according to the “Waveform Transformation to Square Wave”.


This specification may be changed at any time without prior notice.
Please confirm technical specifications before use.

Waveform Transformation to Square Wave


1. Discharge curve wave with time constant “t” → Square wave




2. Damping oscillation wave with time constant of envelope “t” → Square wave




3. Half-wave rectification wave → Square wave



4. Triangular wave → Square wave




5. Special wave → Square wave




This specification may be changed at any time without prior notice.
Please confirm technical specifications before use.

Current Noise:



Reel Specifications




Type/Code	Size	Class	Tape	A Max (1).	B Max	C	D	Unit
CF, CFQ	18	I	0.250 6.35	2.508 63.70	13.504 343.00	0.197 ± 0.020 5.00 ± 0.50	2.063 ± 0.079 52.40 ± 2.00	inches mm
CFF	18			2.508 63.70				inches mm
CF, CFQ, CFF	14			2.638 67.00				inches mm
	12			2.736 69.50				inches mm
CF, CFQ	1			2.972 75.50				inches mm
	2			3.130 79.50		0.394 ± 0.020 10.00 ± 0.50		inches mm
CFM, CFQM, CFFM	14			2.508 63.70		0.197 ± 0.020 5.00 ± 0.50		inches mm
	12			2.638 67.00				inches mm
CFM, CFQM	1			2.736 69.50				inches mm

Dimension "E": This is a non-critical dimension that does not have a tolerance in the standard.
Range of diameters is from 0.547" (13.9 mm) to 1.5" (38.1 mm).

(1) Reference value only. The "A" dimension shall be governed by the overall length of the taped component.
The distance between flanges shall be 0.059' (1.5 mm) to 0.315" (8 mm) greater than the overall component.

This specification may be changed at any time without prior notice.
Please confirm technical specifications before use.

Radial Lead Taping Specifications (Pana-Sert PCF14)




Symbol	Description	PANA-SERT	Unit
A	Resistor body length	0.256 ± 0.020 6.50 ± 0.50	inches mm
C	Height of bending	0.098 ± 0.020 2.50 ± 0.50	inches mm
D	Resistor body diameter	0.091 ± 0.008 2.30 ± 0.20	inches mm
D_0	Sprocket-hole diameter	0.157 ± 0.012 4.00 ± 0.30	inches mm
F	Resistor lead spacing	0.197 ± 0.039 5.00 ± 1.00	inches mm
H	Height to bottom of resistor	0.748 ± 0.039 19.00 ± 1.00	inches mm
H_0	Height to lead clinch	0.630 ± 0.020 16.00 ± 0.50	inches mm
H_1	Height of resistor	1.122 max. 28.50 max.	inches mm
h	Resistor alignment	0 ± 0.079 (0 ± 5º) 0 ± 2.00 (0 ± 5º)	inches mm
h_1	Resistor alignment	0 ± 0.079 (0 ± 5º) 0 ± 2.00 (0 ± 5º)	inches mm
I	Lead protrusion	0.079 max. 2.00 max.	inches mm

Symbol	Description	PANA-SERT	Unit
L	Cutout Length	0.433 max. 11.00 max.	inches mm
P	Resistor pitch	0.500 ± 0.039 12.70 ± 1.00	inches mm
P_0	Sprocket-hole pitch	0.500 ± 0.012 12.70 ± 0.30	inches mm
P_1	Sprocket-hole center to lead center	0.152 ± 0.028 3.85 ± 0.70	inches mm
P_2	Sprocket-hole center to resistor center	0.250 ± 0.051 6.35 ± 1.30	inches mm
T	Thickness (chipboard and tape)	0.028 ± 0.008 0.70 ± 0.20	inches mm
W	Chipboard width	0.709 +0.039 / -0.020 18.00 +1.00 / -0.50	inches mm
W_0	Hold-down tape width	0.49 min. 12.50 min.	inches mm
W_1	Sprocket-hole position	0.354 +0.030 / -0.020 9.00 +0.75 / -0.50	inches mm
W_2	Hold-down tape position	0.118 max. 3.00 max.	inches mm

This specification may be changed at any time without prior notice.
Please confirm technical specifications before use.


Ammo Packaging Specifications




Type/Code	Size	A	B	C	Unit
CF, CFQ	16	2.953 ± 0.079 75.00 ± 2.00	2.756 ± 0.118 70.00 ± 3.00	10.039 ± 0.197 255.00 ± 5.00	inches mm
CF, CFQ	14		3.937 ± 0.118 100.00 ± 3.00		inches mm
CF, CFQ	12		2.756 ± 0.118 70.00 ± 3.00		inches mm
CFQ	2		3.543 ± 0.118 90.00 ± 3.00		inches mm
CFM, CFQM	14		2.756 ± 0.118 70.00 ± 3.00		inches mm
CFM, CFQM	12		3.937 ± 0.118 100.00 ± 3.00		inches mm
CFQ, CFQM	1		2.953 ± 0.118 75.00 ± 3.00		inches mm

Surface Temperature Rise


Measurement Point





This specification may be changed at any time without prior notice.
Please confirm technical specifications before use.

Standard Color Codes



PRECISION - Have three significant-figure bands, a multiplier band, and a tolerance band. Tolerances 1% or less.

GENERAL PURPOSE - Have two significant-figure bands, a multiplier band, and a tolerance band. Tolerances 2% or greater.

Color	Nominal	Multiplier	Tolerance (%)
Black	0	1	-
Brown	1	10	1
Red	2	100	2
Orange	3	1K	-
Yellow	4	10K	-
Green	5	100K	0.5
Blue	6	1000K	0.25
Violet	7	-	0.1
Gray	8	-	-
White	9	0.001	-
Silver	-	0.01	10
Gold	-	0.1	5

COLOR BAND DESCRIPTION

BAND	PRECISION	GENERAL PURPOSE
1st band	Nominal	Nominal
2nd band	Nominal	Nominal
3rd band	Nominal	Multiplier
4th band	Multiplier	Tolerance
5th band	Tolerance	-

RoHS Compliance

Stackpole Electronics has joined the worldwide effort to reduce the amount of lead in electronic components and to meet the various regulatory requirements now prevalent, such as the European Union's directive regarding "Restrictions on Hazardous Substances" (RoHS 3). As part of this ongoing program, we periodically update this document with the status regarding the availability of our compliant components. All our standard part numbers are compliant to EU Directive 2011/65/EU of the European Parliament as amended by Directive (EU) 2015/863/EU as regards the list of restricted substances.

RoHS Compliance Status

Standard Product Series	Description	Package / Termination Type	Standard Series RoHS Compliant	Lead-Free Termination Composition	Lead-Free Mfg. Effective Date (Std Product Series)	Lead-Free Effective Date Code (YY/WW)
CF	Carbon Film Leaded Resistor	Axial	YES	100% Matte Sn	Jan-04 (Taiwan, China)	04/01
CFM	Carbon Film Resistor (Mini)	Axial	YES	100% Matte Sn	Jan-04 (Taiwan, China)	04/01
CFF	Carbon Film Resistor (Flameproof)	Axial	YES	100% Matte Sn	Jan-04 (Taiwan, China)	04/01
CFFM	Carbon Film Resistor (Flameproof - mini)	Axial	YES	100% Matte Sn	Jan-04 (Taiwan, China)	04/01
PCF	Carbon Film Resistor (Panasert CF14)	Axial	YES	100% Matte Sn	Jan-04 (Taiwan, China)	04/01
PCFM	Carbon Film Resistor (Panasert CFM12)	Axial	YES	100% Matte Sn	Jan-04 (Taiwan, China)	04/01
CFQ	Carbon Film Resistor (Tin Plating on Copper Wire)	Axial	YES	100% Matte Sn	Jan-04 (Taiwan, China)	04/01
CFQM	Carbon Film Resistor (Tin Plating Mini on Copper Wire)	Axial	YES	100% Matte Sn	Jan-04 (Taiwan, China)	04/01
PCFQ	Carbon Film Resistor (Tin Plating on Copper Wire - Panasert)	Axial	YES	100% Matte Sn	Jan-04 (Taiwan, China)	04/01

This specification may be changed at any time without prior notice.
Please confirm technical specifications before use.

"Conflict Metals" Commitment

We at Stackpole Electronics, Inc. are joined with our industry in opposing the use of metals mined in the "conflict region" of the eastern Democratic Republic of the Congo (DRC) in our products. Recognizing that the supply chain for metals used in the electronics industry is very complex, we work closely with our own suppliers to verify to the extent possible that the materials and products we supply do not contain metals sourced from this conflict region. As such, we are in compliance with the requirements of Dodd-Frank Act regarding Conflict Minerals.

Compliance to "REACH"

We certify that all passive components supplied by Stackpole Electronics, Inc. are SVHC (Substances of Very High Concern) free and compliant with the requirements of EU Directive 1907/2006/EC, "The Registration, Evaluation, Authorization and Restriction of Chemicals", otherwise referred to as REACH. Contact us for complete list of REACH Substance Candidate List.

Environmental Policy

It is the policy of Stackpole Electronics, Inc. (SEI) to protect the environment in all localities in which we operate. We continually strive to improve our effect on the environment. We observe all applicable laws and regulations regarding the protection of our environment and all requests related to the environment to which we have agreed. We are committed to the prevention of all forms of pollution.

How to Order

C	F	1	2	J	T	1	0	0	K

Product Series	
Code	Description
CF	Standard
CFM	Mini
CFF	Flameproof
CFFM	Flameproof (mini)
PCF	Panasert CF14
PCFM	Panasert CFM12
CFQ	Tin plating on copper wire
CFQM	Tin plating (mini)
PCFQ	Tin plating on copper wire Panasert

Power Rating	
Code	W
18	0.125
CFF18	0.166
14	0.25
12	0.5
1	1
2	2

Tolerance	
Code	Tol
G	2%
J	5%

Packaging			
Code	Description	Product Code	Qty
T	Tape and Reel	CF18, CFQ18, CFF18 CF14, CFM14, CFF14, CFFM14 CFQ14, CFQM14, PCF14 CF12, CFM12, CFF12, CFFM12 CFQ12, CFQM12, PCFM12	5000
		CFM1, CFQM1	2500
		CF1, CFQ1	2000
		CF2, CFQ2	1000
A	Ammo	CF18, CFQ18, CFF18 CF14, CFF14, CFFM14, CFM14 CFQ14, CFQM14 CFM12, CFFM12, CFQM12	5000
		CF12, CFF12, CFQ12, PCFM12 CF1, CFM1, CFQ1, CFQM1 PCF14	2000
		CF2	1000
B(*)	Bulk	All Sizes	1000

Resistance Value
Four characters with the multiplier used as the decimal holder.
10 ohm = 10R0 10.2 Kohm = 10K2 1 Mohm = 1M00

(*) Bulk packaging may be subject to 25 K pieces MOQ

This specification may be changed at any time without prior notice.
Please confirm technical specifications before use.