



SG-8002CA  
SPXO/SPSO

## Product No. / Ordering code :Q3309CA400006

Brief sheet			Data sheet	ROHS	REACH
 English	 Japanese	 Chinese	—	 English	 English

### Specification

Frequency	40.000000 MHz
Output Wave	CMOS
Supply voltage	2.70 to 3.60 V
Size (LxWxH)	7.00 x 5.00 x 1.50 mm
Operating temperature	-20 to +70 °C
frequency tolerance	± 50 ppm
Extra Options	N/A
OSC Type	Programmable Clock OSC

Mounting Type	Surface Mount
Model name item name use	SG-8002CA
Current consumption	28.0 mA
Frequency aging 1	+/-5ppm
Frequency aging 2	N/A
Symmetry	40 to 60 %
Function	OE

#### PRODUCTS

- ▶ TCXO
- ▶ VCXO
- ▶ OCXO
- ▶ Crystal Oscillator
- ▶ Real Time Clock
- ▶ Crystal Unit
- ▶ Sensor
- ▶ Timing Module
- ▶ Epson Products for Car Electronics

#### APPLICATIONS

- ▶ Wired network
- ▶ Measurement instrument
- ▶ Factory automation
- ▶ Security
- ▶ Broadcasting & Audio
- ▶ Automotive

#### IC Partners

- ▶ Circuit design information
- ▶ IC Partners information

#### INFORMATION

- ▶ Support
- ▶ Technical Information
- ▶ Precaution
- ▶ Discontinue products
- ▶ Product Change Notification / Engineering Change Notification Announcement
- ▶ Higher Quality / Green Purchasing / Business continuity management
- ▶ Sales Office and Plants
- ▶ Articles

#### NEWS

- ▶ News Release
- ▶ What's new
- ▶ New products

#### CONTACT

- ▶ Contact
- ▶ Online distributor