

SPECIFICATION


• Supplier : Samsung Electro-Mechanics
• Product : Polymer Tantalum Capacitor

• Samsung P/N : TCPCS0J107MBAR0035
• Description : CAP,TANTAL,100 μ F,6.3V, $\pm$ 20%,3528-19

A. Samsung Part Number

TC **PCS** **0J** **107** **M** **B** **A** **R** **0035**
① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

① Tantalum Capacitor	TC							
② Series	PCS							
③ Rated Voltage	6.3V							
④ Capacitance	100 μ F							
⑤ Capacitance tolerance	$\pm$ 20%							
⑥ Case size code	3528-19							
⑦ Packing code	7" reel							
⑧ Taping code	Taping direction code							
⑨ ESR	35 m Ω							



B. Reliability Test and Judgment Condition

Item	Performance	Test condition
Capacitance	Within specified tolerance	120Hz, maximum 1.0Vrms, 1.0~2.0V D.C at 25℃
Tan δ (DF)	Within specified value	120Hz, maximum 1.0Vrms, 1.0~2.0V D.C at 25℃
Impedance(Z) & ESR	Within specified value	100kHz at 25℃
Leakage current	Within specified value	The rated DC voltage shall be applied to terminals across the test capacitor. Charge time : 5min.
Temperature Characteristics	"-55℃ : Δ C/C -20~0% "+105℃ : Δ C/C 0~+30%	From -55℃ to 105℃
Adhesion Strength	No peeling shall be occur on the terminal electrode	1005mm size : 2N, for 10 $\pm$ 1 sec. 1608~7343mm size : 5N, for 10 $\pm$ 1 sec.
Electrode Strength	Within specified tolerance Tan δ , LC : initial spec.	Bending to the limit (3mm) with 1.0mm/sec.
Solderability	More than 95% of terminal surface is to be soldered newly	Sn-3Ag-0.5Cu solder : 245 $\pm$ 2℃, 3 $\pm$ 0.3sec
Resistance to Soldering heat	Capacitance change : within $\pm$ 20% Tan : 1.3 times of Initial specification. LC : 3 times of Initial specification.	Solder pot : 260 $\pm$ 5℃, 10 $\pm$ 1sec.
Vibration	Capacitance change : within $\pm$ 5% Tan δ , LC : initial spec.	Amplitude : 1.5mm From 10Hz to 55Hz (return : 1min.) 2hours ' 3 direction (x, y, z)
Resistance to Moisture	Capacitance change : -20~+35% Tan : 1.5 times of Initial specification. LC : 3 times of Initial specification.	40 $\pm$ 2℃, 90~95%RH, 500 +8/-0hrs
Load life (High Temperature Resistance)	Capacitance change : -20~+30% Tan : 85℃ $\rightarrow$ 1.5times of Initial specification. 105℃ $\rightarrow$ 3 times of Initial specification. LC : 1.5 times of Initial specification.	Rated voltage at 85℃ Derated voltage(0.8Vr) at 105℃ 2000 +48/-0hrs
Temperature Cycling	Capacitance change : within $\pm$ 20% Tan : within initial specification. LC : 3 times of Initial specification.	1 cycle condition (-55℃ $\rightarrow$ 25℃ $\rightarrow$ 105℃ $\rightarrow$ 25℃) 5 cycles

C. Recommended Soldering method

Reflow (Reflow Peak Temperature : 260 +0/-5℃, 5sec max)

D. Ratings & Part Number Reference

Part Number	Capacitance	Leakage Current	DF	ESR	Allowable Ripple Current
TCPCS0J107MBAR0035	100 μ F	63 μ A	8%	35m Ω	1550mA

Ripple current (100kHz @25℃)