ASSOCIATION CONNECTING ELECTRONICS INDUSTRIES®	© Co	terial Compo pyright 2005. IPC, Bannoo nternational and Pan-Ameri	kburn, Illinois	. All rights reserv	tion with lowe	er level p	parts, the	declaration	on encor	mpasses	all lower	level mate	erials for	which th	eitem is an assembly e manufacturer has eclaration.
1752-2 1.1	IPC Web Site for Information on IPC-1752 Standard http://www.ipc.org/IPC-175x								Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materials and Mfg Informa						
Supplier Information															
Company Name * STMicroelectronics	Company Unique ID		Unique ID Au	uthority	Response Date *				Response Document ID						
Contact Name *		Title - Contact		Phone - Con	Email	Email - Contact *				Duplicate Contact -> Authorized Representative					
Authorized Representati		Title - Representative		Phone - Rep N/A	Email - Representative * N/A			*	Supplier	Commer	nts or URL	for Add	itional In	formation	
Requester Item Numbe	r	Mfr Item Number		Mfr Item Name	Effectiv	ve Date Version		Manufa	acturing Si	te	Weight *	UO	М	Unit Type	
		LMV393IST		IYE3*V393AA	AL.	2011-	12-19	Α	ZS1A		:	28	mg		Each
Alternate Recommend	ation	PACKAGE: MSOP/T	SSOP 8 B	ρ		Alternate Item C			omments	ents ECOPACK2/ROHS; BSA: CD00308005					
Manufacturing Proces	ss In	formation													
Terminal Plating / Grid Array Material Terminal				ase Alloy	J-STD-020 MSL F	Rating	Peak Process Body Tempe			rature Ma	x Time at	Peak Temp	perature	Number	of Reflow Cycles
Matte Tin (Sn) - annealed Cumments			CU Alloy	CU Alloy 1					260 C	;	30 sec		conds	3	
Disclaimer: While STMic	roele	ectronics has endea	vored to p	orovide inform	nation which is	accurat	e and up	to date,	this do	ocument	and its	contents	are prov	rided on	a strict 'as is' an

Save the fields in this form to a file	Export Data	Import fields from a file into this form	oort Data	Clear all of the fields on this form	Reset Form	Lock the fields on this form to prevent changes	Lock Supplier Fields
RoHS Material Co	mposition Declaratio	n				Declaration Type *	Simplified
		nit of 0.1% by mass (1000 PPM ers (PBDE) and quantity limit of					ated Biphenyls (PBB),
ate that Supplier completes the upplier may have relied on in upplier agrees that, at a mining ritten agreement with respect	nis form. Supplier acknowledges formation provided by others in commum, its suppliers have provided	is form concerning RoHS restrictive subst that Company will rely on this certification ompleting this form, and that Supplier may certifications regarding their contributions and conditions of that agreement, including provides in this form.	in determining the co y not have independent to the part, and those	ompliance of its products with ntly verified such information e certifications are at least as	European Union member state However, in situations where S comprehensive as the certificati	laws that implement the RoHS Direction in the company in the paragraph. If the Company	ve. Company acknowledges that Information provided by others, and the Supplier enter into a
RoHS Declaration *	1 - Item(s) does not contain Ro	HS restricted substances per the defini	ition above			Supplier Acceptance * Acceptance	pted
exemptions: If the declar bove and choose all app		RoHS restricted substances per	the definition abo	ove except for defined	RoHS exemptions, then se	elect the corresponding respon	se in the RoHS Declaration
Declaration Signa	ture						
nstructions: Comple	ete all of the required fie	lds on all pages of this form.	Select the "Acc	cepted" on the Suppli	er Acceptance drop-dov	wn. This will display the sig	nature area. Digitally sign

the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.

Supplier Digital Signature

Homogeneous Material Composition Declaration for Electronic Products

Subltem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Line Functions: +I Inserts a New Item /SubItem +M Inserts a new Material +C Inserts a new Substance Category +S Inserts a new Substance - Deletes the element line

	Item/SubItem Name			Homogeneous	Weight	Unit of			Level	Substance Category			Substance	CAS	Exempt	Waigh	Unit of	Tolerance		PPM
				Material	weight	Measure			Level				Substance	CAS		weight	Measure	-	+	FFIVI
+1 -1	IYE3*V393AAL	+1	л-м	Silicon Die	0.548	mg	+C	-C	Supplier	Silicon die	+S	-S	Silicon (Si)	7440-21-3		0.548	mg			1,000,0
	,	+1	и-м	Leadframe	11.608	mg	+C	-C	Supplier	Alloy	+S	-S	Copper	7440-50-8		11.207	mg			965,45
					•	_					+S	-s	Iron (2.1-2.6%)	7439-89-6		0.265	mg			22,829
											+S	-s	Zinc (0.05-0.2%)	7440-66-6		0.015	mg			1,292
											+S	-s	Phosphorus	12185-10-3		0.005	mg			431
											+S	-s	Silver	7440-22-4		0.116	mg			9,993
		+1	и-м	Die Attach	0.524	mg	+C	-C	supplier	Glue	+S	-s	Silver (80-100%)	7440-22-4		0.419	mg			799,61
					•						+S	-s	Carbocyclic Acrylates09	Proprietary		0.052	mg			99,237
											+S	-s	Bismaleimide resin	Proprietary		0.016	mg			30,534
											+S	-s	2-preponoic acid, 2-met	68586-19-6		0.016	mg			30,534
											+S	-s	Additive	proprietary		0.016	mg			30,534
											+S	-s	Dicumlyl peroxide	80-43-3		0.005	mg			9,542
		+1	и-м	Bonding wire	0.31	mg	+C	-C	supplier	Bonding wire	+S	-S	Gold (Au)	7440-57-5		0.31	mg			1,000,0
		+1	и-м	Encapsulation	14.325	mg	+C	-C	supplier	Molding compound	+S	-S	Epoxy resin-1	Proprietary		0.43	mg			30,017
					•						+S	-s	Epoxy resin-2	Proprietary		0.43	mg			30,017
											+S	-s	Phenol resin	Proprietary		0.657	mg			45,864
											+S	-s	Silica	60676-86-0		12.808	mg			894,10
		+1	и-м	Finishing	0.685	mg	+C	-C	supplier	Connection coating	+S	-S	Tin	7440-31-5		0.685	mg			1,000,0