

SMD Power Inductor

CDRH30D14R



Description

- Ferrite drum core construction.
- Magnetically shielded.
- L × W × H: 3.3 × 3.15 × 1.5 mm Max.
- Product weight: 30mg (Ref.)
- Moisture Sensitivity Level: 1
- RoHS compliance.

Environmental Data

- Operating temperature range: -40℃ ~ +105℃ (including coil's self temperature rise)
- Storage temperature range: -40℃ ~ +105℃
- Solder reflow temperature: 260 ℃ peak.


Packaging

- Carrier tape and reel packaging
- 13.0" diameter reel
- 4000pcs per reel


Applications

- Ideally used in Mobilephone, PDA, MP3, DSC/ DVC, HDD, etc as DC-DC converter inductors.

Dimension - [mm]



Land pattern and Schematics - [mm]



Electrical Characteristics

Part No.	Stamp	Inductance (μH) [Within] ※1	D.C.R. (mΩ) [Within] (at20℃)	The saturation Current (A) ※2		Temperature rise Current (A) ※3
				(at20℃)	(at100℃)	
CDRH30D14RNP-1R0NC	A	1.0 ± 30%	39 ± 25%	1.90	1.40	2.43
CDRH30D14RNP-1R4NC	B	1.4 ± 30%	50 ± 25%	1.60	1.20	2.10
CDRH30D14RNP-2R2NC	C	2.2 ± 30%	74 ± 25%	1.30	1.00	1.62
CDRH30D14RNP-3R3MC	D	3.3 ± 20%	111 ± 20%	1.05	0.80	1.28
CDRH30D14RNP-4R7MC	E	4.7 ± 20%	153 ± 20%	0.90	0.68	1.16
CDRH30D14RNP-6R4MC	F	6.4 ± 20%	223 ± 20%	0.75	0.56	0.95
CDRH30D14RNP-100MC	G	10 ± 20%	394 ± 20%	0.60	0.46	0.63

※1. Measuring condition: at 100kHz.

※2. Saturation current: The value of D.C. current when the inductance decreases to 70% of it's nominal value.

※3. Temperature rise current: The value of D.C. current when the temperature rise is Δt=40℃(Ta=20℃).








SMD Power Inductor

CDRH30D14R




Saturation Current & Temperature Rise Graph

— L (20°C) — (100°C) — ΔT




SMD Power Inductor CDRH30D14R




Solder Reflow Condition

Heat Endurance



Temperature Chart



Please refer to the sales offices on our website - <http://www.sumida.com>

Hong Kong

Tel.+852-2880-6781
FAX.+852-2565-9600
sales@hk.sumida.com

Saitama(Japan)

Tel.+81-48-691-7300
FAX.+81-48-691-7340
sales@jp.sumida.com

Chicago

Tel.+1-847-545-6700
FAX. +1-847-545-6720
sales@us.sumida.com

Shanghai

Tel.+86-21-5836-3299
FAX.+86-21-5836-3266
shanghai.sales@cn.sumida.com

Seoul

Tel.+82-2-6237-0777
FAX.+82-2-6237-0778
sales@kr.sumida.com

Obernzell

Tel.+49-8591-937-0
FAX. +49-8591-937-103
contact@eu.sumida.com

Shenzhen

Tel.+86-755-8291-0228
FAX.+86-755-8291-0338
shenzhen.sales@cn.sumida.com

Singapore

Tel.+65-6296-3388
FAX.+65-6841-4426
sales@sg.sumida.com

Neumarkt

Tel.+49-9181-4509-110
FAX. +49-9181-4509-310
infocomp@eu.sumida.com

Taipei

Tel.+886-2-8751-2737
FAX.+886-2-8751-2738
sales@tw.sumida.com

San Jose

Tel.+1-408-321-9660
FAX.+1-408-321-9308
sales@us.sumida.com