




Features

- Metal-Semiconductor junction with guardring
- Epitaxial construction
- Low forward voltage drop
- High current capability
- The plastic material carries UL recognition 94V-0
- For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications



DO-204AL (DO-41)

A-405



Dimensions in inches and (millimeters) Dimensions in inches and (millimeters)

Note: Lead diameter is 0.025(0.64)/0.021(0.53) for suffix "S" part numbers

Mechanical Data

- Case: JEDEC DO-204AL(DO-41)/A-405 molded plastic
- Polarity: Color band denotes cathode end
- Weight: DO-41-0.012 ounce, 0.33 gram
 A-405-0.008 ounce, 0.22 gram
- Mounting position: Any

MAXIMUM RATINGS and ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60HZ, resistive or inductive load.

For capacitive load, derate current by 20%

PARAMETER	SYMBOL	SB170	SB180	SB190	SB1B0	UNIT
Maximum repetitive peak reverse voltage	VRRM	70	80	90	100	V
Maximum RMS voltage	VRMS	49	56	63	70	V
Maximum DC blocking voltage	VDC	70	80	90	100	V
Maximum average forward rectified current 0.375"(9.5mm) lead length at T _L =100°C	IF(AV)	1.0				A
Peak forward surge current 8.3 ms single half sine-wave superimposed on rated load	IFSM	30				A
Maximum forward voltage at 1A DC T _A =25°C T _A =100°C	VF	0.79 0.69				V
Maximum DC reverse current at rated DC blocking voltage ⁽¹⁾	T _J =25°C	0.05				mA
	T _J =125°C	1				
Typical junction capacitance (Note 1)	C _J	30				pF
Typical thermal resistance(Note 2)	R _{θJA}	76				°C/W
	R _{θJC}	41				
	R _{θJL}	32				
Operating junction temperature range	T _J	- 55 to + 150				°C
storage temperature range	T _{STG}	- 55 to + 150				°C

Notes: 1. Measured at 1.0 MHZ and applied reverse voltage of 4.0V DC

2. Thermal Resistance at .375(9.5mm) Lead Length, PC Board Mounted

RATINGS AND CHARACTERISTICS CURVES

