



MATERIAL:

STAINLESS STEEL PER AMS-5640, ALLOY UNS S30300, TYPE 1; OR ASTM A582 TYPE 303, COND. A

FINISH:

PASSIVATED PER AMS-2700

- NOTES:
 - 1. FOR A FOOTPRINT RECOMMENDATION SPECIFIC TO YOUR PCB, PLEASE CONTACT US AT applications@svmicro.com

MATERIAL:	SEE NOTES	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL: +1/64 ANGULAR: X° +1°0'	UNLESS C
FINISH:	SEE NOTES	DECIMAL: .X ±.030 .XX ±.010	1) ALL DIMENSIONS 2) ALL DIMENSIONS 3) BREAK CORNERS 4) CHAM, 1ST & LAS
SURFACE AREA: N/A		.XXX ±.005	5) SURFACE ROUGH 6) DIA.'S ON COMMO WITHIN .004 T.I.R. 7) REMOVE ALL BUR
PROPRIETARY		PER ASME Y14.5M - 1994	.,
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SV MICROWAVE, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SV MICROWAVE, INC IS PROHIBITED.		THIRD ANGLE PROJECTION	DRAWN:
			CHECKED
			APPROVE

REVISION HISTORY					
REV	DESCRIPTION	DATE	APPROVED		
-	DCN 46856	9/17	FSG		

OTHERWISE SPECIFIED NS ARE IN INCHES [MILLIMETERS] NS ARE AFTER PLATING. RS & EDGES .005 R. MAX. AST THREADS.	2400	Amphenol AMPHENOL 2400 Centrepark West Drive, Suite 100 West Palm Beach, FL 33409		
IGHNESS 63-MIL-STD-10. MON CENTERS TO BE CONCENTRIC I.R. JURRS	3m	3mm SMOOTH BORE FLANGE		
GPF 9/26/17		_		
D: FSG 9/26/17	B SIZE CAGE CODE	^{DWG. NO.} 012-80-487/020		
'ED: FSG 9/26/17	SCALE: 8:1	SHEET 1 OF 1		