



*Pb Free part

Customer Name	Standard Specification	TAIYO YUDEN Mobile Technology Co.,Ltd.	
System	W-LAN	DATE	May 19, 2016
Part Number	F6HG2G441EG65	Version 2.0bA	Final

Table 1 Electrical Specification

Item		Condition	S	pecification	on	Unit	Remarks
I	tem	(MHz)	Min.	Тур.	Max.	Offic	Remarks
		2402.5 ~ 2421.5	-	1.4	2.0	dB	
		2407.5 ~ 2426.5	-	1.3	1.9	dB	
	on loss ed(*1)(*2)	2412.5 ~ 2471.5	-	1.3	1.8	dB	
intograti	3a(1)(2)	2457.5 ~ 2476.5	-	1.3	2.0	dB	
		2462.5 ~ 2481.5	-	1.5	2.4	dB	
		2402.5 ~ 2421.5	-	0.6	1.5	dB	
		2407.5 ~ 2426.5	-	0.5	1.4	dB	
Amplitude	Ripple(*2)	2412.5 ~ 2471.5	-	0.5	1.3	dB	
		2457.5 ~ 2476.5	-	0.5	1.5	dB	
		2462.5 ~ 2481.5	-	0.7	1.9	dB	
VSWR	Input	2402.5 ~ 2481.5	-	1.5	2.0	-	
VSVK	Output	2402.5 ~ 2481.5	-	1.5	2.0	-	
Input	Power	2402.5 ~ 2481.5	28dBm Ta=+50°C 10000h, CW				
		800 - 2300	35	39	-	dB	
		2300 - 2370	48	51	-	dB	(*3)
			23		-	dB	-30~-10°C (*3)
		2500 - 2505	30	61	-	dB	-10~+25°C (*3)
Absolute A	Attenuation		42		-	dB	+25~+85°C (*3)
		2505 - 2570	47	52	-	dB	(*3)
		2570 - 2620	42	48	-	dB	(*3)
		2620 - 2690	42	45	-	dB	(*3)
		2690 - 7500	30	39	-	dB	
Term	inating	Input port	50//	6.8nH(Q=	=∞)	Ω	
Impedance		Output port	50//	6.8nH(Q=	=∞)	Ω	
Operating temp				-30 to +85		°C	
	Maximum D	C in all ports	-	-	5	VDC	Device only
Device s (L typ.x W typ.)			1.	1 x 0.9 x 0).5	mm	

- (*1) Specification of Insertion loss excludes loss that comes from the test board.
- (*2) The integrated loss over any 19MHz channel within the band.
- (*3) The integrated loss over any 5MHz channel within the band.








*Pb Free part

Customer Name	Standard Specification	TAIYO YUDEN Mobile Technology Co., Ltd.	
System	W-LAN	DATE	May 19, 2016
Part Number	F6HG2G441EG65	Version 2.0bA	Final

Dimensions



Unit: mm

Pin Configuration

Pin No.	Symbol	Function
1	IN	Input
2	GND	Ground
3	GND	Ground
4	OUT	Output
5	GND	Ground

Figure 1. Dimensions and Pin assignment






RoHS	MSL1
------	------

Customer Name	Standard Specification	TAIYO YUDEN Mobile Technology Co.,Ltd.	
System	W-LAN	DATE	May 19, 2016
Part Number	F6HG2G441EG65	Version 2.0bA	Final

Evaluation Circuit



Recommended foot print pattern




Figure 2. Recommended foot print pattern







*Pb Free part

Customer Name	Standard Specification	TAIYO YUDEN Mobile Technology Co.,Ltd.	
System	W-LAN	DATE	May 19, 2016
Part Number	F6HG2G441EG65	Version 2.0bA	Final

Passband




Figure 3-1. Electrical Characteristics

These data excludes loss that comes from the test board.







*Pb Free part

Customer Name	Standard Specification	TAIYO YUDEN Mobile Technology Co., Ltd.	
System	W-LAN	DATE	May 19, 2016
Part Number	F6HG2G441EG65	Version 2.0bA	Final

Input Port




Figure 3-2. Electrical Characteristics







*Pb Free part

Customer Name	Standard Specification	TAIYO YUDEN Mobile Technology Co.,Ltd.	
System	W-LAN	DATE	May 19, 2016
Part Number	F6HG2G441EG65	Version 2.0bA	Final

Output Port




Figure 3-3. Electrical Characteristics







*Pb Free part

Customer Name	Standard Specification	TAIYO YUDEN Mobile Technology Co., Ltd.	
System	W-LAN	DATE	May 19, 2016
Part Number	F6HG2G441EG65	Version 2.0bA	Final

Wideband




Figure 3-4. Electrical Characteristics







*Pb Free part

Customer Name	Standard Specification	TAIYO YUDEN Mobile Technology Co.,Ltd.	
System	W-LAN	DATE	May 19, 2016
Part Number	F6HG2G441EG65	Version 2.0bA	Final

Ordering Code

Ordering Code	Packing	Reel size	Status
F6HG2G441EG65-J	Tape & Reel	5,000 pcs.	MP
F6HG2G441EG65-JA	Tape & Reel	less than 5000 pcs.	MP
F6HG2G441EG65-Y	Tape & Reel	15,000 pcs.	MP
F6HG2G441EG65-YA	Tape & Reel	less than 15,000 pcs.	MP
F6HG2G441EG65-Q	Bulk	few pcs.	MP

^{*}Minimum order quantity (MOQ) is assigned for each inquiry, Please contact to Sales Representatives.

Notice

All of the contents specified herein are subject to change without notice due to technical improvements, etc.

Please contact TAIYO YUDEN Co., Ltd. for further details of product specifications.

Please conduct validation and verification of products in actual condition of mounting and operating environment before commercial shipment of the equipment.

This product is for general electronics equipment such as Audio-Visual equipment, household electronics, office supplies, information services and telecommunications; therefore, in case this product is used for any medical equipment, space equipment, nuclear equipment or disaster prevention equipment, please contact TAIYO YUDEN in advance.

In case this product is used for general electronics equipment or circuits which require high safety and high reliability, thoroughly evaluate on safety and add a protection circuit if necessary.



^{*} MP : Mass Production