



SAW Components

SAW Tx Filter

WCDMA Band I

| | |
|-----------------------|--------------------------|
| Series/Type: | B9414 |
| Ordering code: | B39202B9414M410 |
| Date: | November 27, 2008 |
| Version: | 2.1 |

© EPCOS AG 2015. Reproduction, publication and dissemination of this publication, enclosures hereto and the information contained therein without EPCOS' prior express consent is prohibited.

EPCOS AG is a TDK Group Company.

SAW Components

B9414

SAW Filter

1950.0 MHz

Data Sheet




Application

- Low-loss RF filter for mobile telephone WCDMA systems, transmit path (TX)
- Impedance transform from 50 Ω to 50 Ω
- Unbalanced to unbalanced operation
- Very low insertion attenuation
- Low amplitude ripple
- Very low Error Vector Magnitude (EVM)
- High Rx-suppression
- Usable passband 60 MHz




Features

- Package size 1.4 x 1.1 x 0.4 mm³
- Package code QCS51
- RoHS compatible
- Approx. weight 0.003 g
- Package for **Surface Mount Technology (SMT)**
- Ni, gold-plated terminals
- **Electrostatic Sensitive Device (ESD)**



Pin configuration

- 1 Input, unbalanced
- 4 Output, unbalanced
- 2,3,5 To be grounded



SAW Components
B9414
SAW Filter
1950.0 MHz
Data Sheet

Characteristics

Operating temperature range: $T = -20\text{ }^{\circ}\text{C}$ to $+85\text{ }^{\circ}\text{C}$
 Terminating source impedance: $Z_S = 50\text{ }\Omega$ (unbalanced)
 Terminating load impedance: $Z_L = 50\text{ }\Omega$ (unbalanced)

| | | min. | typ. @ 25 °C | max. | |
|--------------------------------------|-----------------|------|-----------------|-------------------|-----|
| Center frequency | f_C | — | 1950.0 | — | MHz |
| Maximum insertion attenuation | α_{\max} | | | | |
| 1920.0 ... 1980.0 MHz | | — | 2.5 | 3.2 ¹⁾ | dB |
| Amplitude ripple (p-p) | $\Delta\alpha$ | | | | |
| 1920.0 ... 1980.0 MHz | | — | 1.1 | 1.8 ²⁾ | dB |
| Input VSWR | | | | | |
| 1920.0 ... 1980.0 MHz | | — | 1.8 | 2.2 | |
| Output VSWR | | | | | |
| 1920.0 ... 1980.0 MHz | | — | 1.8 | 2.2 | |
| Attenuation | α | | | | |
| 0.0 ... 960.0 MHz | | 27 | 34 | — | dB |
| 960.0 ... 1575.0 MHz | | 25 | 35 | — | dB |
| 1575.0 ... 1576.0 MHz | | 32 | 35 | — | dB |
| 1576.0 ... 1730.0 MHz | | 30 | 35 | — | dB |
| 1730.0 ... 1880.0 MHz | | 30 | 38 | — | dB |
| 2025.0 ... 2050.0 MHz | | 35 | 54 | — | dB |
| 2110.0 ... 2170.0 MHz | | 35 | 38 | — | dB |
| 2200.0 ... 3100.0 MHz | | 33 | 37 | — | dB |
| 3100.0 ... 3960.0 MHz | | 30 | 42 | — | dB |
| 3960.0 ... 6000.0 MHz | | 20 | 34 | — | dB |

¹⁾ ILmax max. 3.0dB at 25°C



²⁾ AR max. 1.6dB at 25°C
 EVM 1.3% at 25°C, 2.2% over temperature



SAW Components
B9414
SAW Filter
1950.0 MHz
Data Sheet

Maximum ratings

| | | | | |
|----------------------------|------------------|------------------|-----|--------------------------|
| Operable temperature range | T | −30/+85 | °C | |
| Storage temperature range | T _{stg} | −40/+85 | °C | |
| DC voltage | V _{DC} | 5 | V | |
| ESD voltage | V _{ESD} | 50 ¹⁾ | V | machine model, 10 pulses |
| Source Power | P _S | 10 | dBm | cw signal |

¹⁾ acc. to JESD22-A115A (machine model), 10 negative & 10 positive pulses.

Transfer function

Transfer function (wideband)




SAW Components
B9414
SAW Filter
1950.0 MHz

Data Sheet


References

| | |
|----------------------------|--|
| Type | B9414 |
| Ordering Code | B39202B9414M410 |
| Marking and Package | C61157-A8-A3 |
| Packaging | F61074-V8237-Z000 |
| Date Codes | L_1126 |
| Soldering profile | S_6001 |
| S-Parameters | B9414_NB.s2p, B9414_WB.s2p see file header for port/pin assignment table |
| RoHS compatible | defined as compatible with the following documents: "DIRECTIVE 2002/95/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 27 January 2003 on the restriction of the use of certain hazardous substances in electrical and electronic equipment. 2005/618/EC from April 18th, 2005, amending Directive 2002/95/EC of the European Parliament and of the Council for the purposes of establishing the maximum concentration values for certain hazardous substances in electrical and electronic equipment." |
| Moldability | Before using in overmolding environment, please contact your EPCOS sales office. |

For further information please contact your local EPCOS sales office or visit our webpage at www.epcos.com .

Published by EPCOS AG

Surface Acoustic Wave Components Division

P.O. Box 80 17 09, 81617 Munich, GERMANY

© EPCOS AG 27 November 2008. This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.

Important notes

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out **that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application**. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified**. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health (e.g. in accident prevention or life-saving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of an electronic component.
3. **The warnings, cautions and product-specific notes must be observed.**
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as hazardous)**. Useful information on this will be found in our Material Data Sheets on the Internet (www.epcos.com/material). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order.
We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available. The aforementioned does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.
6. Unless otherwise agreed in individual contracts, **all orders are subject to the current version of the "General Terms of Delivery for Products and Services in the Electrical Industry" published by the German Electrical and Electronics Industry Association (ZVEI)**.
7. The trade names EPCOS, BAOKE, Alu-X, CeraDiode, CSSP, CTVS, DSSP, MiniBlue, MKK, MLSC, MotorCap, PCC, PhaseCap, PhaseMod, SIFERRIT, SIFI, SIKOREL, SilverCap, SIMDAD, SIMID, SineFormer, SIOV, SIP5D, SIP5K, ThermoFuse, WindCap are **trademarks registered or pending** in Europe and in other countries. Further information will be found on the Internet at www.epcos.com/trademarks.