

# MULTILAYER CERAMIC CHIP CAPACITORS


Commercial grade, high voltage (1,000V and over)

## C series

---

<b>C3216</b>	<b>[1206 inch]</b>
<b>C3225</b>	<b>[1210 inch]</b>
<b>C4520</b>	<b>[1808 inch]</b>
<b>C4532</b>	<b>[1812 inch]</b>
<b>C5750</b>	<b>[2220 inch]</b>

\* Dimensions code: JIS[EIA]



# REMINDERS FOR USING THESE PRODUCTS

Before using these products, be sure to request the delivery specifications.

## SAFETY REMINDERS

Please pay sufficient attention to the warnings for safe designing when using this products.

 **REMINDERS**

1. The products listed on this catalog are intended for use in general electronic equipment (AV equipment, telecommunications equipment, home appliances, amusement equipment, computer equipment, personal equipment, office equipment, measurement equipment, industrial robots) under a normal operation and use condition.

The products are not designed or warranted to meet the requirements of the applications listed below, whose performance and/or quality require a more stringent level of safety or reliability, or whose failure, malfunction or trouble could cause serious damage to society, person or property.

If you intend to use the products in the applications listed below or if you have special requirements exceeding the range or conditions set forth in the each catalog, please contact us.

- |  |  |
|--|--|
| (1) Aerospace/aviation equipment   | (8) Public information-processing equipment                                  |
| (2) Transportation equipment (cars, electric trains, ships, etc.)                    | (9) Military equipment   |
| (3) Medical equipment (excepting Pharmaceutical Affairs Law classification Class1,2) | (10) Electric heating apparatus, burning equipment                           |
| (4) Power-generation control equipment   | (11) Disaster prevention/crime prevention equipment                          |
| (5) Atomic energy-related equipment  | (12) Safety equipment  |
| (6) Seabed equipment   | (13) Other applications that are not considered general-purpose applications |
| (7) Transportation control equipment   |  |

When designing your equipment even for general-purpose applications, you are kindly requested to take into consideration securing protection circuit/device or providing backup circuits in your equipment.

- We may modify products or discontinue production of a product listed in this catalog without prior notification.
- We provide "Delivery Specification" that explain precautions for the specifications and safety of each product listed in this catalog. We strongly recommend that you exchange these delivery specifications with customers that use one of these products.
- If you plan to export a product listed in this catalog, keep in mind that it may be a restricted item according to the "Foreign Exchange and Foreign Trade Control Law". In such cases, it is necessary to acquire export permission in harmony with this law.
- Any reproduction or transferring of the contents of this catalog is prohibited without prior permission from our company.
- We are not responsible for problems that occur related to the intellectual property rights or other rights of our company or a third party when you use a product listed in this catalog. We do not grant license of these rights.
- This catalog only applies to products purchased through our company or one of our company's official agencies. This catalog does not apply to products that are purchased through other third parties.

Notice: Effective January 2013, TDK will use a new catalog number which adds product thickness and packaging specification detail. This new catalog number should be referenced on all catalog orders going forward, and is not applicable for OEM part number orders.

Please be aware the last five digits of the catalog number will differ from the item description (internal control number) on the product label.

Contact your local TDK Sales representative for more information.

(Example)

Catalog issued date	Catalog number	Item description (on delivery label)
Prior to January 2013	C1608C0G1E103J(080AA)	C1608C0G1E103JT000N
January 2013 and later	C1608C0G1E103J080AA	C1608C0G1E103JT000N

# C series

## High voltage (1,000V and over)

Type: C3216 [1206 inch], C3225 [1210 inch], C4520 [1808 inch],  
C4532 [1812 inch], C5750 [2220 inch]



### SERIES OVERVIEW

High voltage C series, commercial grade of TDK's multilayer ceramic chip capacitor, is a product having a high withstanding voltage characteristic. The lineup is voltage rating of 1,000V to 3,000V with capacitance range up to 47nF.


### FEATURES

- Voltage rating of 1,000V, 2,000V and 3,000V
- Operating temperature range: -55 to +125°C
- COG type having excellent stable temperature and DC-bias characteristics is also available

### APPLICATIONS


- Decoupling, snubber and resonant circuits of high voltage circuits
- Wireless charging units, DC-DC converter, Inverter

### SHAPE & DIMENSIONS



L	Body length
W	Body width
T	Body height
B	Terminal width

### RECOMMENDED CONDITIONS



- It is recommended to provide a slit (about 1mm width) in the board under the components to improve washing flux.
- Please make sure to dry detergent up completely before.
- It is recommended to use low activated flux (Chlorine content: less than 0.1wt%) such rosin due to high voltage usage.
- When mounting on an aluminum substrate, it is more likely to be affected by heat stress from the substrate. Please inquire separate specification when mounted on the substrate.

Dimensions in mm

Type	L	W	T	B
C3216	3.20±0.20	1.60±0.20	1.30±0.20	0.20 min.
C3225	3.20±0.40	2.50±0.30	2.50±0.30	0.20 min.
C4520	4.50±0.40	2.00±0.20	2.00±0.20	0.20 min.
C4532	4.50±0.40	3.20±0.40	2.50±0.30	0.20 min.
C5750	5.70±0.40	5.00±0.40	2.80±0.30	0.20 min.

\*Dimensional tolerances are typical values.

**CATALOG NUMBER CONSTRUCTION**

<b>C</b>	<b>5750</b>	<b>X7S</b>	<b>3A</b>	<b>473</b>	<b>K</b>	<b>250</b>	<b>K</b>	<b>A</b>
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)

## (1) Series

## (2) Dimensions L x W (mm)

Code	EIA	Length	Width	Terminal width
C3216	CC1206	3.20	1.60	0.20 min.
C3225	CC1210	3.20	2.50	0.20 min.
C4520	CC1808	4.50	2.00	0.20 min.
C4532	CC1812	4.50	3.20	0.20 min.
C5750	CC2220	5.70	5.00	0.20 min.

## (3) Temperature characteristics

Temperature characteristics	Temperature coefficient or capacitance change	Temperature range
C0G	0±30 ppm/°C	-55 to +125°C
CH	0±60 ppm/°C	-25 to +85°C
JB	±10%	-25 to +85°C
X7R	±15%	-55 to +125°C
X7S	±22%	-55 to +125°C

## (4) Rated voltage (DC)

Code	Voltage (DC)
3A	1,000V
3D	2,000V
3F	3,000V

## (5) Nominal capacitance (pF)

The capacitance is expressed in three digit codes and in units of pico Farads (pF). The first and second digits identify the first and second significant figures of the capacitance. The third digit identifies the multiplier. R designates a decimal point.

(Example)OR5 = 0.5pF  
 101 = 100pF  
 225 = 2,200,000pF = 2.2μF

## (6) Capacitance tolerance

Code	Tolerance
F	±1pF
J	±5%
K	±10%
M	±20%

## (7) Thickness

Code	Thickness
085	0.85 mm
110	1.10 mm
130	1.30 mm
160	1.60 mm
200	2.00 mm
230	2.30 mm
250	2.50 mm
280	2.80 mm

## (8) Packaging style






Code	Style
A	178mm reel, 4mm pitch
K	178mm reel, 8mm pitch

## (9) Special reserved code

Code	Description
A,C	TDK internal code

## Capacitance range chart

### C3216 [1206 inch]





















Capacitance		X7S	
(pF)	Code	3D (2kV)	3A (1kV)
100	101		
220	221		
470	471		
1,000	102		
2,200	222		

Standard thickness  0.85 mm  1.30 mm

■ For details such as the catalog numbers, please refer to the capacitance range table on page 8 and after.

## Capacitance range chart

### C3225 [1210 inch]

Capacitance		C0G	X7S	
(pF)	Code	3A (1kV)	3D (2kV)	3A (1kV)
1,000	102			
1,200	122			
1,500	152			
1,800	182			
2,200	222			
2,700	272			
3,300	332			
3,900	392			
4,700	472			
5,600	562			
6,800	682			
8,200	822			
10,000	103			
12,000	123			
15,000	153			
18,000	183			
22,000	223			

Standard thickness  1.60 mm  2.00 mm  2.30 mm  2.50 mm

 Background gray: These products are not recommended for new designs.






■ For details such as the catalog numbers, please refer to the capacitance range table on page 8 and after.


# MULTILAYER CERAMIC CHIP CAPACITORS

## Capacitance range chart

C4520 [1808 inch]

Capacitance		C0G	CH	JB		X7R	
(pF)	Code	3F (3kV)	3F (3kV)	3D (2kV)	3A (1kV)	3D (2kV)	3A (1kV)
10	100						
12	120						
15	150						
18	180						
22	220						
27	270						
33	330						
39	390						
47	470						
56	560						
68	680						
82	820						
100	101						
470	471						
1,000	102						

Standard thickness  0.85 mm  1.10 mm  1.30 mm  1.60 mm  2.00 mm






 Background gray: These products are not recommended for new designs.


■ For details such as the catalog numbers, please refer to the capacitance range table on page 8 and after.

## Capacitance range chart


C4532 [1812 inch]

Capacitance		C0G	CH	JB		X7R	
(pF)	Code	3F (3kV)	3F (3kV)	3D (2kV)	3A (1kV)	3D (2kV)	3A (1kV)
100	101						
120	121						
150	151						
180	181						
220	221						
270	271						
330	331						
2,200	222						
4,700	472						
10,000	103						

Standard thickness  1.30 mm  1.60 mm  2.00 mm  2.30 mm  2.50 mm

 Background gray: These products are not recommended for new designs.

■ For details such as the catalog numbers, please refer to the capacitance range table on page 8 and after.

 Please be sure to request delivery specifications that provide further details on the features and specifications of the products for proper and safe use. Please note that the contents may change without any prior notice due to reasons such as upgrading.

## Capacitance range chart

## C5750 [2220 inch]

Capacitance		C0G	X7S	
(pF)	Code		3A (1kV)	3D (2kV)
4,700	472			
10,000	103			
12,000	123			
15,000	153			
18,000	183			
22,000	223			
27,000	273			
33,000	333			
47,000	473			

Standard thickness  1.60 mm  2.00 mm  2.50 mm  2.80 mm

 Background gray: These products are not recommended for new designs.

■ For details such as the catalog numbers, please refer to the capacitance range table on page 8 and after.

## Capacitance range table

Temperature characteristic: C0G (-55 to +125°C, 0±30ppm/°C)

Capacitance	Dimensions	Thickness (mm)	Capacitance tolerance	Catalog number	
				Rated voltage Edc: 3kV	Rated voltage Edc: 1kV
10pF	4520	0.85±0.15	±1pF	<a href="#">C4520C0G3F100F085KA</a>	
12pF	4520	0.85±0.15	±10%	<a href="#">C4520C0G3F120K085KA</a>	
15pF	4520	1.10±0.20	±10%	<a href="#">C4520C0G3F150K110KA</a>	
18pF	4520	1.10±0.20	±10%	<a href="#">C4520C0G3F180K110KA</a>	
22pF	4520	1.10±0.20	±10%	<a href="#">C4520C0G3F220K110KA</a>	
27pF	4520	1.60±0.20	±10%	<a href="#">C4520C0G3F270K160KA</a>	
33pF	4520	1.60±0.20	±10%	<a href="#">C4520C0G3F330K160KA</a>	
39pF	4520	1.60±0.20	±10%	<a href="#">C4520C0G3F390K160KA</a>	
47pF	4520	1.60±0.20	±10%	<a href="#">C4520C0G3F470K160KA</a>	
56pF	4520	2.00±0.20	±10%	<a href="#">C4520C0G3F560K200KA</a>	
68pF	4520	2.00±0.20	±10%	<a href="#">C4520C0G3F680K200KA</a>	
82pF	4520	2.00±0.20	±10%	<a href="#">C4520C0G3F820K200KA</a>	
100pF	4520	2.00±0.20	±10%	<a href="#">C4520C0G3F101K200KA</a>	
	4532	1.60±0.20	±10%	<a href="#">C4532C0G3F101K160KA</a>	
120pF	4532	1.60±0.20	±10%	<a href="#">C4532C0G3F121K160KA</a>	
150pF	4532	1.60±0.20	±10%	<a href="#">C4532C0G3F151K160KA</a>	
180pF	4532	1.60±0.20	±10%	<a href="#">C4532C0G3F181K160KA</a>	
220pF	4532	2.00±0.20	±10%	<a href="#">C4532C0G3F221K200KA</a>	
270pF	4532	2.30±0.20	±10%	<a href="#">C4532C0G3F271K230KA</a>	
330pF	4532	2.50±0.30	±10%	<a href="#">C4532C0G3F331K250KA</a>	
1nF	3225	2.00±0.20	±5%		<a href="#">C3225C0G3A102J200AC</a>
1.2nF	3225	2.00±0.20	±5%		<a href="#">C3225C0G3A122J200AC</a>
1.5nF	3225	2.00±0.20	±5%		<a href="#">C3225C0G3A152J200AC</a>
1.8nF	3225	2.00±0.20	±5%		<a href="#">C3225C0G3A182J200AC</a>
2.2nF	3225	2.00±0.20	±5%		<a href="#">C3225C0G3A222J200AC</a>
2.7nF	3225	2.00±0.20	±5%		<a href="#">C3225C0G3A272J200AC</a>
3.3nF	3225	2.00±0.20	±5%		<a href="#">C3225C0G3A332J200AC</a>
3.9nF	3225	2.00±0.20	±5%		<a href="#">C3225C0G3A392J200AC</a>
4.7nF	3225	2.00±0.20	±5%		<a href="#">C3225C0G3A472J200AC</a>
5.6nF	3225	2.00±0.20	±5%		<a href="#">C3225C0G3A562J200AC</a>
6.8nF	3225	2.00±0.20	±5%		<a href="#">C3225C0G3A682J200AC</a>
8.2nF	3225	2.30±0.20	±5%		<a href="#">C3225C0G3A822J230AC</a>
10nF	3225	2.50±0.30	±5%		<a href="#">C3225C0G3A103J250AC</a>
	5750	2.80±0.30	±5%		<a href="#">C5750C0G3A103J280KC</a>
12nF	3225	2.50±0.30	±5%		<a href="#">C3225C0G3A123J250AC</a>
	5750	2.80±0.30	±5%		<a href="#">C5750C0G3A123J280KC</a>
15nF	3225	2.50±0.30	±5%		<a href="#">C3225C0G3A153J250AC</a>
	5750	2.80±0.30	±5%		<a href="#">C5750C0G3A153J280KC</a>
18nF	3225	2.50±0.30	±5%		<a href="#">C3225C0G3A183J250AC</a>
	5750	2.80±0.30	±5%		<a href="#">C5750C0G3A183J280KC</a>
22nF	3225	2.50±0.30	±5%		<a href="#">C3225C0G3A223J250AC</a>
	5750	2.80±0.30	±5%		<a href="#">C5750C0G3A223J280KC</a>
27nF	5750	2.80±0.30	±5%		<a href="#">C5750C0G3A273J280KC</a>
33nF	5750	2.80±0.30	±5%		<a href="#">C5750C0G3A333J280KC</a>

■ Gray items: These products are not recommended for new designs.  
Click the part numbers for details.



## Capacitance range table

Temperature characteristic: CH (–25 to +85°C, 0±60ppm/°C)

Capacitance	Dimensions	Thickness (mm)	Capacitance tolerance	Catalog number	
				Rated voltage Edc: 3kV	
10pF	4520	0.85±0.15	±1pF	C4520CH3F100F085KA	
12pF	4520	0.85±0.15	±10%	C4520CH3F120K085KA	
15pF	4520	1.10±0.20	±10%	C4520CH3F150K110KA	
18pF	4520	1.10±0.20	±10%	C4520CH3F180K110KA	
22pF	4520	1.10±0.20	±10%	C4520CH3F220K110KA	
27pF	4520	1.60±0.20	±10%	C4520CH3F270K160KA	
33pF	4520	1.60±0.20	±10%	C4520CH3F330K160KA	
39pF	4520	1.60±0.20	±10%	C4520CH3F390K160KA	
47pF	4520	1.60±0.20	±10%	C4520CH3F470K160KA	
56pF	4520	2.00±0.20	±10%	C4520CH3F560K200KA	
68pF	4520	2.00±0.20	±10%	C4520CH3F680K200KA	
82pF	4520	2.00±0.20	±10%	C4520CH3F820K200KA	
100pF	4520	2.00±0.20	±10%	C4520CH3F101K200KA	
	4532	1.60±0.20	±10%	C4532CH3F101K160KA	
120pF	4532	1.60±0.20	±10%	C4532CH3F121K160KA	
150pF	4532	1.60±0.20	±10%	C4532CH3F151K160KA	
180pF	4532	1.60±0.20	±10%	C4532CH3F181K160KA	
220pF	4532	2.00±0.20	±10%	C4532CH3F221K200KA	
270pF	4532	2.30±0.20	±10%	C4532CH3F271K230KA	
330pF	4532	2.50±0.30	±10%	C4532CH3F331K250KA	

■ Gray items: These products are not recommended for new designs.  
Click the part numbers for details.

## Capacitance range table

Temperature characteristic: JB (–25 to +85°C, ±10%)

Capacitance	Dimensions	Thickness (mm)	Capacitance tolerance	Catalog number	
				Rated voltage Edc: 2kV	Rated voltage Edc: 1kV
470pF	4520	1.30±0.20	±10%	C4520JB3D471K130KA	C4520JB3A471K130KA
			±20%	C4520JB3D471M130KA	C4520JB3A471M130KA
1nF	4520	1.30±0.20	±10%	C4520JB3D102K130KA	C4520JB3A102K130KA
			±20%	C4520JB3D102M130KA	C4520JB3A102M130KA
2.2nF	4532	1.30±0.20	±10%	C4532JB3D222K130KA	
			±20%	C4532JB3D222M130KA	
4.7nF	4532	1.60±0.20	±10%		C4532JB3A472K160KA
			±20%		C4532JB3A472M160KA
10nF	4532	2.00±0.20	±10%		C4532JB3A103K200KA
			±20%		C4532JB3A103M200KA

■ Gray items: These products are not recommended for new designs.  
Click the part numbers for details.

## Capacitance range table

Temperature characteristic: X7R (–55 to +125°C, ±15%)

Capacitance	Dimensions	Thickness (mm)	Capacitance tolerance	Catalog number	
				Rated voltage Edc: 2kV	Rated voltage Edc: 1kV
470pF	4520	1.30±0.20	±10%	C4520X7R3D471K130KA	C4520X7R3A471K130KA
			±20%	C4520X7R3D471M130KA	C4520X7R3A471M130KA
1nF	4520	1.30±0.20	±10%	C4520X7R3D102K130KA	C4520X7R3A102K130KA
			±20%	C4520X7R3D102M130KA	C4520X7R3A102M130KA
2.2nF	4532	1.30±0.20	±10%	C4532X7R3D222K130KA	
			±20%	C4532X7R3D222M130KA	
4.7nF	4532	1.60±0.20	±10%		C4532X7R3A472K160KA
			±20%		C4532X7R3A472M160KA
10nF	4532	2.00±0.20	±10%		C4532X7R3A103K200KA
			±20%		C4532X7R3A103M200KA

■ Gray items: These products are not recommended for new designs.  
Click the part numbers for details.

## Capacitance range table

Temperature characteristic: X7S (-55 to +125°C, ±22%)

Capacitance	Dimensions	Thickness (mm)	Capacitance tolerance	Catalog number	
				Rated voltage Edc: 2kV	Rated voltage Edc: 1kV
100pF	3216	0.85±0.15	±10%	<a href="#">C3216X7S3D101K085AA</a>	
220pF	3216	0.85±0.15	±10%	<a href="#">C3216X7S3D221K085AA</a>	
470pF	3216	1.30±0.20	±10%	<a href="#">C3216X7S3D471K130AA</a>	
1nF	3216	0.85±0.15	±10%		<a href="#">C3216X7S3A102K085AA</a>
	3225	2.00±0.20	±10%	<a href="#">C3225X7S3D102K200AA</a>	
2.2nF	3216	1.30±0.20	±10%		<a href="#">C3216X7S3A222K130AA</a>
	3225	2.50±0.30	±10%	<a href="#">C3225X7S3D222K250AA</a>	
4.7nF	3225	1.60±0.20	±10%		<a href="#">C3225X7S3A472K160AA</a>
	5750	2.00±0.20	±10%	<a href="#">C5750X7S3D472K200KA</a>	
10nF	5750	2.50±0.30	±10%	<a href="#">C5750X7S3D103K250KA</a>	
22nF	5750	1.60±0.20	±10%		<a href="#">C5750X7S3A223K160KA</a>
47nF	5750	2.50±0.30	±10%		<a href="#">C5750X7S3A473K250KA</a>

Click the part numbers for details.