

Chip beads

For power line

MPZ series (for automotive)



AEC-Q200

MPZ1608 type



FEATURES

- Noise reduction solution for power line.
- Because of its low DC resistance, it can handle large currents of 8A or more, optimal for low power consumption.
- Various frequency characteristics with 5 materials of different features for countermeasures against everything from general signals to high-speed signals.
- Performs well even in signal lines where low direct current resistance is required.
- Operating temperature range: -55 to +125°C


APPLICATION

- Various ECUs, powertrains, body controls, and car multimedia (telematics).

PART NUMBER CONSTRUCTION

MPZ	1608	S	PH	220	A	T	DH5
Series name	L x W x T dimensions 1.6x0.8x0.6 mm	Material name	Internal code	Impedance (Ω) at 100MHz	Characteristic type	Packaging style	Internal code

MPZ	1608	S	471	A	T	D25
Series name	L x W x T dimensions 1.6x0.8x0.6 mm 1.6x0.8x0.8 mm	Material name	Impedance (Ω) at 100MHz	Characteristic type	Packaging style	Internal code



MPZ1608 type

CHARACTERISTICS SPECIFICATION TABLE


Impedance [100MHz] (Ω)		DC resistance (Ω)max.	Rated current* (A)max.	Thickness T (mm)	Part No.
Tolerance					
470 ±25%		0.150	1.0	0.8	MPZ1608B471ATD25
22 ±7Ω		0.004	8.0	0.6	MPZ1608SPH220ATDH5
26 ±25%		0.007	6.0	0.6	MPZ1608S260ATDH5
30 ±10Ω		0.010	5.0	0.6	MPZ1608S300ATDH5
60 ±25%		0.020	3.5	0.6	MPZ1608S600ATDH5
100 ±25%		0.030	3.0	0.6	MPZ1608S101ATDH5
120 ±25%		0.045	2.0	0.6	MPZ1608S121ATDH5
180 ±25%		0.050	2.0	0.6	MPZ1608S181ATDH5
220 ±25%		0.050	2.2	0.8	MPZ1608S221ATD25
330 ±25%		0.080	1.7	0.8	MPZ1608S331ATD25
470 ±25%		0.150	1.0	0.8	MPZ1608S471ATD25
600 ±25%		0.150	1.0	0.8	MPZ1608S601ATD25
1000 ±25%		0.300	0.8	0.8	MPZ1608S102ATD25
390 ±25%		0.120	1.2	0.8	MPZ1608R391ATD25
60 ±25%		0.030	2.3	0.8	MPZ1608Y600BTD25
100 ±25%		0.040	2.0	0.8	MPZ1608Y101BTD25
150 ±25%		0.050	1.8	0.8	MPZ1608Y151BTD25
220 ±25%		0.100	1.5	0.8	MPZ1608Y221BTD25
30 ±10Ω		0.060	1.8	0.8	MPZ1608D300BTD25
60 ±25%		0.100	1.2	0.8	MPZ1608D600BTD25
100 ±25%		0.150	1.0	0.8	MPZ1608D101BTD25

Measurement equipment

Measurement item	Product No. *	Manufacturer
Impedance	4991A+16192A	Keysight Technologies
DC resistance	Type-755611	Yokogawa

* Equivalent measurement equipment may be used.


Rated current vs. temperature characteristics (derating)




MPZ1608 type

Z VS. FREQUENCY CHARACTERISTICS (BY TYPES)


MPZ1608B type




MPZ1608SPH type




MPZ1608S type




MPZ1608R type



MPZ1608Y type




MPZ1608D type




MPZ1608 type

Z, X, R VS. FREQUENCY CHARACTERISTICS


MPZ1608B471ATD25




MPZ1608SPH220ATDH5




MPZ1608S260ATDH5




MPZ1608S300ATDH5




MPZ1608S600ATDH5




MPZ1608S101ATDH5




MPZ1608S121ATDH5




MPZ1608S181ATDH5




MPZ1608S221ATD25




MPZ1608S331ATD25




MPZ1608S471ATD25




MPZ1608S601ATD25




MPZ1608S102ATD25



MPZ1608R391ATD25




MPZ1608Y600BTD25




MPZ1608 type

Z, X, R VS. FREQUENCY CHARACTERISTICS


MPZ1608Y101BTD25




MPZ1608Y151BTD25




MPZ1608Y221BTD25




MPZ1608D300BTD25



MPZ1608D600BTD25




MPZ1608D101BTD25




MPZ1608 type

SHAPE & DIMENSIONS




RECOMMENDED LAND PATTERN


MPZ1608****TD25/DH5



MPZ1608SPH****TDH5




RECOMMENDED REFLOW PROFILE




PACKAGING STYLE


REEL DIMENSIONS



TAPE DIMENSIONS



Type	A	B	K
MPZ1608	1.1±0.2	1.9±0.2	1.1max.



PACKAGE QUANTITY

Package quantity	4,000 pcs/reel
------------------	----------------

TEMPERATURE RANGE, INDIVIDUAL WEIGHT

Type	Operating temperature range	Storage temperature range *	Individual weight
t=0.6mm	-55 to +125°C	-55 to +125°C	3 mg
t=0.8mm	-55 to +125°C	-55 to +125°C	4 mg

* Operating temperature range includes self-heating.

REMINDERS FOR USING THESE PRODUCTS

Before using these products, be sure to request the delivery specifications.

SAFETY REMINDERS

Please pay sufficient attention to the warnings for safe designing when using this products

REMINDERS

- The storage period is within 12 months. Be sure to follow the storage conditions (temperature: 5 to 40°C, humidity: 10 to 75% RH or less).
If the storage period elapses, the soldering of the terminal electrodes may deteriorate.
- Do not use or store in locations where there are conditions such as gas corrosion (salt, acid, alkali, etc.).
- Before soldering, be sure to preheat components.
The preheating temperature should be set so that the temperature difference between the solder temperature and chip temperature does not exceed 150°C.
- Soldering corrections after mounting should be within the range of the conditions determined in the specifications.
If overheated, a short circuit, performance deterioration, or lifespan shortening may occur.
- When embedding a printed circuit board where a chip is mounted to a set, be sure that residual stress is not given to the chip due to the overall distortion of the printed circuit board and partial distortion such as at screw tightening portions.
- Self heating (temperature increase) occurs when the power is turned ON, so the tolerance should be sufficient for the set thermal design.
- Carefully lay out the coil for the circuit board design of the non-magnetic shield type.
A malfunction may occur due to magnetic interference.
- Use a wrist band to discharge static electricity in your body through the grounding wire.
- Do not expose the products to magnets or magnetic fields.
- Do not use for a purpose outside of the contents regulated in the delivery specifications.
- The products listed on this catalog are intended for use in general electronic equipment (AV equipment, telecommunications equipment, home appliances, amusement equipment, computer equipment, personal equipment, office equipment, measurement equipment, industrial robots) under a normal operation and use condition.
The products are not designed or warranted to meet the requirements of the applications listed below, whose performance and/or quality require a more stringent level of safety or reliability, or whose failure, malfunction or trouble could cause serious damage to society, person or property.
If you intend to use the products in the applications listed below or if you have special requirements exceeding the range or conditions set forth in the each catalog, please contact us.

- (1) Aerospace/aviation equipment
- (2) Transportation equipment (electric trains, ships, etc.)
- (3) Medical equipment
- (4) Power-generation control equipment
- (5) Atomic energy-related equipment
- (6) Seabed equipment

- (7) Transportation control equipment
- (8) Public information-processing equipment
- (9) Military equipment
- (10) Electric heating apparatus, burning equipment
- (11) Disaster prevention/crime prevention equipment
- (12) Safety equipment
- (13) Other applications that are not considered general-purpose applications

When designing your equipment even for general-purpose applications, you are kindly requested to take into consideration securing protection circuit/device or providing backup circuits in your equipment.