


## 4-Port DisplayPort KVM Switch with Audio, Cables and USB 3.0 SuperSpeed Hub

MODEL NUMBER: B004-DPUA4-K



Control 4 DisplayPort computers using one DisplayPort monitor, USB keyboard and USB mouse. Connect USB 3.0 peripherals, such as hard drives and webcams, and share them between computers.

### Features

#### Access and Control Up to 4 Computers with One KVM Switch

- Switch among computers using keyboard hotkeys or front-panel buttons
- Monitor's EDID information sent to connected computer when selected
- Auto Scan feature cycles among computers at regular intervals for at-a-glance observation of activity
- Supports DisplayPort 1.1

#### Independent Audio Switching

- 3.5 mm mini-stereo speaker and microphone jacks allow sharing of audio equipment among computers
- Listen to audio files on one computer while accessing another computer
- Supports 2-channel stereo audio

#### Independent USB 3.0 Peripheral Sharing

- 2-port USB 3.0 SuperSpeed hub allows connection of peripherals, such as webcams, flash drives, printers and scanners
- Print documents from one computer while accessing another computer
- Supports USB 3.0 data transfer rates up to 5 Gbps
- Backward compatible with USB 2.0 and USB 1.1 devices

#### Compatible with All Major Operating Systems

- Easy to set up with no software or drivers to install
- Supports digital video resolutions up to 2560 x 1600, including 1080p
- Works with Windows, Mac, Linux and Sun
- All necessary cables included

### Highlights

- Connect peripherals to built-in 2-port USB 3.0 hub
- Switch among computers via front buttons or keyboard hotkeys
- Supports digital video resolutions up to 2560 x 1600
- Supports Displayport 1.1
- Includes all necessary DisplayPort, USB 3.0 and audio cables

### System Requirements

- DisplayPort-enabled monitor
- USB keyboard and mouse
- Speaker and microphone with 3.5 mm mini-stereo plugs (for audio)
- Computer with USB port (need USB 3.0 port for USB 3.0 speed)
- Computer with 3.5 mm mini-stereo jacks (for audio)
- Compatible with all major operating systems

### Package Includes

- B004-DPUA4-K 4-Port DisplayPort KVM Switch
- (4) DisplayPort cables, 6-ft. (1.83 m)
- (4) USB 3.0 Type-A to Type-B cables, 6-ft. (1.83 m)
- (4) 3.5 mm mini-stereo cables, 6-ft. (1.83 m)
- External power supply (Input: 100/240V, 50/60 Hz, 0.8A; Output: 9V, 2A)
- Universal plug adapters (NEMA 1-15P, CEE 7/16, BS1363, and AS3112)
- Owner's manual



Powering Business Worldwide

TRIPP LITE  
SERIES

## Specifications

| OVERVIEW                                  |                                                                              |
|-------------------------------------------|------------------------------------------------------------------------------|
| UPC Code                                  | 037332188632                                                                 |
| Technology                                | DisplayPort; Stereo Audio                                                    |
| VIDEO                                     |                                                                              |
| Max Supported Video Resolution            | 2560 x 1600 @60Hz                                                            |
| INPUT                                     |                                                                              |
| AC Power Adapter Plug(s)                  | NEMA 1-15P North America; CEE 7/16 Schuko; BS 1363 UK; AS/NZS 3112 Australia |
| AC Power Adapter Input Specs (V / Hz / A) | 100-240V / 50/60Hz / 0.8A                                                    |
| AC Power Adapter Output Specs (V / A)     | 9V / 2A                                                                      |
| AC Power Adapter Cord Length (ft.)        | 6                                                                            |
| AC Power Adapter Cord Length (m)          | 1.83                                                                         |
| Voltage Compatibility (VAC)               | 100; 110; 120; 127; 200; 208; 220; 230; 240                                  |
| POWER                                     |                                                                              |
| Power Source Type                         | AC Adapter                                                                   |
| AC Adapter                                | Input: 100-240V, 50/60Hz, 0.8A Output: 9V, 2A                                |
| DC Barrel Plug                            | OD: 5.5 x 2.1 x 10mm, Positive Pin, Negative Sleeve                          |
| Power Consumption (Watts)                 | 6.5                                                                          |
| CONNECTIONS                               |                                                                              |
| Number of Ports                           | 4                                                                            |
| PC/Server Connections                     | USB; DisplayPort                                                             |
| Side A - Connector 1                      | (4) DISPLAYPORT (FEMALE)                                                     |
| Side A - Connector 2                      | (4) USB 3.0 B (FEMALE)                                                       |
| Side A - Connector 3                      | (8) 3.5MM (FEMALE)                                                           |
| Side B - Connector 1                      | DISPLAYPORT (FEMALE)                                                         |
| Side B - Connector 2                      | (2) USB 3.0 A (FEMALE)                                                       |
| Side B - Connector 3                      | (2) USB A (FEMALE)                                                           |
| Side B - Connector 4                      | (2) 3.5MM (FEMALE)                                                           |
| Computer Keyboard and Mouse Interface     | USB                                                                          |
| Computer Monitor Interface                | Displayport                                                                  |
| Console Keyboard and Mouse Interface      | USB                                                                          |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                              |                                                      |
|----------------------------------------------|------------------------------------------------------|
| Console Monitor Interface                    | Displayport                                          |
| Connector Plating                            | Nickel                                               |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b> |                                                      |
| LED Indicators                               | Red (USB); White (Selected PC)                       |
| <b>PHYSICAL</b>                              |                                                      |
| Color                                        | Black                                                |
| Material of Construction                     | Steel                                                |
| Cable Jacket Color                           | Black                                                |
| Shipping Dimensions (hwd / in.)              | 7.40 x 6.20 x 10.60                                  |
| Shipping Dimensions (hwd / cm)               | 18.80 x 15.75 x 26.92                                |
| Shipping Weight (lbs.)                       | 5.90                                                 |
| Shipping Weight (kg)                         | 2.68                                                 |
| Unit Dimensions (hwd / in.)                  | 1.800 x 8.100 x 3.900                                |
| Unit Packaging Type                          | Box                                                  |
| Unit Weight (lbs.)                           | 2.1                                                  |
| Unit Weight (kg)                             | 0.95                                                 |
| <b>ENVIRONMENTAL</b>                         |                                                      |
| Operating Temperature Range                  | 32° to 104°F (0° to 40°C)                            |
| Storage Temperature Range                    | -4° to 140°F (-20° to 60°C)                          |
| Relative Humidity                            | 0-90% non-condensing                                 |
| BTUs                                         | 22.2 BTU/Hr                                          |
| <b>COMMUNICATIONS</b>                        |                                                      |
| IP Remote Access                             | No                                                   |
| <b>FEATURES &amp; SPECIFICATIONS</b>         |                                                      |
| USB Hub Ports                                | Yes                                                  |
| Number of USB Hub Ports                      | 2                                                    |
| USB Specification                            | USB 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (up to 5 Gbps) |
| NIAP-Certified Secure                        | No                                                   |
| Number of Users                              | 1                                                    |
| Autoscan (Y,N)                               | Y                                                    |
| Port Selection                               | Pushbutton; Hotkey                                   |
| Displayport Specification                    | 1.1                                                  |
| Driver Required                              | No                                                   |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                      |                                                                  |
|--------------------------------------|------------------------------------------------------------------|
| Autoscan Duration                    | 10 TO 60 (DEFAULTS AT 10, USER DEFINABLE IN 10 SECOND INTERVALS) |
| <b>STANDARDS &amp; COMPLIANCE</b>    |                                                                  |
| External Power Supply Certifications | CE; FCC; UL; cUL; TUV; GS; BS; RCM; CB                           |
| Product Compliance                   | RoHS; CE (Europe); REACH; FCC (USA)                              |
| <b>WARRANTY &amp; SUPPORT</b>        |                                                                  |
| Product Warranty Period (Worldwide)  | 3-year limited warranty                                          |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.