




MARKETING SALES DRAWING

DIMENSIONS IN INCHES - DO NOT SCALE THIS DRAWING
DIMENSIONS IN METRIC - []

This drawing is the property of Tusonix, Inc., and may not be used, reproduced, published or disclosed to others without expressed authorization by Tusonix Inc.

Electrical Testing
per Tusonix standard
test plans and Mil-Std-202
Test Methods.



SPECIFICATIONS

CAPACITANCE	1500 pF
CAP. TOL.	±20%
TEMP. COEF.	X5U
WORKING VOLTAGE	500 VDC @ +85°C
TEMP. RANGE	-55°C TO +85°C
CURRENT (A)	20
I.R. MIN. @ 100 VDC	10 G Ω
DWV @ 2 SEC. MIN.	875 VDC

NOTES:

- TUSONIX STANDARD PART NUMBER: 357-001-X5U0-152M.
TUSONIX RoHS COMPLIANT PART NUMBER:
357-001-X5U0-152M LF.
CUSTOMER MUST SPECIFY STANDARD OR RoHS PART
NUMBER WHEN ORDERING.
- PART MARKING: COLOR CODE DOTS, CAPACITANCE AND
TEMP. CHAR. ON TOP OF BUSHING HEX.
RoHS PART WITH ADDITIONAL GREEN DOT ON TUBE
AS IDENTIFIER.
- SUPPLIED WITH SILVER PLATED HEX NUT AND
LOCK WASHER.

X-2015 Rev-0

REVISION RECORD Original Release C.O. 20070112-1-01	0				
		--TOLERANCES-- Unless Otherwise Specified		Title BUSHING TYPE FEED-THRU CAPACITOR	
		DECIMAL ± .015 [0.38]		Drawn S.M. 01-12-07 Scale 4 X	
		ANGLES ±		Approved R.L. 01-12-07	
		TUSONIX TUCSON, ARIZONA		A 357-001-X5U0-152M	