



This drawing is the property of Tusonix, Inc., and may not be used, reproduced, published or disclosed to others without expressed authorization by Tusonix Inc.

MARKETING SALES DRAWING
DIMENSIONS IN INCHES - DO NOT SCALE THIS DRAWING
DIMENSIONS IN METRIC - []



Electrical Testing
per Tusonix standard
test plans and Mil-Std-202
Test Methods.



NOTES:

1. COMPONENT MUST BE CAPABLE OF WITHSTANDING HIPOT TEST AT 1500 VAC, 60 SEC.
2. ENDS OF LEADS MAY SHOW EXPOSED COPPER.
3. EPOXY COATED INSULATION BANDS: COVERAGE OF TOP AS SHOWN, COVERAGE OF BOTTOM .100" [2.54] DIA. MIN. (MAY OVERLAP ONTO OD SURFACE .020" [0.51] MAX.)
4. TUSONIX STANDARD PART NUMBER: 2470-501. TUSONIX RoHS COMPLIANT PART NUMBER: 2470-501 LF. CUSTOMER MUST SPECIFY STANDARD OR RoHS PART NUMBER WHEN ORDERING.
5. PLATED DIELECTRIC FINISH: STANDARD PART #: 60/40 SOLDER PLATED. RoHS PART #: TIN PLATED.
6. PART MARKING: STANDARD PART: NO MARKING. RoHS PART: GREEN INK DOT.
7. UL APPROVED AND CANADIAN RECOGNIZED PART NUMBER.

SPECIFICATIONS

CAP. VALUE:	1000 pF
CAP. TOL.:	+100, -0%
D.F.:	4% MAX.
RATING:	250 VAC @ +85°C
OPERATING RANGE:	-55°C TO +85°C
DWV (25°C):	1500 VAC
I.R.:	10 G Ω MIN.
IDC:	10 A

X-2015 Rev-0

REVISION RECORD	Original Release	
	WAS SK 8080-004 L.E. 10-17-03	
	20031017-1-02	0
	DIM'S IN METRIC ADDED & DIM :200 WAS .185 L.E. 01-06-04	
20031219-2-08	1	ADDED NOTES 3-6. RESCALED DRAWING. S.M. 02-03-06
20060109-1-08	2	SEE NOTE 3 WAS NOTE 2 & NOTE 2 WAS 1. S.M. 04-17-07
20070416-1-01	3	ADDED NOTE 7. S.M. 12-12-07
20071211-5-02	4	

--TOLERANCES-- Unless Otherwise Specified		Title UL RECOGNIZED SHOULDER FEED-THRU	
DECIMAL ± .031 [0.79]		Drawn L.E. 09-04-03	Scale 4 X
ANGLES ±		Approved K.L. 09-04-03	
TUSONIX TUCSON, ARIZONA		A	2470-501