




# MARKETING SALES DRAWING

**DIMENSIONS IN INCHES - DO NOT SCALE THIS DRAWING**  
**DIMENSIONS IN METRIC - [ ]**

This drawing is the property of  
 Tusonix, Inc., and may not be  
 used, reproduced, published or  
 disclosed to others without ex-  
 pressed authorization by Tusonix Inc.

**Electrical Testing**  
 per Tusonix standard  
 test plans and Mil-Std-202  
 Test Methods.



## SPECIFICATIONS

TUSONIX STYLE.	2499-003
Capacitance Value:	500 pF
Capacitance Tolerance:	±20%
Temp. Characteristics:	X5U
Rating:	500 WVDC @ 85 °C
Current (A):	20
IR Min @ 100 vdc	10 GΩ
DWV	1500 VDC
Operating Range:	-55° TO + 85°C

## NOTES:

1. SUPPLIED WITH SILVER PLATED HEX NUT AND INTERNAL TOOTH LOCK WASHER.
2. TUSONIX STANDARD PART NUMBER: 2499-003-X5U0-501M.  
TUSONIX R.o.H.S. COMPLIANT PART NUMBER: 2499-003-X5U0-501M LF.  
CUSTOMER MUST SPECIFY STANDARD OR RoHS PART NUMBER WHEN ORDERING.
3. PART MARKING: TRADEMARK, CAPACITANCE CODE AND TOLERANCE CODE STAMPED ON BUSHING HEX FLATS:  
STANDARD PART: BLACK MARKING.  
RoHS COMPLIANT PART: GREEN MARKING.

X2015 Rev-0 REVISION RECORD	Original Release C.O. 20070321-2-01		--TOLERANCES-- Unless Otherwise Specified	Title <b>BUSHING TYPE FEED-THRU CAPACITOR</b>	
			DECIMAL ± .015 [0.38]	Drawn S.M. 03-26-07	Scale 3X
			ANGLES ±	Approved R.L. 03-26-07	
			<b>TUSONIX</b> TUCSON, ARIZONA	A 2499-003-X5U0-501M	