Supplier Name: Texas Instruments Inc. (DUNS# 00-732-1904) Contact Info: ti.com/support Form/Declaration Type: Distribute - RoHS and IEC 62474 DB Created on: 05/09/2022

Details for "SN74HCT574N"

Current Product Information

TI part number	Lead finish/Ball material	MSL rating/peak reflow	Assembly site	Package Pins	Package body size (mm)	Total device mass (mg)*
SN74HCT574N	NIPDAU	Level-NC-NC-NC	TI MALAYSIA A/T	N 20	6.35x24.33x4.57	1969.5

*Total Device Mass

The summary mass is a rounded value and will be within approximately +/- 10% of the detailed mass value.

Environmental Ratings Information

Yes Yes Yes	Yes Yes	Yes	Yes

Component Information

Component Bond Wire Copper and Its Alloys Precious Metals	Substance Copper Silver	CAS Number 7440-50-8 7440-22-4	Amount (mg)	Percentage % 99.998182	ppm	Percentage %	ppm
Bond Wire Copper and Its Alloys Precious Metals Cold Table	Copper Silver	7440-50-8 7440-22-4	0.109986	99.998182	000000		
Copper and Its Alloys Precious Metals Color Details	Copper Silver	7440-50-8 7440-22-4	0.109986	99.998182	000003		
Precious Metals	Silver	7440-22-4	0.000000		999982	0.005584	56
Cult Tatal			0.000002	0.001818	18	0	0
Sub-Total			0.109988	100	1000000	0.005585	56
Die Attach Adhesive							
Precious Metals	Silver	7440-22-4	0.730052	80	800000	0.037068	371
Thermoplastics	Epoxy	85954-11-6	0.182513	20	200000	0.009267	93
Sub-Total			0.912565	100	1000000	0.046335	463
Lead Frame							
Copper and Its Alloys	Copper	7440-50-8	537.297915	97.05	970500	27.28099	272810
Copper and Its Alloys	Iron	7439-89-6	14.39438	2.6	26000	0.730866	7309
Copper and Its Alloys	Phosphorus	7723-14-0	0.830445	0.15	1500	0.042165	422
Zinc and Its Alloys	Zinc	7440-66-6	1.10726	0.2	2000	0.05622	562
Sub-Total			553.63	100	1000000	28.110242	281102
Lead Frame Plating							
Nickel and Its Alloys	Nickel	7440-02-0	1.835816	95.12	951200	0.093212	932
Precious Metals	Gold	7440-57-5	0.015054	0.78	7800	0.000764	8
Precious Metals	Palladium	7440-05-3	0.07913	4.1	41000	0.004018	40
Sub-Total			1.93	100	1000000	0.097995	980
Mold Compound							
Other Inorganic Materials	Fused Silica	60676-86-0	1240.735261	88	880000	62.997613	629976
Other Plastics and Rubber	Carbon Black	1333-86-4	4.229779	0.3	3000	0.214765	2148
Other Plastics and Rubber	Organic Phosphorus	1330-78-5	7.754595	0.55	5500	0.393735	3937
Thermoplastics	Epoxy	85954-11-6	157.206797	11.15	111500	7.982084	79821
Sub-Total			1409.926432	100	1000000	71.588196	715882
Semiconductor Device							
Ceramics / Glass	Doped Silicon	7440-21-3	2.986697	100	1000000	0.151648	1516
Sub-Total			2.986697	100	1000000	0.151648	1516
Total			1969,495682			100	1000000

Important Note

The ppm calculations are at the homogeneous material level and are maximum concentration values. The ppm displayed represents the homogeneous material with the highest ppm

for that substance. The amount (mg) calculations represent the maximum total amount of each substance within the component.

The ppm calculations are at the component level and are average concentration values. The amount (mg) calculations represent the average total amount of each substance within the component. See Glossary of Terms for more details.

Important Part Information

There is a remote possibility the Customer Part Number (CPN) your company uses could reference more than one TI part number. This is due to two or more users (EMSIs or subcontractors) using the same CPN for different TI part numbers. If this occurs, please check your Customer Part Number and cross reference it with the TI part number seen on this page.

Product Content Methodology

For an explanation of the methods used to determine material weights, See Product Content Methodology

Material Declaration Certificate for Semiconductor IC Packaged Products

TI certifies that the material content information provided by TI is representative and accurate to the best of their knowledge based on material information provided by its suppliers and their combination into finished IC packaged products. TI semiconductor products designated to be "Pb-free", "Green" or "RoHS Exempt" fully meets the latest EU RoHS Directive requirements along with other legislation as seen in the former JIG-101 list that has been transferred to the IEC 62474 database.

Important Information/Disclaimer

Ti bases its material content information on information provided by third-party suppliers and has taken, and continues to take, reasonably diligent steps to provide any required or available information. Ti may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. Ti and Ti suppliers may consider certain information to be proprietary, and thus certain information may not be available for release by Ti. The material content information is provided by Ti "as is."

For additional information, please contact TI customer support.

Signature: (click here for a fuller statement with a signed certificate).

Name/Title: Hubie Payne, Vice President, Worldwide SC Quality For further environmental statements, please go to www.ti.com/ecoinfo Created on: 05/09/2022

RoHS: Means TI semiconductor products that are compliant with the current RoHS requirement that the maximum concentration values of the ten substances listed in RoHS Annex II do not exceed 0.1 % by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI semiconductor products labeled as "RoHS Compliant" are suitable for use in specified lead-free processes. TI may also reference these types of semiconductor products as "Pb-Free." These TI semiconductor products are also fully compliant with GADSL and the IEC 62474 database for electronic requirements.

RoHS Exempt: Means TI semiconductor products that contain lead (Pb) above the RoHS Annex II threshold, but that fall within one of the specific RoHS exemptions noted above or documented in http://www.ti.com/lit/pdf/szzq088

Green: Means the content of Chlorine (Cl) and Bromine (Br)-based flame retardants meet JS709B low halogen requirements of <=1 000ppm threshold; Antimony trioxide (Sb203) contained in halogen based flame retardant materials meets the <=1 000ppm threshold requirement; and Beryllium Oxide (BeO) is <=1000ppm.