Texas Instruments Inc. (DUNS# 00-732-1904) Supplier Name:

Contact Info:

ti.com/support
Distribute - RoHS and IEC 62474 DB Form/Declaration Type:

06/04/2022

### Details for "OPA244UA/2K5"

### **Current Product Information**

TI part number	Lead finish/Ball material	MSL rating/peak reflow	Assembly site	Package   Pins	Package body size (mm)	Total device mass (mg)*
OPA244UA/2K5	NIPDAU	Level-3-260C-168 HR	TI MALAYSIA A/T	D   8	3.91x4.9x1.58	84.2

The summary mass is a rounded value and will be within approximately +/- 10% of the detailed mass value.

## **Environmental Ratings Information**

RoHS	REACH	Green	IEC 62474 DB
Yes	Yes	Yes	Yes

## **Component Information**

				Homogeneous Material Level		Component Level	
Component	Substance	CAS Number	Amount (mg)	Percentage %	ppm	Percentage %	ppm
Bond Wire							
Precious Metals	Gold	7440-57-5	0.089757	99.376661	993767	0.106647	1066
Precious Metals	Palladium	7440-05-3	0.000562	0.622232	6222	0.000668	7
Precious Metals	Silver	7440-22-4	0.000001	0.001107	11	0.000001	0
Sub-Total			0.09032	100	1000000	0.107316	1073
Die Attach Adhesive							
Other Inorganic Materials	Silica	7631-86-9	0.00545	2.000029	20000	0.006476	65
Precious Metals	Silver	7440-22-4	0.188022	68.999912	689999	0.223402	2234
Thermoplastics	Epoxy	85954-11-6	0.079024	29.000059	290001	0.093894	939
Sub-Total			0.272496	100	1000000	0.323772	3238
Lead Frame							
Copper and Its Alloys	Copper	7440-50-8	24.25509	97.41	974100	28.819167	288192
Copper and Its Alloys	Iron	7439-89-6	0.5976	2.4	24000	0.71005	7101
Copper and Its Alloys	Phosphorus	7723-14-0	0.00747	0.03	300	0.008876	89
Other Nonferrous Metals and Alloys	Lead	7439-92-1	0.00747	0.03	300	0.008876	89
Other Nonferrous Metals and Alloys	Tin	7440-31-5	0.00747	0.03	300	0.008876	89
Zinc and Its Alloys	Zinc	7440-66-6	0.0249	0.1	1000	0.029585	296
Sub-Total			24.9	100	1000000	29.58543	295854
Lead Frame Plating							
Nickel and Its Alloys	Nickel	7440-02-0	0.355273	95.119946	951199	0.422125	4221
Precious Metals	Gold	7440-57-5	0.002913	0.77992	7799	0.003461	35
Precious Metals	Palladium	7440-05-3	0.015314	4.100134	41001	0.018196	182
Sub-Total			0.3735	100	1000000	0.443781	4438
Mold Compound							
Other Inorganic Materials	Fused Silica	60676-86-0	49.566008	86	860000	58.892837	588928
Other Plastics and Rubber	Carbon Black	1333-86-4	0.172905	0.300001	3000	0.205441	2054
Other Plastics and Rubber	Organic Phosphorus	1330-78-5	0.316992	0.55	5500	0.37664	3766
Thermoplastics	Ероху	85954-11-6	7.578988	13.149999	131500	9.005125	90051
Sub-Total			57.634893	100	1000000	68.480043	684800
Semiconductor Device	·	•	·		·	•	
Ceramics / Glass	Doped Silicon	7440-21-3	0.891841	100	1000000	1.059659	10597
Sub-Total			0.891841	100	1000000	1.059659	10597
·							
Total			84.16305			100	1000000

## Important Note

The ppm calculations are at the homogeneous material level and are maximum concentration values. The ppm displayed represents the homogeneous material with the highest ppm

for that substance. The amount (mg) calculations represent the maximum total amount of each substance within the component.

The ppm calculations are at the component level and are average concentration values. The amount (mg) calculations represent the average total amount of each substance within the component. See Glossary of Terms for more details.

# Important Part Information

There is a remote possibility the Customer Part Number (CPN) your company uses could reference more than one TI part number. If this occurs, please check your Customer Part Number and cross reference it with the TI part number seen on this page.

Product Content Methodology
For an explanation of the methods used to determine material weights, See Product Content Methodology

## **Material Declaration Certificate for Semiconductor IC Packaged Products**

TI certifies that the material content information provided by TI is representative and accurate to the best of their knowledge based on material information provided by its suppliers and their combination into finished IC packaged products. TI semiconductor products designated to be "Pb-free", "Green" or "RoHS Exempt" fully meets the latest EU RoHS Directive requirements along with other legislation as seen in the former JIG-101 list that has been transferred to the IEC 62474 database.

Ti bases its material content information on information provided by third-party suppliers and has taken, and continues to take, reasonably diligent steps to provide any required or available information. Ti may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. Ti and Ti suppliers may consider certain information to be proprietary, and thus certain information may not be available for release by Ti. The material content information is provided by TI "as is."

For additional information, please contact TI customer support.

Signature: (click here for a fuller statement with a signed certificate)

Name/Title: Hubie Payne, Vice President, Worldwide SC Quality For further environmental statements, please go to www.ti.com/ecoinfo Created on: 06/04/2022

RoHS: Means TI semiconductor products that are compliant with the current RoHS requirement that the maximum concentration values of the ten substances listed in RoHS Annex II do not exceed 0.1 % by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI semiconductor products labeled as "RoHS Compliant" are suitable for use in specified lead-free processes. TI may also reference these types of semiconductor products as "Pb-Free." These TI semiconductor products are also fully compliant with GADSL and the IEC 62474 database for electronic requirements.

ROHS Exempt: Means TI semiconductor products that contain lead (Pb) above the RoHS Annex II threshold, but that fall within one of the specific RoHS exemptions noted above or documented in http://www.ti.com/lit/odf/szzg088

Green: Means the content of Chlorine (CI) and Bromine (Br)-based flame retardants meet JS709B low halogen requirements of <=1 000ppm threshold; Antimony trioxide (Sb203) contained in halogen based flame retardant materials meets the <=1 000ppm threshold requirement; and Beryllium Oxide (BeO) is <=1000ppm.