Texas Instruments Inc. (DUNS# 00-732-1904) Supplier Name:

Contact Info:

ti.com/support
Distribute - RoHS and IEC 62474 DB Form/Declaration Type:

06/05/2022

## Details for "REG101UA-A"

### **Current Product Information**

TI part number	Lead finish/Ball material	MSL rating/peak reflow	Assembly site	Package   Pins	Package body size (mm)	Total device mass (mg)*
REG101UA-A	NIPDAU	Level-2-260C-1 YFAR	TI MALAYSIA A/T	D   8	3.91x4.9x1.58	84.7

The summary mass is a rounded value and will be within approximately +/- 10% of the detailed mass value.

## **Environmental Ratings Information**

RoHS	REACH	Green	IEC 62474 DB
Yes	Yes	Yes	Yes

## **Component Information**

	Substance			Homogeneous Material Level		Component Level	
Component		CAS Number	Amount (mg)	Percentage %	ppm	Percentage %	ppm
Bond Wire							
Other Nonferrous Metals and Alloys	Yttrium	7440-65-5	0.000001	0.00101	10	0.000001	0
Precious Metals	Gold	7440-57-5	0.098965	99.997979	999980	0.11679	1168
Precious Metals	Silver	7440-22-4	0.000001	0.00101	10	0.000001	
Sub-Total			0.098967	100	1000000	0.116793	1168
Die Attach Adhesive							
Precious Metals	Silver	7440-22-4	0.210446	79.999848	799998	0.248351	2484
Thermoplastics	Epoxy	85954-11-6	0.052612	20.000152	200002	0.062088	621
Sub-Total			0.263058	100	1000000	0.31044	3104
Lead Frame							
Copper and Its Alloys	Copper	7440-50-8	24.25509	97.41	974100	28.62388	286239
Copper and Its Alloys	Iron	7439-89-6	0.5976	2.4	24000	0.705239	7052
Copper and Its Alloys	Phosphorus	7723-14-0	0.00747	0.03	300	0.008815	88
Other Nonferrous Metals and Alloys	Lead	7439-92-1	0.00747	0.03	300	0.008815	88
Other Nonferrous Metals and Alloys	Tin	7440-31-5	0.00747	0.03	300	0.008815	88
Zinc and Its Alloys	Zinc	7440-66-6	0.0249	0.1	1000	0.029385	294
Sub-Total			24.9	100	1000000	29.38495	293850
Lead Frame Plating							
Nickel and Its Alloys	Nickel	7440-02-0	0.355273	95.119946	951199	0.419264	4193
Precious Metals	Gold	7440-57-5	0.002913	0.77992	7799	0.003438	34
Precious Metals	Palladium	7440-05-3	0.015314	4.100134	41001	0.018072	181
Sub-Total			0.3735	100	1000000	0.440774	4408
Mold Compound	•	•	•		•	•	
Other Inorganic Materials	Fused Silica	60676-86-0	51.252736	87.999999	880000	60.484301	604843
Other Plastics and Rubber	Carbon Black	1333-86-4	0.174725	0.3	3000	0.206196	2062
Other Plastics and Rubber	Organic Phosphorus	1330-78-5	0.32033	0.550001	5500	0.378027	3780
Thermoplastics	Ероху	85954-11-6	6.493955	11.150001	111500	7.663636	76636
Sub-Total			58.241746	100	1000000	68.732161	687322
Semiconductor Device				•			
Ceramics / Glass	Doped Silicon	7440-21-3	0.859983	100	1000000	1.014882	10149
Sub-Total			0.859983	100	1000000	1.014882	10149
Total			84.737254			100	1000000

The ppm calculations are at the homogeneous material level and are maximum concentration values. The ppm displayed represents the homogeneous material with the highest ppm for that substance. The amount (mg) calculations represent the maximum total amount of each substance within the component.

The ppm calculations are at the component level and are average concentration values. The amount (mg) calculations represent the average total amount of each substance within the component.

See Glossary of Terms for more details.

There is a remote possibility the Customer Part Number (CPN) your company uses could reference more than one TI part number. This is due to two or more users (EMSIs or subcontractors) using the same CPN for different TI part numbers. If this occurs, please check your Customer Part Number and cross reference it with the TI part number seen on this page.

# **Product Content Methodology**

For an explanation of the methods used to determine material weights, See Product Content Methodology

## Material Declaration Certificate for Semiconductor IC Packaged Products

TI certifies that the material content information provided by TI is representative and accurate to the best of their knowledge based on material information provided by its suppliers and their combination into finished IC packaged products. TI semiconductor products designated to be "Pb-free", "Green" or "RoHS Exempt" fully meets the latest EU RoHS Directive requirements along with other legislation as seen in the former JIG-101 list that has been transferred to the IEC 62474 database.

# Important Information/Disclaimer

Tibases its material content information on information provided by third-party suppliers and has taken, and continues to take, reasonably diligent steps to provide any required or available information. TI may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. Tl and Tl suppliers may consider certain information to be proprietary, and thus certain information may not be available for release by Tl. The material content information is

For additional information, please contact TI customer support.

Signature: (click here for a fuller statement with a signed certificate)

Name/Title: Hubie Payne, Vice President, Worldwide SC Quality For further environmental statements, please go to www.ti.com/ecoinfo Created on: 06/05/2022

ROHS: Means TI semiconductor products that are compliant with the current ROHS requirement that the maximum concentration values of the ten substances listed in ROHS Annex II do not exceed 0.1 % by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI semiconductor products labeled as "RoHS Compliant" are suitable for use in specified lead-free processes. TI may also reference these types of semiconductor products as "Pb-Free." These TI semiconductor products are also fully compliant with GADSL and the IEC 62474 database for electronic requirements.

RoHS Exempt: Means TI semiconductor products that contain lead (Pb) above the RoHS Annex II threshold, but that fall within one of the specific RoHS exemptions noted above or documented in http://www.ti.com/lit/pdf/szzq088

Green: Means the content of Chlorine (CI) and Bromine (Br)-based flame retardants meet JS709B low halogen requirements of <=1 000ppm threshold; Antimony trioxide (5b203) contained in halogen based flame retardant materials meets the <=1 000ppm threshold requirement; and Beryllium Oxide (BeO) is <=1000ppm.